PHILIPPINE BIDDING DOCUMENTS

Procurement of GOODS

Government of the Republic of the Philippines

FOR Project 2025-1E: Supply and Delivery of Various Laboratory Equipment and Machinery for the University

Sixth Edition July 2020

Preface

These Philippine Bidding Documents (PBDs) for the procurement of Goods through Competitive Bidding have been prepared by the Government of the Philippines for use by any branch, constitutional commission or office, agency, department, bureau, office, or instrumentality of the Government of the Philippines, National Government Agencies, including Government-Owned and/or Controlled Corporations, Government Financing Institutions, State Universities and Colleges, and Local Government Unit. The procedures and practices presented in this document have been developed through broad experience, and are for mandatory use in projects that are financed in whole or in part by the Government of the Philippines or any foreign government/foreign or international financing institution in accordance with the provisions of the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184.

The Bidding Documents shall clearly and adequately define, among others: (i) the objectives, scope, and expected outputs and/or results of the proposed contract or Framework Agreement, as the case may be; (ii) the eligibility requirements of Bidders; (iii) the expected contract or Framework Agreement duration, the estimated quantity in the case of procurement of goods, delivery schedule and/or time frame; and (iv) the obligations, duties, and/or functions of the winning bidder.

Care should be taken to check the relevance of the provisions of the PBDs against the requirements of the specific Goods to be procured. If duplication of a subject is inevitable in other sections of the document prepared by the Procuring Entity, care must be exercised to avoid contradictions between clauses dealing with the same matter.

Moreover, each section is prepared with notes intended only as information for the Procuring Entity or the person drafting the Bidding Documents. They shall not be included in the final documents. The following general directions should be observed when using the documents:

- a. All the documents listed in the Table of Contents are normally required for the procurement of Goods. However, they should be adapted as necessary to the circumstances of the particular Procurement Project.
- b. Specific details, such as the "name of the Procuring Entity" and "address for bid submission," should be furnished in the Instructions to Bidders, Bid Data Sheet, and Special Conditions of Contract. The final documents should contain neither blank spaces nor options.
- c. This Preface and the footnotes or notes in italics included in the Invitation to Bid, Bid Data Sheet, General Conditions of Contract, Special Conditions of Contract, Schedule of Requirements, and Specifications are not part of the text of the final document, although they contain instructions that the Procuring Entity should strictly follow.

- d. The cover should be modified as required to identify the Bidding Documents as to the Procurement Project, Project Identification Number, and Procuring Entity, in addition to the date of issue.
- e. Modifications for specific Procurement Project details should be provided in the Special Conditions of Contract as amendments to the Conditions of Contract. For easy completion, whenever reference has to be made to specific clauses in the Bid Data Sheet or Special Conditions of Contract, these terms shall be printed in bold typeface on Sections I (Instructions to Bidders) and III (General Conditions of Contract), respectively.
- f. For guidelines on the use of Bidding Forms and the procurement of ForeignAssisted Projects, these will be covered by a separate issuance of the Government Procurement Policy Board.

Table of Contents

Glossary of Acronyms, Terms, and Abbreviations	
Section I. Invitation to Bid	
Section II. Instructions to Bidders	10
1. Scope of Bid	11
2. Funding Information	
3. Bidding Requirements	11
4. Corrupt, Fraudulent, Collusive, and Coercive Practices	12
5. Eligible Bidders	12
6. Origin of Goods	13
7. Subcontracts	13
8. Pre-Bid Conference	14
9. Clarification and Amendment of Bidding Documents	14
10. Documents comprising the Bid: Eligibility and Technical Components	14
11. Documents comprising the Bid: Financial Component	15
12. Bid Prices	
13. Bid and Payment Currencies	16
14. Bid Security	
15. Sealing and Marking of Bids	17
16. Deadline for Submission of Bids	17
17. Opening and Preliminary Examination of Bids	18
18. Domestic Preference	
19. Detailed Evaluation and Comparison of Bids	18
20. Post-Qualification	
21. Signing of the Contract	
Section III. Bid Data Sheet	
Section IV. General Conditions of Contract	
1. Scope of Contract	
2. Advance Payment and Terms of Payment	50
3. Performance Security	
4. Inspection and Tests	51
5. Warranty	
6. Liability of the Supplier	
Section V. Special Conditions of Contract	
Section VI. Schedule of Requirements	
Section VII. Technical Specifications	
Section VIII. Checklist of Technical and Financial Documents	

Glossary of Acronyms, Terms, and Abbreviations

ABC – Approved Budget for the Contract.

BAC – Bids and Awards Committee.

Bid – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*. (2016 revised IRR, Section 5[c])

Bidder – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

Bidding Documents – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

BIR – Bureau of Internal Revenue.

BSP – Bangko Sentral ng Pilipinas.

Consulting Services – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to: (i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

CDA - Cooperative Development Authority.

Contract – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

CIF – Cost Insurance and Freight.

CIP – Carriage and Insurance Paid.

CPI – Consumer Price Index.

DDP – Refers to the quoted price of the Goods, which means "delivered duty paid."

DTI – Department of Trade and Industry.

EXW – Ex works.

FCA – "Free Carrier" shipping point.

FOB – "Free on Board" shipping point.

Foreign-funded Procurement or Foreign-Assisted Project— Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR, Section 5[b]).

Framework Agreement – Refers to a written agreement between a procuring entity and a supplier or service provider that identifies the terms and conditions, under which specific purchases, otherwise known as "Call-Offs," are made for the duration of the agreement. It is in the nature of an option contract between the procuring entity and the bidder(s) granting the procuring entity the option to either place an order for any of the goods or services identified in the Framework Agreement List or not buy at all, within a minimum period of one (1) year to a maximum period of three (3) years. (GPPB Resolution No. 27-2019)

GFI – Government Financial Institution.

GOCC – Government-owned and/or –controlled corporation.

Goods – Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term "related" or "analogous services" shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

GOP – Government of the Philippines.

GPPB – Government Procurement Policy Board.

INCOTERMS – International Commercial Terms.

Infrastructure Projects – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as *civil works or works*. (2016 revised IRR, Section 5[u])

LGUs – Local Government Units.

NFCC – Net Financial Contracting Capacity.

NGA – National Government Agency.

PhilGEPS - Philippine Government Electronic Procurement System.

Procurement Project – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

PSA – Philippine Statistics Authority.

SEC – Securities and Exchange Commission.

SLCC – Single Largest Completed Contract.

Supplier – refers to a citizen, or any corporate body or commercial company duly organized and registered under the laws where it is established, habitually established in business and engaged in the manufacture or sale of the merchandise or performance of the general services covered by his bid. (Item 3.8 of GPPB Resolution No. 13-2019, dated 23 May 2019). Supplier as used in these Bidding Documents may likewise refer to a distributor, manufacturer, contractor, or consultant.

UN – United Nations.

Section I. Invitation to Bid

Notes on the Invitation to Bid

The Invitation to Bid (IB) provides information that enables potential Bidders to decide whether to participate in the procurement at hand. The IB shall be posted in accordance with Section 21.2 of the 2016 revised IRR of RA No. 9184.

Apart from the essential items listed in the Bidding Documents, the IB should also indicate the following:

- a. The date of availability of the Bidding Documents, which shall be from the time the IB is first advertised/posted until the deadline for the submission and receipt of bids;
- b. The place where the Bidding Documents may be acquired or the website where it may be downloaded;
- c. The deadline for the submission and receipt of bids; and
- d. Any important bid evaluation criteria (*e.g.*, the application of a margin of preference in bid evaluation).

The IB should be incorporated in the Bidding Documents. The information contained in the IB must conform to the Bidding Documents and in particular to the relevant information in the Bid Data Sheet.



Republic of the Philippines NUEVA VIZCAYA STATE UNIVERSITY

Bayombong, Nueva Vizcaya

INVITATION TO BID

FOR Project 2025-1E: Supply and Delivery of Various Laboratory Equipment and Machinery for the University

- 1. The *Nueva Vizcaya State University*, through *F101 FY 2025* intends to apply the sum of *Php10,184,886.92* being the ABC to payments under the contract for *Project 2025-1E: Supply and Delivery of Various Laboratory Equipment and Machinery for the University* Bids received in excess of the ABC shall be automatically rejected at bid opening.
- 2. The *NVSU* now invites bids for the above Procurement Project. Delivery of the Goods/Equipment is required by *thirty* (30) *calendar days*. Bidders should have completed, within *two* (02) *years* from the date of submission and receipt of bids, a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II (Instructions to Bidders).
- 3. Bidding will be conducted through open competitive bidding procedures using a nondiscretionary "pass/fail" criterion as specified in the 2016 revised Implementing Rules and Regulations (IRR) of Republic Act (RA) No. 9184.

Bidding is restricted to Filipino citizens/sole proprietorships, partnerships, or organizations with at least sixty percent (60%) interest or outstanding capital stock belonging to citizens of the Philippines, and to citizens or organizations of a country the laws or regulations of which grant similar rights or privileges to Filipino citizens, pursuant to RA No. 5183.

- 4. Prospective Bidders may obtain further information from *NVSU-BAC* and inspect the Bidding Documents at the address given below during *Mondays-Fridays from 8:00AM to 5:00PM*.
- 5. A complete set of Bidding Documents may be acquired by interested Bidders starting on *December 5*, 2024 from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of Php25,000.00. The Procuring Entity shall allow the bidder to present its proof of payment for the fees through electronic means.

NVSU LANDBANK ACCOUNT No.: 0432-1028-82

6. The NVSU will hold a Pre-Bid Conference¹ on December 13, 2024, 9:00 AM at the Board Room, 3F New Administration Building, NVSU Bayombong Campus through video conferencing/webcasting via **ZOOM** (Meeting ID: 525 793 2135 Passcode: nvsu@2024) which shall be open to prospective bidders.

¹ May be deleted in case the ABC is less than One Million Pesos (PhP1,000,000) where the Procuring Entity may not hold a Pre-Bid Conference.

- 7. Bids must be duly received by the BAC Secretariat through manual submission at the office address indicated below on or before December 26, 2024, at 8:59 am or courier submission at the same address on or before December 23, 2024, at 5:00 pm. Late bids shall not be accepted.
- 8. All Bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in ITB Clause 14.
- 9. Bid opening shall be on *December 26*, 2024, at 9:00 am at the given address and via **ZOOM** (Meeting ID: 525 793 2135 Passcode: nvsu@2024) Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.
- 10. The Nueva Vizcaya State University reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.
- 11. For further information, please refer to:

MARITESS MORTERA **MARY JANE TIME** MARY JANE DULINAYAN ARSHIELA MANUEL SHERYL CAROLINE FONTANILLA **DENNYLAINE IBASCO** VIVIAN ALMENDRA **NORBERT JOHN ESPIRITU**

UBAC Secretariat

3rd floor UBAC Office, New Administration Building NVSU Bayombong Campus, Bayombong, Nueva Vizcaya Tel. No. 078-392-1605/078-321-2112

Email Address: bac.equipment@nvsu.edu.ph

12. You may visit the website:

For downloading of Bidding Documents: www.nvsu.edu.ph December 5, 2024

UBAC Chairperson, Equipment

Section II. Instructions to Bidders

Notes on the Instructions to Bidders

This Section on the Instruction to Bidders (ITB) provides the information necessary for bidders to prepare responsive bids, in accordance with the requirements of the Procuring Entity. It also provides information on bid submission, eligibility check, opening and evaluation of bids, post-qualification, and on the award of contract.

1. Scope of Bid

The Procuring Entity, Nueva Vizcaya State University, wishes to receive Bids for *Project* 2025-1E: Supply and Delivery of Various Laboratory Equipment and Machinery for the University [insert, if applicable:] under a Framework Agreement}, with identification number [indicate number].

[Note: The Project Identification Number is assigned by the Procuring Entity based on its own coding scheme and is not the same as the PhilGEPS reference number, which is generated after the posting of the bid opportunity on the PhilGEPS website.]

The Procurement Project referred to herein as *Project 2025-1E: Supply and Delivery of Various Laboratory Equipment and Machinery for the University*. is composed of *sixty* (60) item/s, the details of which are described in Section VII (Technical Specifications).

2. Funding Information

2.1. The GOP through the source of funding as indicated below for Fund 101 FY2025 [indicate funding year] in the amount of Ten Million One Hundred Eighty-Four Thousand Eight Hundred Eighty-six pesos and 92/100 (Php10,184,886.92) [indicate amount].

2.2. The source of funding is: F101

[If an early procurement activity, select one and delete others:]

- a. NGA, the National Expenditure Program.
- b. GOCC and GFIs, the proposed Corporate Operating Budget.
- c. LGUs, the proposed Local Expenditure Program.

[If not an early procurement activity, select one and delete others:]

- a. NGA, the General Appropriations Act or Special Appropriations.
- b. GOCC and GFIs, the Corporate Operating Budget.
- c. LGUs, the Annual or Supplemental Budget, as approved by the Sanggunian.

3. Bidding Requirements

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manuals and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or **IB** by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have verified and accepted the general requirements of this Project, including other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and examine all instructions, forms, terms, and project requirements in the Bidding Documents.

4. Corrupt, Fraudulent, Collusive, and Coercive Practices

The Procuring Entity, as well as the Bidders and Suppliers, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex "I" of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

5. Eligible Bidders

- 5.1. Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.
- 5.2. [Select one, delete other/s]
 - a. Foreign ownership exceeding those allowed under the rules may participate pursuant to:
 - i. When a Treaty or International or Executive Agreement as provided in Section 4 of the RA No. 9184 and its 2016 revised IRR allow foreign bidders to participate;
 - ii. Citizens, corporations, or associations of a country, included in the list issued by the GPPB, the laws or regulations of which grant reciprocal rights or privileges to citizens, corporations, or associations of the Philippines;
 - iii. When the Goods sought to be procured are not available from local suppliers; or
 - iv. When there is a need to prevent situations that defeat competition or restrain trade.
 - b. Foreign ownership limited to those allowed under the rules may participate in this Project.

5.3. Pursuant to Section 23.4.1.3 of the 2016 revised IRR of RA No.9184, the Bidder shall have an SLCC that is at least one (1) contract similar to the Project the value of which, adjusted to current prices using the PSA's CPI, must be at least equivalent to:

[Select one, delete the other/s]

- a. For the procurement of Non-expendable Supplies and Services: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least fifty percent (50%) of the ABC.
- b. For the procurement of Expendable Supplies: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least twenty-five percent (25%) of the ABC.
- c. For procurement where the Procuring Entity has determined, after the conduct of market research, that imposition of either (a) or (b) will likely result to failure of bidding or monopoly that will defeat the purpose of public bidding: the Bidder should comply with the following requirements: [Select either failure or monopoly of bidding based on market research conducted]
 - i. Completed at least two (2) similar contracts, the aggregate amount of which should be equivalent to at least fifty percent (50%) in the case of non-expendable supplies and services or twenty-five percent (25%) in the case of expendable supplies] of the ABC for this Project; and
 - ii. The largest of these similar contracts must be equivalent to at least half of the percentage of the ABC as required above.
- 5.4. The Bidders shall comply with the eligibility criteria under Section 23.4.1 of the 2016 IRR of RA No. 9184.

6. Origin of Goods

There is no restriction on the origin of goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN, subject to Domestic Preference requirements under **ITB** Clause 18.

7. Subcontracts

7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than twenty percent (20%) of the Project.

The Procuring Entity has prescribed that:

- a. Subcontracting is allowed. The portions of Project and the maximum percentage allowed to be subcontracted are indicated in the **BDS**, which shall not exceed twenty percent (20%) of the contracted Goods.
- b. Subcontracting is not allowed.
- 7.2. [If Procuring Entity has determined that subcontracting is allowed during the bidding, state:] The Bidder must submit together with its Bid the documentary requirements of the subcontractor(s) complying with the eligibility criteria stated in ITB Clause 5 in accordance with Section 23.4 of the 2016 revised IRR of RA No. 9184 pursuant to Section 23.1 thereof.
- 7.3. [If subcontracting is allowed during the contract implementation stage, state:] The Supplier may identify its subcontractor during the contract implementation stage. Subcontractors identified during the bidding may be changed during the implementation of this Contract. Subcontractors must submit the documentary requirements under Section 23.1 of the 2016 revised IRR of RA No. 9184 and comply with the eligibility criteria specified in ITB Clause 5 to the implementing or end-user unit.
- 7.4. Subcontracting of any portion of the Project does not relieve the Supplier of any liability or obligation under the Contract. The Supplier will be responsible for the acts, defaults, and negligence of any subcontractor, its agents, servants, or workmen as fully as if these were the Supplier's own acts, defaults, or negligence, or those of its agents, servants, or workmen.

8. Pre-Bid Conference

The Procuring Entity will hold a pre-bid conference for this Project on the specified date and time and either at its physical address { [insert if applicable] and/or through videoconferencing/webcasting} as indicated in paragraph 6 of the **IB**.

9. Clarification and Amendment of Bidding Documents

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the **IB**, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids

10. Documents comprising the Bid: Eligibility and Technical Components

- 10.1. The first envelope shall contain the eligibility and technical documents of the Bid as specified in **Section VIII** (Checklist of Technical and Financial **Documents**).
- 10.2. The Bidder's SLCC as indicated in **ITB** Clause 5.3 should have been completed within [state relevant period as provided in paragraph 2 of the **IB**] prior to the deadline for the submission and receipt of bids.

10.3. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. Similar to the required authentication above, for Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.

11. Documents comprising the Bid: Financial Component

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in **Section VIII** (Checklist of Technical and Financial Documents).
- 11.2. If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification issued by DTI shall be provided by the Bidder in accordance with Section 43.1.3 of the 2016 revised IRR of RA No. 9184.
- 11.3. Any bid exceeding the ABC indicated in paragraph 1 of the **IB** shall not be accepted.
- 11.4. For Foreign-funded Procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.
- 11.5. [Include if Framework Agreement will be used:] Financial proposals for single or multi-year Framework Agreement shall be submitted before the deadline of submission of bids as prescribed in the **IB**. For multi-year Framework Agreement, evaluation of the financial proposal during this stage is for purposes of determining eligibility and whether or not such financial proposal is within the ABC.

12. Bid Prices

- 12.1. Prices indicated on the Price Schedule shall be entered separately in the following manner:
 - a. For Goods offered from within the Procuring Entity's country:
 - i. The price of the Goods quoted EXW (ex-works, ex-factory, exwarehouse, ex-showroom, or off-the-shelf, as applicable);
 - ii. The cost of all customs duties and sales and other taxes already paid or payable;

- iii. The cost of transportation, insurance, and other costs incidental to delivery of the Goods to their final destination; and
- iv. The price of other (incidental) services, if any, listed in e.
- b. For Goods offered from abroad:
 - i. Unless otherwise stated in the **BDS**, the price of the Goods shall be quoted delivered duty paid (DDP) with the place of destination in the Philippines as specified in the **BDS**. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
 - ii. The price of other (incidental) services, if any, as listed in **Section VII (Technical Specifications).**
- 12.2. [Include if Framework Agreement will be used:] For Framework Agreement, the following should also apply in addition to Clause 12.1:
 - a. For a single year Framework Agreement, the prices quoted by the Bidder shall be fixed during the Bidder's performance of the contract and not subject to variation or escalation on any account. Price schedules required under Clause 12.1 shall be submitted with the bidding documents.
 - b. For a multi-year Framework Agreement, the prices quoted by the Bidder during submission of eligibility documents shall be the ceiling and the price quoted during mini-competition must not exceed the initial price offer. The price quoted during call for mini-competition shall be fixed during the Bidder's performance of that Call-off and not subject to variation or escalation on any account. Price schedules required under Clause 12.1 shall be submitted with the bidding documents.

13. Bid and Payment Currencies

- 13.1. For Goods that the Bidder will supply from outside the Philippines, the bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies, shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 13.2. Payment of the contract price shall be made in:

[Select one, delete the other/s]

- a. Philippine Pesos.
- b. [indicate currency if procurement involves a foreign-denominated bid as allowed by the Procuring Entity, which shall be tradeable or acceptable by the BSP].

14. Bid Security

- 14.1. The Bidder shall submit a Bid Securing Declaration² or any form of Bid Security in the amount indicated in the **BDS**, which shall be not less than the percentage of the ABC in accordance with the schedule in the **BDS**.
- 14.2. The Bid and bid security shall be valid until [indicate date]. Any Bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.
- 14.3. [Include if Framework Agreement will be used:] In the case of Framework Agreement, other than the grounds for forfeiture under the 2016 revised IRR, the bid security may also be forfeited if the successful bidder fails to sign the Framework Agreement, or fails to furnish the performance security or performance securing declaration. Without prejudice on its forfeiture, bid securities shall be returned only after the posting of performance security or performance securing declaration, as the case may be, by the winning Bidder or compliant Bidders and the signing of the Framework Agreement.

15. Sealing and Marking of Bids

Each Bidder shall submit one copy of the first and second components of its Bid.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

If the Procuring Entity allows the submission of bids through online submission or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

16. Deadline for Submission of Bids

16.1. The Bidders shall submit on the specified date and time and either at its physical address or through online submission as indicated in paragraph 7 of the **IB**.

² In the case of Framework Agreement, the undertaking shall refer to entering into contract with the Procuring Entity and furnishing of the performance security or the performance securing declaration within ten (10) calendar days from receipt of Notice to Execute Framework Agreement.

16.2. [Include if Framework Agreement will be used:] For multi-year Framework Agreement, the submission of bids shall be for the initial evaluation of their technical and financial eligibility. Thereafter, those declared eligible during the said initial eligibility evaluation and entered into a Framework Agreement with the Procuring Entity shall submit anew their best financial offer at the address and on or before the date and time indicated in the Call for each minicompetition.

17. Opening and Preliminary Examination of Bids

17.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the **IB**. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.

In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.

17.2. The preliminary examination of bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

18. Domestic Preference

- 18.1. The Procuring Entity will grant a margin of preference for the purpose of comparison of Bids in accordance with Section 43.1.2 of the 2016 revised IRR of RA No. 9184.
- 18.2. [Include if Framework Agreement will be used:] For multi-year Framework Agreement, determination of margin of preference shall be conducted every call for Mini-Competition.

19. Detailed Evaluation and Comparison of Bids

19.1. The Procuring BAC shall immediately conduct a detailed evaluation of all Bids rated "passed," using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of the 2016 revised IRR of RA No. 9184.

[Include the following options if Framework Agreement will be used:]

- a. In the case of single-year Framework Agreement, the Lowest Calculated Bid shall be determined outright after the detailed evaluation;
- b. For multi-year Framework Agreement, the determination of the eligibility and the compliance of bidders with the technical and financial aspects of

the projects shall be initially made by the BAC, in accordance with Item 7.4.2 of the Guidelines on the Use of Framework Agreement.

- 19.2. If the Project allows partial bids, bidders may submit a proposal on any of the lots or items, and evaluation will be undertaken on a per lot or item basis, as the case maybe. In this case, the Bid Security as required by **ITB** Clause 15 shall be submitted for each lot or item separately.
- 19.3. The descriptions of the lots or items shall be indicated in **Section VII** (**Technical Specifications**), although the ABCs of these lots or items are indicated in the **BDS** for purposes of the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184. The NFCC must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder.
- 19.4. The Project shall be awarded as follows:

[Select one, delete the other/s]

Option 1 – One Project having several items that shall be awarded as one contract.

Option 2 – One Project having several items grouped into several lots, which shall be awarded as separate contracts per lot.

Option 3 - One Project having several items, which shall be awarded as separate contracts per item.

[Delete Options 2 and 3 if Framework Agreement will be used.]

19.5. Except for bidders submitting a committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation, all Bids must include the NFCC computation pursuant to Section 23.4.1.4 of the 2016 revised IRR of RA No. 9184, which must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder. For bidders submitting the committed Line of Credit, it must be at least equal to ten percent (10%) of the ABCs for all the lots or items participated in by the prospective Bidder.

20. Post-Qualification

20.1. [Include if Framework Agreement will be used:] For multi-year Framework Agreement, all bidders initially determined to be eligible and financially compliant shall be subject to initial post-qualification. The BAC shall then recommend the execution of a Framework Agreement among all eligible, technically and financially compliant bidders and the Procuring Entity and shall be issued by HoPE a Notice to Execute Framework Agreement. The determination of the Lowest Calculated Bid (LCB) shall not be performed by the BAC until a Mini-Competition is conducted among the bidders who

- executed a Framework Agreement. When a Call for Mini-Competition is made, the BAC shall allow the bidders to submit their best financial proposals on such pre-scheduled date, time and place to determine the bidder with the LCB.
- 20.2. Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, {[Include if Framework Agreement will be used:] or in the case of multi-year Framework Agreement, that it is one of the eligible bidders who have submitted bids that are found to be technically and financially compliant,}the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the BDS. {[Include if Framework Agreement will be used:] For every mini-competition in Framework Agreement, the LCB shall likewise submit the required documents for final Post Qualification.}

21. Signing of the Contract

21.1. The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the **BDS**.

[Include the following clauses if Framework Agreement will be used:]

- 21.2. At the same time as the Procuring Entity notifies the successful Bidder that its bid has been accepted, the Procuring Entity shall send the Framework Agreement Form to the Bidder, which contract has been provided in the Bidding Documents, incorporating therein all agreements between the parties.
- 21.3. Within ten (10) calendar days from receipt of the Notice to Execute Framework Agreement with the Procuring Entity, the successful Bidder or its duly authorized representative shall formally enter into a Framework Agreement with the procuring entity for an amount of One Peso to be paid to the procuring entity as a consideration for the option granted by the procuring entity to procure the items in the Framework Agreement List when the need arises.
- 21.4. The Procuring Entity shall enter into a Framework Agreement with the successful Bidder within the same ten (10) calendar day period provided that all the documentary requirements are complied with.
- 21.5. The following documents shall form part of the Framework Agreement:
 - a. Framework Agreement Form;
 - b. Bidding Documents;
 - c. Call-offs;
 - d. Winning bidder's bid, including the Technical and Financial Proposals, and all other documents/statements submitted (e.g., bidder's response to

- request for clarifications on the bid), including corrections to the bid, if any, resulting from the Procuring Entity's bid evaluation;
- e. Performance Security or Performance Securing Declaration, as the case may be;
- f. Notice to Execute Framework Agreement; and
- g. Other contract documents that may be required by existing laws and/or specified in the **BDS**.

Section III. Bid Data Sheet

Notes on the Bid Data Sheet

The Bid Data Sheet (BDS) consists of provisions that supplement, amend, or specify in detail, information, or requirements included in the ITB found in Section II, which are specific to each procurement.

This Section is intended to assist the Procuring Entity in providing the specific information in relation to corresponding clauses in the ITB and has to be prepared for each specific procurement.

The Procuring Entity should specify in the BDS information and requirements specific to the circumstances of the Procuring Entity, the processing of the procurement, and the bid evaluation criteria that will apply to the Bids. In preparing the BDS, the following aspects should be checked:

- a. Information that specifies and complements provisions of the ITB must be incorporated.
- b. Amendments and/or supplements, if any, to provisions of the ITB as necessitated by the circumstances of the specific procurement, must also be incorporated.

Bid Data Sheet

ITB Clause						
5.3	For this purpose, contracts similar to the Project shall be:					
	a. [provide the definition or description o	of simile	ar contracts].		
		ompleted within two (2) years prior to eceipt of bids.	the de	adline for the su	ibmission and	
7.1	- 1 00	the portions of Goods to be subcontra- ial component of the Project as determ			0 0	
	Not app	icable				
12	The pric	e of the Goods shall be quoted in Phil	ippine _l	peso.		
14.1		security shall be in the form of a Biog forms and amounts:	d Secur	ing Declaration	, or any of the	
	a. The amount of not less than Two Hundred Three Thousand Six Hundred Ninety-seven pesos and 74/100 only (Php203,697.74) [Indicate the amount equivalent to two percent (2%) of ABC], if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or					
	1	The amount of not less than Five Hu Forty-Four Pesos and 35/100 only (1 Equivalent to five percent (5%) of ABC	Php509,	244.35) [Indica	te the amount	
19.3	[In case the Project will be awarded by lot, list the grouping of lots by specifying the group title, items, and the quantity for every identified lot, and the corresponding ABC for each lot.]					
	[In case the project will be awarded by item, list each item indicating its quantity and ABC.]					
	Item No.	Particulars	Qty	Unit Cost	Total Cost	
		AUTOCLAVE, Laboratory Autoclave Class N autoclave sterilizer, vertical type volume: 100L	1	50,000.00	50,000.00	
	1.	Bolted digital display automatic control Sterilization temperature: 116 to 134C Design pressure: 0.25 Mpa				

		Automatic protection function			
		Automatic protection function			
		With manufacturer's warranty			
		CABINET, Dimensions: 465 X 620 X	1	50,000.00	50,000.00
		1300			
		A durable 2 drawer steel filing cabinet			
		able to hold either A4 suspension or			
		foolscap hanging files			
	2.	40kg loading capacity			
		Fully lockable			
		Anti-tilt mechanism			
		100% drawer extension on smooth			
		runners			
		With manufacturer's warranty	1	67,000,00	65,000,00
		CABINET, Filing Cabinet Black- Brown/Light Brown	1	65,000.00	65,000.00
		Wood type			
		Depth: 37 cm (14 5/8 ")			
		Height: 198 cm (78 ")			
	3.	Width: 270 cm (106 1/4 ")			
		Bookcase			
		Glass			
		Glass-door cabinet with 3 drawers			
		With manufacturer's warranty			
		CABINET, Laminar Flow cabinet	2	80,000.00	160,000.00
		ULPA Filter			
		ISO Class 3 work zone			
		DC ECM blower for up to 70 percent			
		energy savings			
	4.	Low noise at 55.8 dBA			
	4.	Glass side walls			
		Fixed Sash			
		Internal height: 2.50 ft			
		Available sizes: 6ft			
		W/d C			
		With manufacturer's warranty	1	154 000 00	154,000.00
		DRILL, Radial drill press 220V, 4 KW, spindle rpm 1150,	1	154,000.00	134,000.00
		spindle travel 420 mm, spindle feeding			
	5.	step16, spindle taper MT5, distance			
		from spindle axis to column 350-1650			
		With manufacturer's warranty			
		ENGINE, Hybrid Engine,	1	229,274.32	229,274.32
	6.	Engine Code: A25A Complete Engine	•	,	

	Fuel: Gasoline			1
	Doors: 5			
	Mileage: 83979			
	Power: 218CV / 160KW			
	With manufacturer's warranty			
	FLOOR POLISHER, 16 IN. Heavy	4	53,678.90	214,715.60
	Duty with brush and			
<i>7</i> .	Bracket, 230 Volts			
	With manufacturer's warranty			
	GENERATOR, Silent type diesel	3	79,637.50	238,912.50
	generator			
	Rated voltage V:220-240			
	Rated frequency Hz:60			
	Phase: Single			
	Max output kW :9.5			
	Rated output kW:8.5			
8.	Power Factor:1			
	Rated speed rpm :3600			
	Fuel tank L:26			
	Net weight Kg :280kg			
	Cooling system: Air cooled			
	Starting system: Electric with			
	maintenance free battery			
	W. d			
	With manufacturer's warranty	2	70,000,00	140,000,00
	INCUBATOR, Laboratory Incubator Ventiflow Ventilation System:	2	70,000.00	140,000.00
	,			
	Forced air convection design			
	Pre-heat Chamber Technology: 4-zone			
	heated air jacket			
	Smart Sense Microprocessor PID			
9.	Control Technology			
<i>J</i> .	DIN 12880 Class 3.1 Certified for			
	Temperature Safety			
	Electrogalvanized steel body construction			
	Audible and visual alarms			
	Available volume: 110L			
	Available volume, 110L			
	With manufacturer's warranty			
	with manufacturer 8 warranty			

LABORATORY EQUIPMENT, 1 90,000.00 90,000.00 Automatic Feed Pelletizer Machine, Output Capacity: 150-180 kg/h Dimension (LxWxH): 38 x 12 x 26 inches Voltage: 220-240 v Motor power: 5 HP Die hole specification: 6 mm Material: Durable metal Emergency stop: Yes
150-180 kg/h Dimension (LxWxH): 38 x 12 x 26 inches 10. Voltage: 220-240 v Motor power: 5 HP Die hole specification: 6 mm Material: Durable metal
Dimension (LxWxH): 38 x 12 x 26 inches 10. Voltage: 220-240 v Motor power: 5 HP Die hole specification: 6 mm Material: Durable metal
inches Voltage: 220-240 v Motor power: 5 HP Die hole specification: 6 mm Material: Durable metal
Voltage: 220-240 v Motor power: 5 HP Die hole specification: 6 mm Material: Durable metal
Motor power: 5 HP Die hole specification: 6 mm Material: Durable metal
Die hole specification: 6 mm Material: Durable metal
Material: Durable metal
Emergency stop: Yes
With manufacturer's warranty
LABORATORY EQUIPMENT, 1 95,000.00 95,000.00
Chlorophyll meter, Two (2) wavelength entired density
Two (2) wavelength optical density difference method; Measurement area:
2 x 3mm;
Measurement accuracy: within
±1.0SPAD;
Memory: 30 data; Warning buzzer, with arbitrary correction function;
Waterproof structure: IPX4;
11. Power supply: AA alkaline dry cell x
2 pieces (included);
Weight: 200g;
Model number: SPAD-502 Plus;
Display range: -9.9 to +199.9SPAD;
Size (mm): 78 x 49 x 164;
Accessories: Stopper, Reading checker, Strap, Soft case
checker, Strap, Soft case
With manufacturer's warranty
LABORATORY EQUIPMENT, 1 97,000.00 97,000.00
Diesel engine with
common rail intercooler Educational
Trainer, 4 stroke engine; 4 in-line
cylinders; 4 valves per cylinder
12. Displacement: 2500/2800 cu. Cm
Power: 150-170 hp At 4000 RPM Twin overhead complete (DOHC) with
Twin overhead camshaft (DOHC) with timing belt
Vibration-damping balancing shafts
Common rail-type direct injection with
electro-injectors

13.	Turbo-supercharger with air-air intercooler Alternator-oil filter-oil pump With manufacturer's warranty LABORATORY EQUIPMENT, Digital Salinity Refractometer, Hydrometer salinity, measurement and analysis instruments Size: 160x59x49mm Weight:230g Function: 0-28% ATC salinity refractometer	2	50,000.00	100,000.00
	With manufacturer's warranty			
14.	LABORATORY EQUIPMENT, Double Door Laboratory Refrigerator, Double Door Laboratory Refrigerator, Shelf/drawer: Shelves/10 Cooling method: Forced Air Cooling System Defrost: Auto Refrigerant: R290 Power consumption(kWh/24h): 5.8 Noise(db): 52 Ambient temperature celcius: 10~32 Temperature range celcius: 2~8	1	150,000.00	150,000.00
15.	With manufacturer's warranty LABORATORY EQUIPMENT, ELECTRIC MIXER, Stand mixer Heavy duty mixer Kneading Cream Filling Machine Eggbeater Mixer Dough Commercial dough mixer Kneading Dough Power: 1100W Voltage: 220V Capacity: 15L-30L Three major accessories: egg-beating cage. Clapper board. Kneading hook	4	50,000.00	200,000.00
16.	With manufacturer's warranty LABORATORY EQUIPMENT, ESPRESSO MACHINE, 1560 watts	1	71,000.00	71,000.00

	Espresso Machine			
	Dimensions (HxWxL):			
	13.1" x 12.8" x 12.2"			
	Construction Materials: Brushed			
	Stainless Steel.			
	Bean Hopper Capacity: 1/2 lb. Water			
	Tank Capacity: 2000ml			
	Voltage: 220-240 volts			
	0 0. 1 5 11 01 .			
	Settings: Single or Double Shots.			
	Heating system: Thermocoil integrated			
	stainless steel water path accurately			
	controls water temperature. With pre			
	infusion function that gradually			
	increases water pressure to gently			
	expand grinds for an even extraction.			
	Adjustable Grind Amount & Manual			
	over-ride.			
	Included Accessories:			
	Razor Dose Trimming Tool.			
	54mm Stainless Steel Portafilter.			
	1 cup & 2cup Single & Dual Wall			
	Filter Baskets.			
	Coffee Scoop.			
	Integrated Tamper.			
	Stainless Steel Milk Jug.			
	Cleaning disc and tablets.			
	Cleaning brush, tool and Allen Key.			
	Water Filter Holder and Water Filter.			
	With manufacturer's warranty			
	LABORATORY EQUIPMENT, Feed Pelletizer	1	150,000.00	150,000.00
	Machine, With Electric Motor			
	Power: 5HP Single Phase			
17.	Working Load: 80-100 kg/hr			
	Default Disc Mill: 3mm			
	Boundary Dimension: 750 x 280 x 700mm			
	With manufacturer's warranty			
	LABORATORY EQUIPMENT, Fish	1	342,000.00	342,000.00
18.	Smokehouse Oven		, 3. 	,

	Drying Smoker meat,			
	Dimension: 1185x950x1960mm			
	Capacity: 50kg/time			
	* · · · ·			
	Voltage: 380V 50HZ			
	Power: 6kw			
	W'41 C 4 2			
	With manufacturer's warranty LABORATORY EQUIPMENT,	1	60,000.00	60,000.00
	Heavy duty vacuum	1	00,000.00	00,000.00
	sealing integrated machine for air			
	packaging compression and high			
	suction,			
19.	Voltage power: 220V/480w			
	Vacuum pump: 2.0L copper core			
	single pump			
	Sealing strip size: length 32cmx 8cm widex2			
	Weight: 42kg			
	With manufacturer's warranty			
	LABORATORY EQUIPMENT,	1	100,000.00	100,000.00
	Illuminated Tissue			
	Flotation Bath, Dimensions: Width			
	295mm x Depth			
	370mm x Height 135mm			
	Bowl: Diameter 220mm x Height 90mm			
	Weight: 4.5Kgs			
20	Temperature range: 30 °C to 70 °C			
20.	Digital display: +/- 1°C			
	Safety: Class 1 cut out			
	Heater power: 400 watts			
	Power Supply: Dual Voltage 220-			
	240V or 110-120V			
	50/60Hz			
	2 3, 332-22			
	With manufacturer's warranty			
	LABORATORY EQUIPMENT, Lab	1	100,000.00	100,000.00
	Mill/Husker,			
	Capacity: 250 grams paddy sample			
21.				
21.	Power: 400 W (0.5 hp) single phase			
	Head Power: 1,900 RPM			
	Follow power: 1,000 RPM			
	Tonow power. 1,000 Kt W			

		Size: 720mm x 480mm x 1400 mm			
		Weight: 49kg			
		Power source: 220 V, 60 hz			
		W/41 2 2			
		With manufacturer's warranty LABORATORY EQUIPMENT,	1	50,000.00	50,000.00
		Laboratory Electric	1	30,000.00	30,000.00
		Furnace			
		Product name: Electric Furnace			
	22.				
		Power: 3300W			
		Maximum temperature about 1000 °C			
		Furnace net size: 16 x 16 x 17cm			
		With manufacturer's warranty			
		LABORATORY EQUIPMENT,	1	50,000.00	50,000.00
		laboratory water tank			
		Stainless Pressure tank Water Tank 50			
		gals. with			
		JRKJET100 4HP Water Pump			
		Water Tank 50 gallons			
		Industrial			
	23.	Stainless			
		Heavy Duty			
		Secured Thread Tube Fittings			
		50 Gallons or 80 Liters in Capacity			
		16 inches in diameter			
		24 inches in height			
		Frequency: 60hz			
		With many footsman's systematic			
		With manufacturer's warranty LABORATORY EQUIPMENT,	1	106,700.00	106,700.00
		Moisture analyzer	1	100,700.00	100,700.00
		(multi-crop)			
		Input voltage: 230 V AC 50 Hz			
		Weighing capacity [Max]: 200 g			
		Weighing units: % Trockenmasse g %			
		Feuchte			
	24.	Maximum humidity: 80 %			
		Maximum operating temperature: 40			
		⁰ C Minimum ambient temperature: 5			
		⁰ C Minimum humidity: 5 %			
		Readability (moisture): 0.050 %			
		Tare range: 200 g			
		Taic lange. 200 g			
		With manufacturer's warranty			
		,	·		1

Г	LARORA MORAL FOLLOW		200 000 00	200,000,00
	LABORATORY EQUIPMENT,	1	200,000.00	200,000.00
	Moisture analyzer,			
25.	Moisture analyzer, capacity 120g;			
	Display-LCD(backlight); AC powered			
	With manufacturer's warranty			
	LABORATORY EQUIPMENT,	1	300,000.00	300,000.00
	Multi-Test Photometer,			
26	140 parameters, 18 wavelengths, 5.5 touch-display, WiFi, USB, camera,			
26.	Bluetooth. With complete accessories			
	Since of the complete development			
	With manufacturer's warranty			
	LABORATORY EQUIPMENT,	1	60,000.00	60,000.00
	Multiparameter Water			
	Quality Meter, Portable Type, pH			
	Range			
	-2.000-20.000pH			
	Resolution 0001,0.01,0.1pH,			
	selectable			
	Accuracy 0.002pH			
	Calibration Points 1 to 5 points			
	pH Buffer Options USA, NIST, DIN,			
	2 custom buffers			
	ORP Range ±1999.9mV			
	Resolution 0.1, 1mV, selectable			
	Accuracy ±0.2mV			
	Calibration Points 1 point			
27.				
	Ion Range 0.001~19999 (depending on			
	the range of			
	ISE)			
	Resolution 0.001, 0.01, 0.1, 1			
	Accuracy ±0.5% F.S. (monovalent),			
	±1% F.S.			
	(divalent)			
	Measurement Units ppm, mg/L, mol/L, mmol/L			
	Calibration Paints 2 to 5 points (0.001,			
	0.01, 0.1, 1, 10,			
	100, 1000, 10000)			
	Conductivity Range 0.01~20.00,			
	200.0, 2000μS/cm,			
	20.00, 200.0mS/cm			

	D l	<u> </u>		
	Resolution 0001,0.01,0.1,1 Accuracy			
	±0.5% F.S.			
	Calibration Paints 1 to 5 points			
	Calibration Solutions 10µS/cm,			
	84μS/cm, 1413μS/cm, 12.88mS/cm, 111.8mS/cm			
	Temperature Coefficient Linear(0.0-			
	•			
	10.0%/°C) pure water			
	Reference Temperature 20/25°C			
	Cell Constant K=0.1, 1, 10 or custom			
	With manufacturer's warranty			
	LABORATORY EQUIPMENT, Oil	1	78,792.00	78,792.00
	Insulation Test Kit, Features:			
	Voltage Display Resolution:			
	Safety Standards: Meeting IEC 61010			
	Accuracy: +/- 1 Percent of FSD			
	Variac: Motorized			
	Shutdown sensitivity: 5mA			
	Gap Gauge: 1mm /2mm / 2.5mm and 4mm			
	Indications Cover Open, Wait time, HT On, KV rise, &			
28.	BDV			
	Weight: 40 Kg. Approx			
	Dimensions: L=700 x B=320 x H=325 mm +/- 10mm			
	Humidity Range: 80 Percent Rh at 40 $^{ m o}{ m C}$			
	Temperature Range: Operating 0 - 40 °C			
	Voltage Range: 0 to 60 KV AC			
	Trip Current: Less than10mA			
	Indication: 3 1/2 Digit Panel Meter			
	With manufacturer's wearest			
	With manufacturer's warranty LABORATORY EQUIPMENT,	1	100,000.00	100,000.00
	Series Biological	•		
	Trinocular Compound Microscope 40X-1000X			
29.	Magnification with 9.7" Touchscreen			
	Imaging System,			
	OS Android 4.1.1			
	CPU 1.8GHz			

AGD (DDDA)		
Memory 2GB (DDR3)		
Internal Storage 2GB		
External Storage MicroSD (TF) 32GB max, USB		
Screen Size (diagonal) 9.7"		
Display Resolution 2048 x 1536		
Display Mount 360° rotation, 90° tilt		
Sensor Type CMOS		
Active Pixels 5M (2592 x 1944)		
Shutter electronic rolling shutter		
Photo Capture Resolution 2592 x 1944		
2048 x 1536		
1600 x 1200		
Video Capture Resolution and Maximum		
Framerate 15fps @ 2048x1536		
Connectivity Micro HDMI		
USB 2.0		
Wi-Fi Optical System Finite-conjugate		
Mechanical Tube Length 160mm		
Head Trinocular, 30° incline, 360°		
rotatable		
Interpupillary Adjustment 55-75mm		
Siedentopfcompensation-free gemel		
Ocular Diameter 23mm		
Eyepieces 10X		
Photo Port height-adjustable 23mm		
tube, CX series, simul-focal		
Objective Lenses DIN standard		
Objective Parfocal Distance 45mm		
Objective Mounting Thread RMS 20.32mm		
Objective Turret quadruple		
Focusing System Coaxial coarse and		
fine focus, upper limit-stop, tension		
control		
Focus Range 28mm		
Division of Fine Focus 0.002mm		
Stage Design Double-layer with caliper		
Stage Dimensions 140mm x 132mm		
X-Y Translation Range 76mm x 50mm		
ű		

		Transmitted Illumination 20W halogen			
		Condenser NA1.25 Abbe condenser			
		with iris diaphragm, 32mm filter holder			
		Sub-stage Condenser-holder rack and pinion			
		Power 85-265VAC 50/60Hz wide-			
		band			
		With manufacturer's warranty			
		LABORATORY EQUIPMENT,	1	50,000.00	50,000.00
	30.	Stainless Steel Bench	-	20,000.00	20,000.00
		Scale, Commercial Digital Weighing Scale/Postal			
		Scale/Shipping Scale, 800×0.05lb			
		Capacity (16"x 20")			
		Will Control			
		With manufacturer's warranty LABORATORY EQUIPMENT,	1	180,000.00	180,000.00
		Triple Deck Gas Oven, triple deck	1	100,000.00	100,000.00
		design			
		1.5" thick Cordierite decks			
	31.	(3) 8" high decks with (3) cooking			
		chambers			
		Throttling thermostat range from 300° to 650°			
		Independently controlled top and bottom heat dampers			
		Heavy-duty, slide-out flame diverters			
		Spring-balanced, fully insulated doors			
		Gas controls with valve, regulator, 50			
		kg LPG tank and pilot safety			
		Side or rear 3/4" NPT gas connection			
		6" steel legs finished with durable			
		Bakertone Stainless steel exterior			
		CE, NSF, CSA Star, CSA Flame			
		CL, NSI', CSA Star, CSA Franc			
		With manufacturer's warranty			
	32.	LABORATORY EQUIPMENT, Type: Analytical Balance	1	50,000.00	50,000.00
		Model: PR124-Alumin (120 grams, 0.1 milligrams),			
		<i>- ''</i>			

	PR204-Alumin (200 grams, 0.1			
	PR204-Alumin (200 grams, 0.1 milligrams),			
	PR224-Alumin (220 grams, 0.1 milligrams)			
	Capacity: 120 grams, 200 grams, 220 grams			
	Resolution: 0.0001 grams			
	Minimum Weight: 0.0004 grams			
	Repeatability: plus or minus 0.0002 grams			
	Linearity: plus or minus 0.0003 grams			
	Stabilization Time: less than or equal to 3 seconds			
	Operating Temperature: 5 to 25 degrees Celsius			
	Draft Shield Size: 240 millimeters x 190 millimeters x			
	265 millimeters			
	Calibration Weight:100 grams, 200 grams, 200 grams			
	Options: Printer			
	Calibration: Internal Calibration			
	With manufacturer's warranty	1	50,000,00	5 0,000,00
	LABORATORY EQUIPMENT, Type: Laboratory Pipette, 4 Pack	1	50,000.00	50,000.00
	starter kit, volume range 0.5 uL to			
33.	1,000 uL,			
33.				
	Single Channel			
	With manufacturer's warranty			
	LABORATORY EQUIPMENT, Water DO meter,	1	80,000.00	80,000.00
	Measures Dissolved oxygen, with			
	datalogger feature; with spare probes; Rugged, IP67-rated housing for plant			
	and field applications; USB and RS-			
	232 output for up to 500 data sets; 500			
34.	hours battery life, or optional universal			
	power adapter; Built-in stand with wall mount allows for easy benchtop			
	measurement or storage; Ready			
	(stability) indicator; Smart averaging;			
	Hold function; Calibration alarm;			
	Battery-life indicator			
1 11				

LAWN MOWER, Riding Lawn Mower Engine: Gas or Diese! Horsepower: 16-25HP Fuel Capacity: 2-4 Gallons Max Forward Speed: 3-5 mph Max Reverse Speed: 2-3 mph 35. Cutting Width: 30 - 64 inches Cutting Height: 1/2 - 4 inches Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video 36. microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch. Includes measuring capability with the		LAWN MOWER, Riding Lawn	1	295 000 00	285,000.00
Engine: Gas or Diesel Horsepower: 16-25HP Fuel Capacity: 2-4 Gallons Max Forward Speed: 3-5 mph Max Reverse Speed: 2-3 mph 35. Cutting Width: 30 - 64 inches Cutting Height: 1/2 - 4 inches Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		,	1	283,000.00	283,000.00
Horsepower: 16-25HP Fuel Capacity: 2-4 Gallons Max Forward Speed: 3-5 mph Max Reverse Speed: 2-3 mph 35. Cutting Width: 30 - 64 inches Cutting Height: 1/2 - 4 inches Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video 36. microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
Fuel Čapacity: 2-4 Gallons Max Forward Speed: 3-5 mph Max Reverse Speed: 2-3 mph 35. Cutting Width: 30 - 64 inches Cutting Height: 1/2 - 4 inches Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video 36. microscope images, Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		•			
Max Forward Speed: 3-5 mph Max Reverse Speed: 2-3 mph 35. Cutting Width: 30 - 64 inches Cutting Height: 1/2 - 4 inches Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images, Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		•			
Max Reverse Speed: 2-3 mph Cutting Width: 30 - 64 inches Cutting Height: 1/2 - 4 inches Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		* *			
35. Cutting Width: 30 - 64 inches Cutting Height: 1/2 - 4 inches Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
Cutting Height: 1/2 - 4 inches Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.	35.	<u> </u>			
Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video 36. microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
Side Discharge With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		-			
With manufacturer's warranty MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
MACHINERY AND EQUIPMENT, 3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		Rear Discharge			
3-Head Teaching Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		With manufacturer's warranty			
Microscope Student Teacher Version Objectives: Plan Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.			1	150,000.00	150,000.00
Objectives: Plan Infinity Led arrow Pointer Trinocular w/14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
w/ 14 MP HDMI Camera, Video and Photography High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
High Resolution 3.1 MegaPixel Digital Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
Camera System. Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		Camera, Video and Photography			
Complete Digital Microscopy Solution Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		-			
Included. Capture high resolution digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		*			
digital microscope images, 2048×1536 pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		1 0 11			
pixels. View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		, ,			
View and record full motion live video microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
microscope images. Frame size options for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		•			
for video mode: 2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.	26				
2048X1536 (up to 11 FPS, depending on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.	30.				
on PC), 1024 X 768, 640 X 480, 512 X 384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
384. Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
Computer connected digital microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
microscope camera connects via USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
USB2.0. Includes USB cable and MS Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
Windows software. Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.		•			
Color DSP built into camera provides sharp quality color images. Image sensor size is half inch.					
sharp quality color images. Image sensor size is half inch.					
sensor size is half inch.		•			
		sharp quality color images. Image			
Includes measuring capability with the		sensor size is half inch.			
software.					

	Eyepieces and Magnification			
	With manufacturer's warranty			
	MACHINERY AND EQUIPMENT,	1	80,000.00	80,000.00
	Combined Forage Shredder &			
	Chopper Machine, Maximum			
	Capacity:			
	450-600 kg/hour			
	Dimension(LxWxH): 610x			
	635x780mm			
37.				
	No. of Hammers: 16			
	Hammer Clearance: 40-50			
	Spindle speed: 4000 rpm			
	Inlet size: 240x180mm			
	Material: Durable metal			
	With manufacturer's warranty	1	200,000,00	200,000,00
	MACHINERY AND EQUIPMENT,	1	200,000.00	200,000.00
	CONVENTIONAL TOP CAGES/			
	LABORATORY ANIMAL CAGE,			
	for MICE/HAMSTER, HANG RACK			
	Stainless Steel with swivel castor			
	wheels with brake			
	105.1cmx42cmx155cm			
	MICE/HAMSTER			
	29cmx17cmx15cm			
	DBPC-0003 (PP)			
	COMPLETE SET: Cage body +			
38.				
	feed hopper and hinged divider +			
	250ml water bottle, whole set			
	25 cages and rack included			
	MATERIAL:POLYPROPYLENE			
	Made from translucent food grade			
	plastic which may be a more practical			
	option with good impact strength and			
	heat resistance. More resistant to			
	scratches and can be autoclaved up to			
	121 °C			

	whole set			
	25 cages and rack included			
	20 Jugos una ruen meruada			
	With manufacturer's warranty			
	MACHINERY AND EQUIPMENT, Cordless Air Blower	7	7,422.50	51,957.50
	(Bare Tool), Very powerful with an air			
	speed of 270 km/hr			
	Very versatile with four accessories			
	Compact and handy design			
	Technical data			
39.	Battery voltage 18.0 V			
	No-load speed 17.000 rpm			
	Max. air speed 75.0 m/s			
	Max. airflow 120.0 m³/h			
	Runtime Speed I: 9 min/Ah			
	Speed II: 5 min/Ah			
	Weight excl. battery 1.1 kg			
	With manufacturer's warranty			
	MACHINERY AND EQUIPMENT, CRDI Engine Fault	2	210,000.00	420,000.00
	Diagnosis Training Equipment, Feature			
	CRDI (Common Rail Direct Engine)			
	Simulator Equipment which has fuel,			
	cooling, intake, exhaust panel so that			
	allows theoretical training and			
	experiments.			
	Pressure gauge is attached on each			
	range of hydraulic line on A/T for			
40.	•			
	process. Exhaust muffler is specially			
	designed with heat-resisting paint to be			
	maintained at high temperatures up to			
	600? (minimum).			
	ISO9001 certified or its equivalent in manufacturing.			
	Specification			
	Composition			
	1) CRDI Diesel Engine Assembly, 2,900cc			
	- 4, 2			

	2) equipped with Automatic			
	Transmission Assembly			
	3) Injector, Fuel Filter, Fuel			
	Tank, Fuel Pump, Fuel			
	Devices, DC 12V			
	Car Battery and alternator			
	4) Cooling System such as			
	Radiator, Overflow Tank, Relay,			
	cooling fan			
	5) Exhaust System such as Catalytic Converter,			
	Emission, Silencer			
	7) Ignition Switch (Key S/W)			
	Anti-vibration dampersand a urethane			
	wheels			
	8) Control box, fuel tank (removable), accelerator lever			
	9) molding type safety guard is installed			
	10) Battery Voltage Gauge 12DCV			
	11) Fault insertion, control panel			
	open and close feature and 3 stage			
	PCB board mounted			
	at least Euro 4, engine			
	With manufacturer's warranty			
	MACHINERY AND EQUIPMENT, Demolition Hammer	2	56,500.00	113,000.00
	/Jack Hammer, Voltage: 220-240/50Hz			
	Rated Input power: 1750-2,000W			
	Impact Energy: 41- 62 Joules			
	Impact Rate : 1,000-1300 bpm at Rated Speed			
41.	Weight : 16.9 - 29.5 kg			
	Tool Holder : 28mm 30mm Hex Shank			
	Included Chisel Bit: 2 pcs 28mm - 30mm Hex Shank			
	Service Warranty: 1 to 3 years			
	With manufacturer's warranty			

	MACHINERY AND EQUIPMENT, Fiber Glass	1	85,507.00	85,507.00
	Telescoping Hot Stick (Hasting Tip-Lock), Lockable			
	Length 17, 21, 25.5 ft			
42.	Retractable Length 60 ft			
12.	Base Diameter 2 3/16 inches			
	Weight 3.75 kg			
	Carrying Case C-30			
	With manufacturer's warranty			
	MACHINERY AND EQUIPMENT, GBH 3-28 DRE ?	3	18,000.00	54,000.00
	Rotary Hammer Drill, Power Input: 800 W			
	Max. Bit Dia. : 28 mm			
12	Max. Core Bit Dia.: 80 mm			
43.	No-load Speed: 0 to 900 rpm			
	Impact Rate: 0 to 4000 bpm			
	Impact Force: 0 to 3.5 J			
	Weight: 3.5 kg			
	With manufacturer's warranty	2	120,000,00	240,000,00
	MACHINERY AND EQUIPMENT, High Pressure	2	120,000.00	240,000.00
	Washer, Voltage:220-240V 60Hz			
	Copper pump. Copper wire induction			
	motor			
44.	Input power:3000W. Max			
	Pressure:130Bar 1850PSI Flow rate:14L/min. Soap bottle, metal spray			
	gun, 10 m high pressure hose steel			
	wired			
	With manufacturer's warranty	2	150 000 00	450,000,00
	MACHINERY AND EQUIPMENT, K-SML05/10/15	3	150,000.00	450,000.00
	Motor Driven Sirens, K-SML15			
	features: All weather enclosed motor is			
45.	ideally suited for outdoor use. This			
75.	siren would be used for audible			
	warning at refineries, oil rigs, in the			
	event of fires and open-cast mining			
	operations. This precision machined			
	*			

	unit produces a powerful dual low			
	frequency sound that is ideal for long			
	distance signalling.			
	Maximum Output: 145 db (A) @ 1m			
	Tones: Continuous or Wail Tone			
	(when supply is switched on/off)			
	Frequency: 560Hz			
	2.5Km effective range			
	Voltages: 400V 3 Phase			
	Motor Power: 7.5kW			
	Duty: Continuous			
	Enclosure Material: Cast Aluminium			
	Colour: Grey, other colours available			
	Operating Temperature: -20 to +40°C			
	Storage Temperature: -40 to +70°C			
	Relative Humidity: 90% at 20°C			
	Weight: 118KgK-SML15			
	With manufacturer's warranty			
	MACHINERY AND EQUIPMENT,	1	65,000.00	65,000.00
	On Board Diagnostic (OBD) 2			
	SCANNER EQUIPMENT, Android			
	system, 8			
	inch touchscreen (at least) with link			
	cables or wireless adaptor and			
	complete set of accessories Battery			
	7700mAh (at least) supports 150+ car			
	brands worldwide from 1996-2024 car			
	models. OBD2 code reader equipped			
46.	with 28+ hot services including Oil			
	Reset, SAS Calibration, ABS			
	Bleeding, Injector Coding, Battery			
	Registration, Injector registration,			
	Fault code delete, Auto Transmission			
	fault detection, A/C fault detection,			
	etc. support more newer car models			
	and brands from 2023 to 2024.			
	effectively works all cars for all system			
	diagnostics. It reads/clears codes,			
	provides ECU info, displays 5-in-1			

 				T
	Live Data, performs active tests, and			
	special functions for all available			
	modules. With a few clicks, you can			
	easily understand the vehicle's			
	condition.			
	1-year brand warranty, 12-month free			
	updates, lifetime technical support, and			
	free return and replacement policy.			
	With product certification			
	W'd C			
	With manufacturer's warranty MACHINERY AND EQUIPMENT,	1	988,680.00	000 600 00
	Plastic Shredder	1	988,080.00	988,680.00
	Machine, Motor : 3 Phase, 380V,			
	50Hz			
	Power: 4KW-4, Double motor			
	Reducer : JL3#-15 (double) Input			
	speed 15 rpm			
	Input torque: 5800Nm			
	Input shaft Ø: 50			
47	Blade size: 180x15			
47.	Blade material: 9CrSi			
	Blade Qty.: 26 PCS			
	Inlet size : 600x500x300 mm			
	Outlet width: 480 mm			
	Outlet height : 200 mm			
	Machine size (LxWxH) :			
	1540x650x1450 mm			
	Machine weight: 800kg			
	Wild Co.			
	With manufacturer's warranty MACHINERY AND EQUIPMENT	1	102 200 00	192,388.00
	MACHINERY AND EQUIPMENT, PLC Training	1	192,388.00	172,300.00
	System Programmable Controls			
	(Multi-Brand) Training			
	System,			
40	Dimension: Height :26 inches Width:			
48.	24 inches Depth:			
	26 inches			
	Training Hardware Kit Height: 26			
	inches			
	Training Hardware Kit Width: 24 inches			
	menes			

	T :: II 1 W: D 4 04:			
	Training Hardware Kit Depth: 24 in inches			
	Language: English			
	Software: PLC Programming Software			
	System Format: Freestanding with			
	Cable, Logic components			
	With manufacturer's warranty			
	MACHINERY AND EQUIPMENT, Potable Toilet,	3	320,000.00	960,000.00
	1.Wall Panel: 50mm EPS sandwich panel			
	2.Aluminum trim and flashing			
	3.Equipment:one washing			
	basin(triangle shape) and one			
	sitting toilet, one exhaust fan, one			
	light(220V60HZ),one tap ,One Shower			
49.	TT 14 1 1 1			
49.	4.Weight: 110kg;			
	5.The door is 1.9m			
	6.The wall is white color.			
	7. The thickness of the angle steel is			
	2mm,the thickness of galvanized steel			
	plate is 2.75mm)			
	8. Color: white			
	W/:41			
	With manufacturer's warranty MACHINERY AND EQUIPMENT,	6	50,000.00	300,000.00
	SEWING MACHINE,	U	30,000.00	300,000.00
	20-30 Stitches			
	One-step buttonhole			
	Built-in needle threader			
	Snap-on presser feet			
	3-5-piece feed dog			
	Extra high-presser foot lift			
50.	Stitch selection dials			
	Mechanical Sewing Machine			
	Residential Use			
	Automatic Buttonholer; Needle			
	Threading System			
	220 watts			
	Shipping Dimension			
	18-25 x 15-20 x 10-15 inches			
	Shipping Weight 20.55 lbs			

	Colom Arra			1
	Color: Any			
	With manufacturer's warranty	1	100 000 00	100,000.00
	MACHINERY AND EQUIPMENT, SURGICAL	1	100,000.00	100,000.00
	CAUTERY MACHINE, Portable			
	Electrocautery			
	Machine			
	Modes in CUT - Pure, Blend			
	Modes in COAG-Contact Coag			
	Bipolar coag- standard coag			
	Microprocessor controlled			
	*			
51	Handswitch and Footswitch Operation			
	Frequency - 400 W			
	Minimum RF Distortion; User settable program modes			
	HF Leakage current > 150mA			
	Weight: 7.5 Kg (Approx.)			
	Size: 40x20x15CM			
	Weight: Approx. 4.2KG			
	* **			
	With complete accessories			
	With manufacturer's warranty	1	100 000 00	100 000 00
	MACHINERY AND EQUIPMENT, Vocational Training	1	180,000.00	180,000.00
	Equipment House Fire alarm Trainer			
	Kit, Single phase			
52				
	Minimum dimension			
	1500x660x1800mm 100kg			
	With manufacturer's warranty			
	MICROSCOPE, Binocular	4	50,000.00	200,000.00
	Microscope with electronic eyepiece			
	and monitor			
	360 degree adjustable binocular head,			
	ocular distance is from 55 to 75 mm			
	adjustable.			
53	Coarse and fine focus knob,			
	Power and Battery Dual Supply			
	System. with up to 2000x power;			
	Changeable wide field 10x 25x			
	eyepieces and 2x extender allow you to			
]	view specimens at 40x; 80x; 160x;			

100x; 200x; 250x 400x; 800x 1000x 2000x etc. magnification. Built-in 6 colored filters Improve the quality of your magnified images. with a 2.0 mp electronic eyepiece, easy to connect to a computer and save images / videos or viewing specimen live, with measurement / draw line function, with high speed transmission software, not worry about lag. Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.751bs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Inclined at 30°, capable of 360° rotation Rotatable eyepiece				T	1
Built-in 6 colored filters Improve the quality of your magnified images. with a 2.0 mp electronic eyepiece, easy to connect to a computer and save images / videos or viewing specimen live, with measurement / draw line function, with high speed transmission software, not worry about lag. Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square:Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		100x; 200x; 250x 400x; 800x 1000x			
quality of your magnified images. with a 2.0 mp electronic eyepiece, easy to connect to a computer and save images / videos or viewing specimen live, with measurement / draw line function, with high speed transmission software, not worry about lag. Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage: 90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.751bs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		2000x etc. magnification.			
with a 2.0 mp electronic eyepiece, easy to connect to a computer and save images / videos or viewing specimen live, with measurement / draw line function, with high speed transmission software, not worry about lag. Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 340° rotation Inclined at 30°, capable of Adjustable interpupillary distance: 52-75mm		Built-in 6 colored filters Improve the			
to connect to a computer and save images / videos or viewing specimen live, with measurement / draw line function, with high speed transmission software, not worry about lag. Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE. Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		quality of your magnified images.			
images / videos or viewing specimen live, with measurement / draw line function, with high speed transmission software, not worry about lag. Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		with a 2.0 mp electronic eyepiece, easy			
live, with measurement / draw line function, with high speed transmission software, not worry about lag. Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 54. 360° rotation Adjustable interpupillary distance: 52-75mm		to connect to a computer and save			
function, with high speed transmission software, not worry about lag. Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.751bs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		images / videos or viewing specimen			
software, not worry about lag. Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		live, with measurement / draw line			
Specification: Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		function, with high speed transmission			
Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 54. Adjustable interpupillary distance: 52-75mm		software, not worry about lag.			
Model: GF24B Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm					
Optical System: Finite Biological Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 34. 360° rotation - Adjustable interpupillary distance: 52-75mm		Specification:			
Microscope bservation head: binocular head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 34. 360° rotation - Adjustable interpupillary distance: 52-75mm		Model: GF24B			
head, 45 degree tilt, 360 degree rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		Optical System: Finite Biological			
rotation Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		Microscope bservation head: binocular			
Eyepiece: WF10X WF25X Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 54. Adjustable interpupillary distance: 52-75mm		head, 45 degree tilt, 360 degree			
Objective: 4X 10X 40X Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		rotation			
Extender: 2.0X Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		Eyepiece: WF10X WF25X			
Magnification: 40X-2000X Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment : Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		Objective: 4X 10X 40X			
Working Stage :90mmX90mm Square/Moving Scale/Disc Filters Adjustment : Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		Extender: 2.0X			
Square/Moving Scale/Disc Filters Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.751bs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		Magnification: 40X-2000X			
Adjustment: Coarse Focuser & Fine Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm					
Focuser (dual knobs) Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications 2 52,000.00 104,000.00 Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		Scale/Disc Filters			
Illuminator Top/Bottom: LED Lights, Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications 2 52,000.00 104,000.00 Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		Adjustment: Coarse Focuser & Fine			
Uses 3pcs AA batteries (Not included) or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head - Inclined at 30°, capable of 360° rotation - Adjustable interpupillary distance: 52-75mm		Focuser (dual knobs)			
or DC power supply. Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		Illuminator Top/Bottom: LED Lights,			
Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		Uses 3pcs AA batteries (Not included)			
Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		•			
Item Size: 185x140x290mm Monitor for viewing With manufacturer's warranty MICROSCOPE, Specifications 2 52,000.00 104,000.00 Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm					
With manufacturer's warranty MICROSCOPE, Specifications 2 52,000.00 104,000.00 Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm					
With manufacturer's warranty MICROSCOPE, Specifications 2 52,000.00 104,000.00 Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm					
MICROSCOPE, Specifications 2 52,000.00 104,000.00 Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		Monitor for viewing			
Binocular Head Inclined at 30°, capable of 360° rotation Adjustable interpupillary distance: 52-75mm		-			
54. 360° rotation - Adjustable interpupillary distance: 52-75mm		_	2	52,000.00	104,000.00
distance: 52-75mm	54.				
- Rotatable eyepiece					
		- Rotatable eyepiece			

	- Wide field eyepiece with			
	multiple magnification options (e.g.,			
	10x, 20x)			
	- Semi-plan achromatic and			
	plan achromatic objectives, available			
	in various magnifications (e.g., 4x,			
	10x, 20x, 40x, 60x, 100x)			
	- Infinite achromatic and plan			
	achromatic objectives- Quadruple or			
	quintuple nosepiece for backward			
	rotation			
	- Double-layer mechanical			
	stage: 140x140mm with movement			
	controls and fine adjustments			
	- Coarse and fine adjustment			
	with precision up to 0.002mm			
	- Condenser with iris			
	diaphragm, adjustable illumination-			
	LED or halogen illumination options			
	with adjustable brightness			
	- Attachments available for			
	photography, video, polarization,			
	phase contrast, and dark field			
	- Fluorescent illumination capabilities			
	- Dimensions: Approx. 35cm x 31cm			
	Weight: Approx. 9.5kg			
	With manufacturer's warranty			
	OVEN, Capacity:138L	1	67,000.00	67,000.00
	Temp. Range: RT 5 C to 300 C			
	Temp. Fluctuation: plus or minus 1 C			
55.	Power Supply: 2500W, AC220V, 50Hz			
	Chamber Size: 50x50x55cm			
	Package Size: 90x76x98cm			
	G. Weight:115kg			
	With manufacturer's warranty			
	PRESSURE WASHER, Power Cleaning Machine	1	172,500.00	172,500.00
56.	20 Inches stainless steel floor cleaner			
	Stainless steel handle			

		1		<u> </u>
	2pcs nozzle			
	13hp Gasoline Motor			
	250bar 3600psi pressure			
	Complete set of water gun with 20			
	meters high pressure hose			
	With manufacturer's warranty	1	120,000,00	120,000,00
	REFRIGERATOR, laboratory refrigerator	1	120,000.00	120,000.00
	"Cu. Ft.: 30			
	Door(s): Single Glass, Locking			
	Temperature Range: 2°C to 8°C (36°F to 46°F)			
	Exterior Dimensions: 33.85?W x 37.80?D x 81.12?H			
	Interior Dimensions: 27.50?W x			
57.	30.80?D x 61.84?H Alarm: Audible			
	and visual high and low temperature			
	alarms			
	Shelves: 4 adjustable shelves, sliding			
	Keyed Door Lock			
	Electrical Requirements: 115V, 60Hz;			
	6 amps			
	UL/cUL 61010-1 listed			
	Shipping Weight: 471 lbs.			
	With manufacturer's warranty			
	ROBOTICS V5, Robotics Portable Competition Field	1	265,860.00	265,860.00
	Perimeter & Tiles Kit Specifications:			
	(16) T Connectors (4) Center Panels,			
	(8) Corner Connectors (2) Straps,			
	(4) Side Extrusions (2) Field Cases,			
58.	(4) Center Extrusions (2) Field Tile Cases,			
	(4) Left Extrusions,			
	(8) Vertical Center Extrusions,			
	4) Vertical Corner Extrusions,			
	(12) GPS Code Extrusions,			
	(8) Side Panels,			
	With manufacturer's warranty			
	WEIGHING SCALE, Digital	1	72,600.00	72,600.00
59.	Weighing Balance minimum display			
	value" 0.01g; minimum weighing capacity: minimum-maximum: .0002-			
	capacity. minimum-maximum0002-			

	60.	10mg;; with calibration weights; power supply: AC adapter or dry cell With manufacturer's warranty WELDING MACHINE, TIG Welding Machine (Best Use for Aluminum): Ampere: 250A Voltage: 220V Input Power: 6.0Kw No Load Voltage: 56V Weight: 9Kg With manufacturer's warranty	1	55,000.00	55,000.00
20.2	_	re any licenses and permits relevant wiring it.]	to the I	Project and the	corresponding
21.2	_	re any additional contract documents l by existing laws and/or the Procuring		v	ct that may be

Notes on the General Conditions of Contract

The General Conditions of Contract (GCC) in this Section, read in conjunction with the Special Conditions of Contract in Section V and other documents listed therein, should be a complete document expressing all the rights and obligations of the parties.

Matters governing performance of the Supplier, payments under the contract, or matters affecting the risks, rights, and obligations of the parties under the contract are included in the GCC and Special Conditions of Contract.

Any complementary information, which may be needed, shall be introduced only through the Special Conditions of Contract.

1. Scope of Contract

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuances, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

Additional requirements for the completion of this Contract shall be provided in the **Special Conditions of Contract (SCC).**

2. Advance Payment and Terms of Payment

- 2.1. Advance payment of the contract amount is provided under Annex "D" of the revised 2016 IRR of RA No. 9184.
- 2.2. The Procuring Entity is allowed to determine the terms of payment on the partial or staggered delivery of the Goods procured, provided such partial payment shall correspond to the value of the goods delivered and accepted in accordance with prevailing accounting and auditing rules and regulations. The terms of payment are indicated in the SCC.

[Include the following clauses if Framework Agreement will be used:]

- 2.3. For a single-year Framework Agreement, prices charged by the Supplier for Goods delivered and/or services performed under a Call-Off shall not vary from the prices quoted by the Supplier in its bid.
- 2.4. For multi-year Framework Agreement, prices charged by the Supplier for Goods delivered and/or services performed under a Call-Off shall not vary from the prices quoted by the Supplier during conduct of Mini-Competition.

3. Performance Security

Within ten (10) calendar days from receipt of the Notice of Award by the Bidder from the Procuring Entity but in no case later than prior to the signing of the Contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR of RA No. 9184. [Include if Framework Agreement will be used:] In the case of Framework Agreement, the Bidder

may opt to furnish the performance security or a Performance Securing Declaration as defined under the Guidelines on the Use of Framework Agreement.}

4. Inspection and Tests

The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Project {[Include if Framework Agreement will be used:] or Framework Agreement} specifications at no extra cost to the Procuring Entity in accordance with the Generic Procurement Manual. In addition to tests in the SCC, Section IV (Technical Specifications) shall specify what inspections and/or tests the Procuring Entity requires, and where they are to be conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.

All reasonable facilities and assistance for the inspection and testing of Goods, including access to drawings and production data, shall be provided by the Supplier to the authorized inspectors at no charge to the Procuring Entity.

5. Warranty

- 5.1 In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier as provided under Section 62.1 of the 2016 revised IRR of RA No. 9184.
- 5.2 The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall, repair or replace the defective Goods or parts thereof without cost to the Procuring Entity, pursuant to the Generic Procurement Manual.

6. Liability of the Supplier

The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Supplier is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.

Section V. Special Conditions of Contract

Notes on the Special Conditions of Contract

Similar to the BDS, the clauses in this Section are intended to assist the Procuring Entity in providing contract-specific information in relation to corresponding clauses in the GCC found in Section IV.

The Special Conditions of Contract (SCC) complement the GCC, specifying contractual requirements linked to the special circumstances of the Procuring Entity, the Procuring Entity's country, the sector, and the Goods purchased. In preparing this Section, the following aspects should be checked:

- a. Information that complements provisions of the GCC must be incorporated.
- b. Amendments and/or supplements to provisions of the GCC as necessitated by the circumstances of the specific purchase, must also be incorporated.

However, no special condition which defeats or negates the general intent and purpose of the provisions of the GCC should be incorporated herein.

Special Conditions of Contract

GCC	_
Clause	
1	[List here any additional requirements for the completion of this Contract. The following requirements and the corresponding provisions may be deleted, amended, or retained depending on its applicability to this Contract:]
	Delivery and Documents –
	For purposes of the Contract, "EXW," "FOB," "FCA," "CIF," "CIP," "DDP" and other trade terms used to describe the obligations of the parties shall have the meanings assigned to them by the current edition of INCOTERMS published by the International Chamber of Commerce, Paris. The Delivery terms of this Contract shall be as follows:
	[For Goods supplied from abroad, state:] "The delivery terms applicable to the Contract are DDP delivered [indicate place of destination]. In accordance with INCOTERMS."
	[For Goods supplied from within the Philippines, state:] "The delivery terms applicable to this Contract are delivered [indicate place of destination]. Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination."
	Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI (Schedule of Requirements).
	For purposes of this Clause the Procuring Entity's Representative at the Project Site is <i>Ms. Divina DC. Pinaroc</i> .
	Incidental Services –
	The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements: Select appropriate requirements and delete the rest.
	a. performance or supervision of on-site assembly and/or start-up of the supplied Goods;
	b. furnishing of tools required for assembly and/or maintenance of the supplied Goods;
	c. furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied Goods;
	d. performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided that this service shall not relieve the Supplier of any warranty obligations under this Contract; and

- e. training of the Procuring Entity's personnel, at the Supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods.
- f. [Specify additional incidental service requirements, as needed.]

The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.

Spare Parts –

The Supplier is required to provide all of the following materials, notifications, and information pertaining to spare parts manufactured or distributed by the Supplier:

Select appropriate requirements and delete the rest.

- a. such spare parts as the Procuring Entity may elect to purchase from the Supplier, provided that this election shall not relieve the Supplier of any warranty obligations under this Contract; and
- b. in the event of termination of production of the spare parts:
 - i. advance notification to the Procuring Entity of the pending termination, in sufficient time to permit the Procuring Entity to procure needed requirements; and
- ii. following such termination, furnishing at no cost to the Procuring Entity, the blueprints, drawings, and specifications of the spare parts, if requested.

The spare parts and other components required are listed in **Section VI** (**Schedule of Requirements**) and the cost thereof are included in the contract price.

The Supplier shall carry sufficient inventories to assure ex-stock supply of consumable spare parts or components for the Goods for a period of [indicate here the time period specified. If not used indicate a time period of three times the warranty period].

Spare parts or components shall be supplied as promptly as possible, but in any case, within [*insert appropriate time period*] months of placing the order.

Packaging -

The Supplier shall provide such packaging of the Goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in this Contract. The packaging shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage. Packaging case size and weights shall take into consideration, where appropriate, the remoteness of the Goods' final destination and the absence of heavy handling facilities at all points in transit.

The packaging, marking, and documentation within and outside the packages shall comply strictly with such special requirements as shall be expressly provided for in the Contract, including additional requirements, if any, specified below, and in any subsequent instructions ordered by the Procuring Entity.

The outer packaging must be clearly marked on at least four (4) sides as follows:

Name of the Procuring Entity
Name of the Supplier
Contract Description
Final Destination
Gross weight
Any special lifting instructions
Any special handling instructions
Any relevant HAZCHEM classifications

A packaging list identifying the contents and quantities of the package is to be placed on an accessible point of the outer packaging if practical. If not practical the packaging list is to be placed inside the outer packaging but outside the secondary packaging.

Transportation –

Where the Supplier is required under Contract to deliver the Goods CIF, CIP, or DDP, transport of the Goods to the port of destination or such other named place of destination in the Philippines, as shall be specified in this Contract, shall be arranged and paid for by the Supplier, and the cost thereof shall be included in the Contract Price.

Where the Supplier is required under this Contract to transport the Goods to a specified place of destination within the Philippines, defined as the Project Site, transport to such place of destination in the Philippines, including insurance and storage, as shall be specified in this Contract, shall be arranged by the Supplier, and related costs shall be included in the contract price.

Where the Supplier is required under Contract to deliver the Goods CIF, CIP or DDP, Goods are to be transported on carriers of Philippine registry. In the event that no carrier of Philippine registry is available, Goods may be shipped by a carrier which is not of Philippine registry provided that the Supplier obtains and presents to the Procuring Entity certification to this effect from the nearest Philippine consulate to the port of dispatch. In the event that carriers of Philippine registry are available but their schedule delays the Supplier in its performance of this Contract the period from when the Goods were first ready for shipment and the actual date of shipment the period of delay will be considered force majeure. The Procuring Entity accepts no liability for the damage of Goods during transit other than those prescribed by INCOTERMS for DDP deliveries. In the case of Goods supplied from within the Philippines or supplied by domestic Suppliers risk and title will not be deemed to have passed to the Procuring Entity until their receipt and final acceptance at the final destination. **Intellectual Property Rights –** The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof. 2.2 [If partial payment is allowed, state] "The terms of payment shall be as follows: Not applicable The inspections and tests that will be conducted are: Quality and functional ICT 4 Equipment. Complete and conforms to the technical specifications.

Section VI. Schedule of Requirements

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item No		Particulars	Qty	Delivered, Weeks/Months
	Unit	AUTOCLAVE, Laboratory Autoclave	1	
		Class N autoclave sterilizer,		
		vertical type volume: 100L		
		Bolted digital display automatic control		
1.		Sterilization temperature: 116 to 134C		
		Design pressure: 0.25 Mpa		
		Automatic protection function		
		With manufacturer's warranty		
	Piece	CABINET, Dimensions: 465 X 620 X 1300	1	
		A durable 2 drawer steel filing cabinet able to hold		
		either A4 suspension or foolscap hanging files		
2.		40kg loading capacity		
۷.		Fully lockable		
		Anti-tilt mechanism		
		100% drawer extension on smooth runners		
		With manufacturer's warranty		
	Piece	CABINET, Filing Cabinet Black-	1	
		Brown/Light Brown		30 Calendar Days
		Wood type		
		Depth: 37 cm (14 5/8 ")		
3.		Height: 198 cm (78 ")		
3.		Width: 270 cm (106 1/4 ")		
		Bookcase		
		Glass		
		Glass-door cabinet with 3 drawers		
		With manufacturer's warranty		
	Unit	CABINET, Laminar Flow cabinet	2	
		ULPA Filter		
		ISO Class 3 work zone		
		DC ECM blower for up to 70 percent energy savings		
4.		Low noise at 55.8 dBA		
		Glass side walls		
		Fixed Sash		
		Internal height: 2.50 ft		
		Available sizes: 6ft		

		With manufacturer's warranty		
	Unit	DRILL, Radial drill press	1	
		220V, 4 KW, spindle rpm 1150, spindle		
		travel 420 mm, spindle feeding step16,		
5.		spindle taper MT5, distance from spindle		
		axis to column 350-1650		
		With manufacturer's warranty		
	Unit	ENGINE, Hybrid Engine,	1	
		Engine Code: A25A Complete Engine		
		Fuel: Gasoline		
6.		Doors: 5		
		Mileage: 83979		
		Power: 218CV / 160KW		
		With manufacturer's warranty		
	Unit	FLOOR POLISHER, 16 IN. Heavy Duty	4	
		with brush and		
7.		Bracket, 230 Volts		
		Wide Control		
	Unit	With manufacturer's warranty GENERATOR, Silent type diesel generator	3	
	Unit	GENERATOR, Shell type diesel generator	3	
		Rated voltage V :220-240		
		Rated frequency Hz:60		
		Phase: Single		
		Max output kW :9.5		
		Rated output kW :8.5		
0		Power Factor:1		
8.		Rated speed rpm :3600		
		Fuel tank L :26		
		Net weight Kg :280kg		
		Cooling system: Air cooled		
		Starting system: Electric with maintenance		
		free battery		
		With manufacturer's warranty		
	Unit	INCUBATOR, Laboratory Incubator	2	
		Ventiflow Ventilation System: Forced air		
		convection design		
9.		Pre-heat Chamber Technology: 4-zone		
		heated air jacket		
		Smart Sense Microprocessor PID Control		
		Technology		

		DIN 12880 Class 3.1 Certified for		
		Temperature Safety		
		Electrogalvanized steel body construction		
		Audible and visual alarms		
		Available volume: 110L		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Automatic Feed	1	
		Pelletizer Machine, Output Capacity: 150-180 kg/h		
		Dimension (LxWxH): 38 x 12 x 26 inches		
		Voltage: 220-240 v		
10.		Motor power: 5 HP		
		Die hole specification: 6 mm		
		Material: Durable metal		
		Emergency stop: Yes		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Chlorophyll meter,	1	
		Two (2) wavelength optical density		
		difference method; Measurement area: 2 x 3mm;		
		Measurement accuracy: within ±1.0SPAD;		
		Memory: 30 data; Warning buzzer, with arbitrary correction function;		
		Waterproof structure: IPX4;		
11.		Power supply: AA alkaline dry cell x 2 pieces (included);		
		Weight: 200g;		
		Model number: SPAD-502 Plus;		
		Display range: -9.9 to +199.9SPAD;		
		Size (mm): 78 x 49 x 164;		
		Accessories: Stopper, Reading checker,		
		Strap, Soft case		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Diesel	1	
		engine with		
12.		common rail intercooler Educational		
14.		Trainer, 4 stroke engine; 4 in-line cylinders;		
		4 valves per cylinder		
		Displacement: 2500/2800 cu. Cm		

		Power: 150-170 hp At 4000 RPM		
		Twin overhead camshaft (DOHC) with		
		timing belt		
		Vibration-damping balancing shafts		
		Common rail-type direct injection with		
		electro-injectors		
		Turbo-supercharger with air-air intercooler		
		Alternator-oil filter-oil pump		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Digital	2	
		Salinity		
		Refractometer, Hydrometer salinity, measurement		
13.		and analysis instruments Size: 160x59x49mm		
13.		Weight:230g		
		Function: 0-28% ATC salinity refractometer		
	TT '4	With manufacturer's warranty	1	
	Unit	LABORATORY EQUIPMENT, Double Door Laboratory	1	
		Refrigerator, Double Door Laboratory		
		Refrigerator,		
		Shelf/drawer: Shelves/10		
		Cooling method: Forced Air Cooling		
		System		
14.		Defrost: Auto		
		Refrigerant: R290		
		Power consumption(kWh/24h): 5.8		
		Noise(db): 52		
		Ambient temperature celcius: 10~32		
		Temperature range celcius: 2~8		
	T In:	With manufacturer's warranty	4	
	Unit	LABORATORY EQUIPMENT, ELECTRIC MIXER,	4	
		Stand mixer Heavy duty mixer Kneading		
		Cream Filling Machine Eggbeater Mixer		
		Dough Commercial dough mixer Kneading		
		Dough		
15.		Power: 1100W		
		Voltage: 220V		
		Capacity: 15L-30L		
		Three major accessories: egg-beating cage.		
		Clapper board. Kneading hook		

	With manufacturer's warranty		
16.	With manufacturer's warranty LABORATORY EQUIPMENT, ESPRESSO MACHINE, 1560 watts Espresso Machine Dimensions (HxWxL): 13.1" x 12.8" x 12.2" Construction Materials: Brushed Stainless Steel. Bean Hopper Capacity: 1/2 lb. Water Tank Capacity: 2000ml Voltage: 220-240 volts Settings: Single or Double Shots. Heating system: Thermocoil integrated stainless steel water path accurately controls water temperature. With pre infusion function that gradually increases water pressure to gently expand grinds for an even extraction. Adjustable Grind Amount & Manual override. Included Accessories: Razor Dose Trimming Tool. 54mm Stainless Steel Portafilter. 1 cup & 2cup Single & Dual Wall Filter Baskets. Coffee Scoop. Integrated Tamper. Stainless Steel Milk Jug. Cleaning disc and tablets. Cleaning brush, tool and Allen Key. Water Filter Holder and Water Filter.	1	
17.	LABORATORY EQUIPMENT, Feed Pelletizer Machine, With Electric Motor Power: 5HP Single Phase Working Load: 80-100 kg/hr Default Disc Mill: 3mm Boundary Dimension: 750 x 280 x 700mm With manufacturer's warranty	1	
18. Ur	·	1	

		Drying Smoker meat,		
		Dimension: 1185x950x1960mm		
		Capacity: 50kg/time		
		Voltage: 380V 50HZ		
		Power: 6kw		
		1 OWCI. OKW		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Heavy	1	
	CIII	duty vacuum		
		sealing integrated machine for air packaging		
		compression and high suction,		
		Voltage power: 220V/480w		
19.		Vacuum pump: 2.0L copper core single		
		pump		
		Sealing strip size: length 32cmx 8cm widex2		
		Weight: 42kg		
	TT 1.	With manufacturer's warranty	1	
	Unit	LABORATORY EQUIPMENT, Illuminated Tissue	1	
		Flotation Bath, Dimensions: Width 295mm		
		x Depth		
		370mm x Height 135mm		
		Bowl: Diameter 220mm x Height 90mm		
		Weight: 4.5Kgs		
		Temperature range: 30 °C to 70 °C		
20.		Digital display: +/- 1 ⁰ C		
		Safety: Class 1 cut out		
		Heater power: 400 watts		
		Power Supply: Dual Voltage 220-240V or		
		110-120V		
		50/60Hz		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Lab	1	
		Mill/Husker,		
		Capacity: 250 grams paddy sample		
		Capacity/hr: 50 kg/hr		
21.		Power: 400 W (0.5 hp) single phase		
21.		Head Power: 1,900 RPM		
		Follow power: 1,000 RPM		
		Size: 720mm x 480mm x 1400		
		mm		
		Weight: 49kg		

		Power source: 220 V, 60 hz		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Laboratory	1	
		Electric		
		Furnace		
		Product name: Electric Furnace		
22.		Voltage: 110V / 220V		
		Power: 3300W		
		Maximum temperature about 1000 °C		
		Furnace net size: 16 x 16 x 17cm		
	T T 14	With manufacturer's warranty	1	
	Unit	LABORATORY EQUIPMENT, laboratory water tank	1	
		Stainless Pressure tank Water Tank 50 gals.		
		with		
		JRKJET100 4HP Water Pump		
		Water Tank 50 gallons		
		Industrial		
		Stainless		
23.		Heavy Duty		
		Secured Thread Tube Fittings		
		50 Gallons or 80 Liters in Capacity		
		16 inches in diameter		
		24 inches in height		
		Frequency: 60hz		
		rrequency. oonz		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Moisture	1	
		analyzer		
		(multi-crop)		
		Input voltage: 230 V AC 50 Hz		
		Weighing capacity [Max]: 200 g		
		Weighing units: % Trockenmasse g %		
		Feuchte		
24.		Maximum humidity: 80 %		
		Maximum operating temperature: 40 °C		
		Minimum ambient temperature: 5 °C		
		Minimum humidity: 5 %		
		Readability (moisture): 0.050 %		
		Tare range: 200 g		
		With manufacturer's warranty		
25.	Unit	LABORATORY EQUIPMENT, Moisture	1	
23.		analyzer,		

		Moisture analyzer, capacity 120g;		
		Display-LCD(backlight); AC powered		
		2 is play 2 c2 (calculation), 11c per vices		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Multi-Test	1	
		Photometer,		
		140 parameters, 18 wavelengths, 5.5 touch-		
26.		display, WiFi, USB, camera, Bluetooth.		
		With complete accessories		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT,	1	
		Multiparameter Water		
		Quality Meter, Portable Type, pH Range		
		-2.000-20.000pH		
		Resolution 0001,0.01,0.1pH, selectable		
		Accuracy 0.002pH		
		Calibration Points 1 to 5 points		
		pH Buffer Options USA, NIST, DIN, 2		
		custom buffers		
		ORP Range ±1999.9mV		
		Resolution 0.1, 1mV, selectable		
		Accuracy ±0.2mV		
		Calibration Points 1 point		
		Ion Range 0.001~19999 (depending on the		
		range of		
		ISE)		
27.		Resolution 0.001, 0.01, 0.1, 1		
		Accuracy ±0.5% F.S. (monovalent), ±1%		
		F.S.		
		(divalent)		
		Measurement Units ppm, mg/L, mol/L,		
		mmol/L		
		Calibration Paints 2 to 5 points (0.001, 0.01,		
		0.1, 1, 10,		
		100, 1000, 10000)		
		Conductivity Range 0.01~20.00, 200.0,		
		2000μS/cm,		
		20.00, 200.0mS/cm		
		Resolution 0001,0.01,0.1,1		
		Accuracy ±0.5% F.S.		
		Calibration Paints 1 to 5 points		
		Calibration Solutions 10µS/cm, 84µS/cm,		
		1413μS/cm,		

		12.88mS/cm, 111.8mS/cm		
		Temperature Coefficient Linear(0.0-		
		10.0%/°C) pure water		
		Reference Temperature 20/25°C		
		Cell Constant K=0.1, 1, 10 or custom		
		Cen Constant K=0.1, 1, 10 of custom		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Oil	1	
		Insulation Test Kit, Features:		
		Voltage Display Resolution:		
		Safety Standards: Meeting IEC 61010		
		Accuracy: +/- 1 Percent of FSD		
		Variac: Motorized		
		Shutdown sensitivity: 5mA		
		Gap Gauge: 1mm /2mm / 2.5mm and 4mm		
		Indications Cover Open, Wait time, HT On,		
		KV rise, &		
28.		BDV		
		Weight: 40 Kg. Approx		
		Dimensions: L=700 x B=320 x H=325 mm		
		+/- 10mm		
		Humidity Range: 80 Percent Rh at 40 °C		
		Temperature Range: Operating 0 - 40 °C		
		Voltage Range: 0 to 60 KV AC		
		Trip Current: Less than 10mA		
		Indication: 3 1/2 Digit Panel Meter		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Series	1	
		Biological		
		Trinocular Compound Microscope 40X-		
		1000X		
		Magnification with 9.7" Touchscreen		
		Imaging System,		
		OS Android 4.1.1		
29.		CPU 1.8GHz		
2).		Memory 2GB (DDR3)		
		Internal Storage 2GB		
		External Storage MicroSD (TF) 32GB max, USB		
		Screen Size (diagonal) 9.7"		
		Display Resolution 2048 x 1536		
		Display Mount 360° rotation, 90° tilt		
		Sensor Type CMOS		
		Sensor Type CiviOs		

		Active Pixels 5M (2592 x 1944)		
		Shutter electronic rolling shutter		
		Photo Capture Resolution 2592 x 1944		
		2048 x 1536		
		1600 x 1200		
		Video Capture Resolution and Maximum		
		Framerate 15fps @ 2048x1536		
		Connectivity Micro HDMI		
		USB 2.0		
		Wi-Fi Optical System Finite-conjugate		
		Mechanical Tube Length 160mm		
		Head Trinocular, 30° incline, 360° rotatable		
		Interpupillary Adjustment 55-75mm		
		Siedentopfcompensation-free gemel		
		Ocular Diameter 23mm		
		Eyepieces 10X		
		Photo Port height-adjustable 23mm tube,		
		CX series, simul-focal		
		Objective Lenses DIN standard		
		Objective Parfocal Distance 45mm		
		Objective Mounting Thread RMS 20.32mm		
		Objective Turret quadruple		
		Focusing System Coaxial coarse and fine		
		focus, upper limit-stop, tension control		
		Focus Range 28mm		
		Division of Fine Focus 0.002mm		
		Stage Design Double-layer with caliper		
		Stage Dimensions 140mm x 132mm		
		X-Y Translation Range 76mm x 50mm		
		Transmitted Illumination 20W halogen		
		Condenser NA1.25 Abbe condenser with iris		
		diaphragm, 32mm filter holder		
		Sub-stage Condenser-holder rack and pinion		
		Power 85-265VAC 50/60Hz wide-band		
		7 0 11 00 2 00 1110 0 0 0 00112 11100 0 0 0 0 0 0 0		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Stainless Steel Bench	1	
30.		Scale, Commercial Digital Weighing Scale/Postal		
		Scale/Shipping Scale, 800×0.05lb Capacity (16"x 20")		

		With manufacturer's warranty	
	Unit	LABORATORY EQUIPMENT, Triple	1
		Deck Gas Oven, triple deck design	
		1.5" thick Cordierite decks	
		(3) 8" high decks with (3) cooking chambers	
		Throttling thermostat range from 300° to 650°	
		Independently controlled top and bottom heat dampers	
2.4		Heavy-duty, slide-out flame diverters	
31.		Spring-balanced, fully insulated doors	
		Gas controls with valve, regulator, 50 kg	
		LPG tank and pilot safety	
		Side or rear 3/4" NPT gas connection	
		6" steel legs finished with durable Bakertone	
		Stainless steel exterior	
		CE, NSF, CSA Star, CSA Flame	
		With manufacturer's warranty	
	Unit	LABORATORY EQUIPMENT, Type:	1
		Analytical Balance	
		Model: PR124-Alumin (120 grams, 0.1 milligrams),	
		PR204-Alumin (200 grams, 0.1 milligrams),	
		PR224-Alumin (220 grams, 0.1 milligrams)	
		Capacity: 120 grams, 200 grams, 220 grams	
		Resolution: 0.0001 grams	
		Minimum Weight: 0.0004 grams	
		Repeatability: plus or minus 0.0002 grams	
		Linearity: plus or minus 0.0003 grams	
32.		Stabilization Time: less than or equal to 3 seconds	
		Operating Temperature: 5 to 25 degrees Celsius	
		Draft Shield Size: 240 millimeters x 190 millimeters x	
		265 millimeters	
		Calibration Weight:100 grams, 200 grams, 200 grams	
		Options: Printer	
		Calibration: Internal Calibration	
		With manufacturer's warranty	

	Unit	LABORATORY EQUIPMENT, Type:	1	
	Oilit	Laboratory Pipette, 4 Pack starter kit,	1	
		volume range 0.5 uL to 1,000 uL,		
33.		, , , , , , , , , , , , , , , , , , , ,		
		Single Channel		
		3.1.8.1		
		With manufacturer's warranty		
	Unit	LABORATORY EQUIPMENT, Water DO	1	
		meter,		
		Measures Dissolved oxygen, with		
		datalogger feature; with spare probes;		
		Rugged, IP67-rated housing for plant and field applications; USB and RS-232 output		
		for up to 500 data sets; 500 hours battery life,		
34.		or optional universal power adapter; Built-in		
		stand with wall mount allows for easy		
		benchtop measurement or storage; Ready		
		(stability) indicator; Smart averaging; Hold		
		function; Calibration alarm; Battery-life		
		indicator		
		With manufacturer's warranty		
	Unit	LAWN MOWER, Riding Lawn Mower	1	
		Engine: Gas or Diesel		
		Horsepower: 16-25HP		
		Fuel Capacity: 2-4 Gallons		
		Max Forward Speed: 3-5 mph		
		Max Reverse Speed: 2-3 mph		
25		Cutting Width: 30 - 64 inches		
35.		Cutting Height: 1/2 - 4 inches		
		Number of Cutting Blades: 1-4		
		_		
		Discharge Type: Fabric, Mulching, Side Discharge and		
		Rear Discharge		
		Real Discharge		
		With manufacturer's warranty		
	Unit	MACHINERY AND EQUIPMENT, 3-	1	
		Head Teaching		
		Microscope Student Teacher Version		
		Objectives: Plan		
36.		Infinity Led arrow Pointer Trinocular w/ 14		
		MP HDMI		
		Camera, Video and Photography		
		High Resolution 3.1 MegaPixel Digital		
		Camera System.		

		Complete Digital Microscopy Solution		
		Included. Capture high resolution digital		
		microscope images, 2048×1536 pixels.		
		View and record full motion live video		
		microscope images. Frame size options for		
		video mode:		
		2048X1536 (up to 11 FPS, depending on		
		PC), 1024 X 768, 640 X 480, 512 X 384.		
		Computer connected digital microscope		
		camera connects via USB2.0. Includes USB		
		cable and MS Windows software.		
		Color DSP built into camera provides sharp		
		quality color images. Image sensor size is		
		half inch.		
		Includes measuring capability with the software.		
		Eyepieces and Magnification		
		With manufacturer's warranty		
	Unit	MACHINERY AND EQUIPMENT,	1	
		Combined Forage Shredder & Chopper		
		Machine, Maximum Capacity:		
		450-600 kg/hour		
		Dimension(LxWxH): 610x 635x780mm		
		Power: 5.5-7.5Kw		
37.		No. of Hammers: 16		
		Hammer Clearance: 40-50		
		Spindle speed: 4000 rpm		
		Inlet size: 240x180mm		
		Material: Durable metal		
		Will		
	Set	With manufacturer's warranty MACHINERY AND EQUIPMENT,	1	
	501	CONVENTIONAL TOP CAGES/		
		LABORATORY ANIMAL CAGE, for		
		MICE/HAMSTER, HANG RACK		
38.		Stainless Steel with swivel castor wheels with		
		brake		
		105.1cmx42cmx155cm		
		MICE/HAMSTER		
		WITCE/TIAIVISTER		

		29cmx17cmx15cm		
		DBPC-0003 (PP)		
		COMPLETE SET: Cage body + stainless steel		
		lid cover with built-in feed hopper and hinged		
		divider + 250ml water bottle, whole set		
		25 cages and rack included		
		MATERIAL:POLYPROPYLENE		
		Made from translucent food grade plastic		
		which may be a more practical option with		
		good impact strength and heat resistance.		
		More resistant to scratches and can be		
		autoclaved up to 121 °C		
		whole set		
		25 cages and rack included		
	Linit	With manufacturer's warranty MACHINERY AND EOUIPMENT.	7	
	Unit	MACHINERY AND EQUIPMENT, Cordless Air Blower	'	
		(Bare Tool), Very powerful with an air speed		
		of 270 km/hr		
		Very versatile with four accessories		
		Compact and handy design		
		Technical data		
39.		Battery voltage 18.0 V		
37.		No-load speed 17.000 rpm		
		Max. air speed 75.0 m/s		
		Max. airflow 120.0 m ³ /h		
		Runtime Speed I : 9 min/Ah		
		Speed II: 5 min/Ah		
		Weight excl. battery 1.1 kg		
		With manufacturer's warranty		
	unit	MACHINERY AND EQUIPMENT, CRDI	2	
		Engine Fault		
		Diagnosis Training Equipment, Feature		
		CRDI (Common Rail Direct Engine)		
		Simulator Equipment which has fuel, cooling,		
40.		intake, exhaust panel so that allows		
		theoretical training and experiments.		
		Pressure gauge is attached on each range of		
		hydraulic line on A/T for circuit training of each		
		shifting process. Exhaust muffler is specially		
		Sintering process. Extraust murrer is specially		

		designed with heat-resisting paint to be maintained		
		at high temperatures up to 600? (minimum).		
		ISO9001 certified or its equivalent in manufacturing.		
		manufacturing.		
		Specification		
		Composition		
		6) CRDI Diesel Engine Assembly, 2,900cc		
		7) equipped with Automatic Transmission		
		Assembly		
		8) Injector, Fuel Filter, Fuel Tank, Fuel		
		Pump, Fuel Devices, DC 12V		
		Car Battery and alternator		
		9) Cooling System such as Radiator,		
		Overflow Tank, Relay, cooling fan		
		10) Exhaust System such as Catalytic		
		Converter,		
		Emission, Silencer		
		12) Ignition Switch (Key S/W) Anti-vibration		
		dampersand a urethane wheels		
		13) Control box, fuel tank (removable),		
		accelerator lever		
		14) molding type safety guard is installed		
		15) Battery Voltage Gauge 12DCV		
		16) Fault insertion, control panel open and		
		close feature and 3 stage PCB board mounted		
		at least Euro 4, engine		
		Wild Co.		
	Unit	With manufacturer's warranty MACHINERY AND EQUIPMENT,	2	
	Unit	MACHINERY AND EQUIPMENT, Demolition Hammer		
		/Jack Hammer, Voltage: 220-240/50Hz		
		Rated Input power: 1750-2,000W		
		Impact Energy: 41- 62 Joules		
		Impact Rate : 1,000-1300 bpm at Rated		
41.		Speed		
41.		Weight : 16.9 - 29.5 kg		
		Tool Holder : 28mm 30mm Hex Shank		
		Included Chisel Bit: 2 pcs 28mm -30mm		
		Hex Shank Service Warranty : 1 to 3 years		
		Service Warranty: 1 to 3 years		
		With manufacturer's warranty		
		** Toll illustration of warranty	l .	

42.	Unit	MACHINERY AND EQUIPMENT, Fiber Glass Telescoping Hot Stick (Hasting Tip-Lock), Lockable Length 17, 21, 25.5 ft Retractable Length 60 ft Base Diameter 2 3/16 inches Weight 3.75 kg Carrying Case C-30 With manufacturer's warranty	1	
43.	Unit	MACHINERY AND EQUIPMENT, GBH 3-28 DRE? Rotary Hammer Drill, Power Input: 800 W Max. Bit Dia.: 28 mm Max. Core Bit Dia.: 80 mm No-load Speed: 0 to 900 rpm Impact Rate: 0 to 4000 bpm Impact Force: 0 to 3.5 J Weight: 3.5 kg With manufacturer's warranty	3	
44.	Unit	MACHINERY AND EQUIPMENT, High Pressure Washer, Voltage:220-240V 60Hz Copper pump. Copper wire induction motor Input power:3000W. Max Pressure:130Bar 1850PSI Flow rate:14L/min. Soap bottle, metal spray gun, 10 m high pressure hose steel wired With manufacturer's warranty	2	
45.	Unit	MACHINERY AND EQUIPMENT, K-SML05/10/15 Motor Driven Sirens, K-SML15 features: All weather enclosed motor is ideally suited for outdoor use. This siren would be used for audible warning at refineries, oil rigs, in the event of fires and open-cast mining operations. This precision machined unit produces a powerful dual low frequency sound that is ideal for long distance signalling.	3	

		Mariana Ontant 145 dt (A) @ 1		
		Maximum Output: 145 db (A) @ 1m		
		Tones: Continuous or Wail Tone (when		
		supply is switched on/off)		
		Frequency: 560Hz		
		2.5Km effective range		
		Voltages: 400V 3 Phase		
		Motor Power: 7.5kW		
		Duty: Continuous		
		Enclosure Material: Cast Aluminium		
		Colour: Grey, other colours available		
		Operating Temperature: -20 to +40°C		
		Storage Temperature: -40 to +70°C		
		Relative Humidity: 90% at 20°C		
		Weight: 118KgK-SML15		
	.	With manufacturer's warranty		
	Unit	MACHINERY AND EQUIPMENT, On	1	
		Board Diagnostic (OBD) 2 SCANNER		
		EQUIPMENT, Android system, 8		
		inch touchscreen (at least) with link cables		
		or wireless adaptor and complete set of		
		accessories Battery		
		7700mAh (at least) supports 150+ car brands		
		worldwide from 1996-2024 car models. OBD2		
		code reader equipped with 28+ hot services		
		including Oil Reset, SAS Calibration, ABS		
		Bleeding, Injector Coding, Battery Registration,		
		Injector registration, Fault code delete, Auto		
46.		Transmission fault detection, A/C fault detection,		
		etc. support more newer car models and brands		
		from 2023 to 2024.		
		effectively works all cars for all system		
		diagnostics. It reads/clears codes, provides		
		ECU info, displays 5-in-1 Live Data,		
		performs active tests, and special functions		
		for all available modules. With a few clicks,		
		you can easily understand the vehicle's		
		condition.		
		1-year brand warranty, 12-month free		
		updates, lifetime technical support, and free		

		return and replacement policy. With product	
		certification	
		With manufacturer's warranty	
	Unit	MACHINERY AND EQUIPMENT, Plastic	1
		Shredder	
		Machine, Motor: 3 Phase, 380V, 50Hz	
		Power: 4KW-4, Double motor	
		Reducer: JL3#-15 (double) Input speed 15	
		rpm	
		Input torque: 5800Nm	
		Input shaft Ø: 50	
		Blade size: 180x15	
47.		Blade material: 9CrSi	
		Blade Qty.: 26 PCS	
		Inlet size : 600x500x300 mm	
		Outlet width: 480 mm	
		Outlet height: 200 mm	
		Machine size (LxWxH): 1540x650x1450 mm	
		Machine weight: 800kg	
		Within Weight : 600kg	
		With manufacturer's warranty	
	Unit	MACHINERY AND EQUIPMENT, PLC	1
		Training	
		System Programmable Controls (Multi-	
		Brand) Training	
		System,	
		Dimension: Height :26 inches Width: 24 inches Depth:	
		26 inches	
48.		Training Hardware Kit Height: 26 inches	
		Training Hardware Kit Width: 24 inches	
		Training Hardware Kit Widin: 24 in inches	
		Language: English	
		Software: PLC Programming Software	
		System Format: Freestanding with Cable,	
		Logic components	
		With manufacturer's warranty	
		L MACHINEDY AND EQUIDMENT	3
	Unit	MACHINERY AND EQUIPMENT,	3
49.	Unit	Potable Toilet,	3
49.	Unit	,	3

		2 Fi		
		3.Equipment:one washing basin(triangle		
		shape) and one		
		sitting toilet, one exhaust fan, one		
		light(220V60HZ),one tap ,One Shower		
		Head,4psc angle steel gasket		
		4.Weight: 110kg;		
		5.The door is 1.9m		
		6.The wall is white color .		
		7.The thickness of the angle steel is 2mm,the		
		thickness of galvanized steel plate is		
		2.75mm)		
		8. Color: white		
		With manufacturar's warments		
	Unit	With manufacturer's warranty MACHINERY AND EQUIPMENT,	6	
	Oilit	SEWING MACHINE,	0	
		20-30 Stitches		
		One-step buttonhole		
		Built-in needle threader		
		Snap-on presser feet		
		3-5-piece feed dog		
		Extra high-presser foot lift		
		Stitch selection dials		
50.		Mechanical Sewing Machine		
		Residential Use		
		Automatic Buttonholer; Needle Threading		
		System		
		220 watts		
		Shipping Dimension		
		18-25 x 15-20 x 10-15 inches		
		Shipping Weight 20.55 lbs		
		Color: Any		
		With manufacturer's warranty		
	Unit	MACHINERY AND EQUIPMENT,	1	
		SURGICAL		
		CAUTERY MACHINE, Portable		
		Electrocautery Machine		
51.		Modes in CUT - Pure, Blend		
		Modes in COAG-Contact Coag		
		Bipolar coag- standard coag		
		Microprocessor controlled		
		_		
		Handswitch and Footswitch Operation		

		Frequency - 400W		
		Minimum RF Distortion; User settable		
		program modes		
		HF Leakage current > 150mA		
		Weight: 7.5 Kg (Approx.)		
		Size: 40x20x15CM		
		Weight: Approx. 4.2KG		
		With complete accessories		
		With manufacturer's warranty		
	Unit	MACHINERY AND EQUIPMENT,	1	
		Vocational Training		
		Equipment House Fire alarm Trainer Kit, Single phase		
52.		AC220V 50hz		
32.		Minimum dimension 1500x660x1800mm		
		100kg		
		With manufacturer's warranty		
	Unit	MICROSCOPE, Binocular Microscope with	4	
		electronic eyepiece and monitor		
		360 degree adjustable binocular head,		
		ocular distance is from 55 to 75 mm		
		adjustable.		
		Coarse and fine focus knob,		
		Power and Battery Dual Supply System.		
		with up to 2000x power; Changeable wide		
		field 10x 25x eyepieces and 2x extender		
		allow you to view specimens at 40x; 80x;		
52		160x; 100x; 200x; 250x 400x; 800x 1000x		
53.		2000x etc. magnification.		
		Built-in 6 colored filters Improve the quality		
		of your magnified images.		
		with a 2.0 mp electronic eyepiece, easy to connect		
		to a computer and save images / videos or viewing		
		specimen live, with measurement / draw line		
		function, with high speed transmission software,		
		not worry about lag.		
		Specification:		
		Model: GF24B		

		Optical System: Finite Biological Microscope		
		bservation head: binocular head, 45 degree tilt, 360		
		degree rotation		
		Eyepiece: WF10X WF25X		
		Objective: 4X 10X 40X		
		Extender: 2.0X		
		Magnification: 40X-2000X		
		Working Stage :90mmX90mm Square/Moving		
		Scale/Disc Filters		
		Adjustment : Coarse Focuser & Fine		
		Focuser (dual knobs)		
		Illuminator Top/Bottom: LED Lights, Uses		
		3pcs AA batteries (Not included) or DC		
		•		
		power supply.		
		Net Weight: 1700g / 3.75lbs Item Size: 185x140x290mm		
		Helli Size: 183x140x290IIIII		
		Monitor for viewing		
		With manufacturer's warranty		
	Unit	MICROSCOPE, Specifications Binocular	2	
		Head		
		- Inclined at 30°, capable of 360° rotation		
		- Adjustable interpupillary distance: 52-75mm		
		- Rotatable eyepiece		
		- Wide field eyepiece with multiple		
		magnification options (e.g., 10x, 20x)		
		- Semi-plan achromatic and plan		
		achromatic objectives, available in various		
54.		magnifications (e.g., 4x, 10x, 20x, 40x, 60x, 100x)		
		- Infinite achromatic and plan achromatic		
		objectives- Quadruple or quintuple nosepiece for		
		backward rotation		
		- Double-layer mechanical stage:		
		140x140mm with movement controls and fine		
		adjustments		
		- Coarse and fine adjustment with precision up to 0.002mm		
		- Condenser with iris diaphragm, adjustable		
		illumination- LED or halogen illumination options		
		with adjustable brightness		

		- Attachments available for photography,	
		video, polarization, phase contrast, and dark field	
		- Fluorescent illumination capabilities	
		- Dimensions: Approx. 35cm x 31cm	
		Weight: Approx. 9.5kg	
	Unit	With manufacturer's warranty	1
	Ullit	OVEN, Capacity: 138L	1
		Temp. Range: RT 5 C to 300 C	
		Temp. Fluctuation: plus or minus 1 C	
55.		Power Supply: 2500W, AC220V, 50Hz	
		Chamber Size: 50x50x55cm	
		Package Size: 90x76x98cm	
		G. Weight:115kg	
	** *	With manufacturer's warranty	4
	Unit	PRESSURE WASHER, Power Cleaning Machine	1
		20 Inches stainless steel floor cleaner	
		Stainless steel handle	
56.		2pcs nozzle	
		13hp Gasoline Motor	
		250bar 3600psi pressure	
		Complete set of water gun with 20 meters	
		high pressure hose With manufacturer's warranty	
	Unit	REFRIGERATOR, laboratory refrigerator	1
	Omt	"Cu. Ft.: 30	1
		Door(s): Single Glass, Locking Temperature Range: 2°C to 8°C (36°F to	
		46°F)	
		Exterior Dimensions: 33.85?W x 37.80?D x	
		81.12?H	
		Interior Dimensions: 27.50?W x 30.80?D x	
57.		61.84?H Alarm: Audible and visual high and	
		low temperature alarms	
		Shelves: 4 adjustable shelves, sliding	
		Keyed Door Lock	
		Electrical Requirements: 115V, 60Hz; 6	
		amps	
		UL/cUL 61010-1 listed	
		Shipping Weight: 471 lbs.	
		With manufacturer's warranty	
58.	Set	ROBOTICS V5, Robotics Portable	1
50.		Competition Field	

		Perimeter & Tiles Kit		
		Specifications:		
		(16) T Connectors (4) Center Panels,		
		(8) Corner Connectors (2) Straps,		
		(4) Side Extrusions (2) Field Cases,		
		(4) Center Extrusions (2) Field Tile Cases,		
		(4) Left Extrusions,		
		(8) Vertical Center Extrusions,		
		4) Vertical Corner Extrusions,		
		(12) GPS Code Extrusions,		
		(8) Side Panels,		
		With manufacturer's warranty		
59.	Unit	WEIGHING SCALE, Digital Weighing Balance minimum display value" 0.01g; minimum weighing capacity: minimum-maximum: .0002-10mg;; with calibration weights; power supply: AC adapter or dry cell	1	
		With manufacturer's warranty		
	Unit	WELDING MACHINE, TIG Welding	1	
		Machine (Best Use for Aluminum): Ampere:		
		250A		
		Voltage: 220V		
60.		Input Power: 6.0Kw		
		No Load Voltage: 56V		
		Weight: 9Kg		
		With manufacturer's warranty		

[Use this form for Framework Agreement:]

Framework Agreement List

Limited to repeatedly required goods and services that are identified to be necessary and desirable, but, by its nature, use or characteristic, the quantity and/ or exact time of need cannot be accurately pre-determined and are not advisable to be carried in stock.

Prepared by the End-User, attached to the APP and submitted to the BAC for the approval of the HOPE.

Item / Service Type and nature of each item/service	Cost per item or service	Maximum Quantity	Total Cost per Item
TOTAL (Approved Budget for the Contract)			
Expected delivery timeframe after receipt of a Call-Off.	Within [no. of days] ca	lendar days upon issuance o	of Call-off .
Remarks	Indicate here any other necessary.	appropriate information as	may be

SIGNATURE OVER PRINTED NAME	POSITION	DEPARTMENT/DIVISION

Section VII. Technical Specifications

Notes for Preparing the Technical Specifications

A set of precise and clear specifications is a prerequisite for Bidders to respond realistically and competitively to the requirements of the Procuring Entity without qualifying their Bids. In the context of Competitive Bidding, the specifications (*e.g.* production/delivery schedule, manpower requirements, and after-sales service/parts, descriptions of the lots or items) must be prepared to permit the widest possible competition and, at the same time, present a clear statement of the required standards of workmanship, materials, and performance of the goods and services to be procured. Only if this is done will the objectives of transparency, equity, efficiency, fairness, and economy in procurement be realized, responsiveness of bids be ensured, and the subsequent task of bid evaluation and post-qualification facilitated. The specifications should require that all items, materials and accessories to be included or incorporated in the goods be new, unused, and of the most recent or current models, and that they include or incorporate all recent improvements in design and materials unless otherwise provided in the Contract.

Samples of specifications from previous similar procurements are useful in this respect. The use of metric units is encouraged. Depending on the complexity of the goods and the repetitiveness of the type of procurement, it may be advantageous to standardize the General Technical Specifications and incorporate them in a separate subsection. The General Technical Specifications should cover all classes of workmanship, materials, and equipment commonly involved in manufacturing similar goods. Deletions or addenda should then adapt the General Technical Specifications to the particular procurement.

Care must be taken in drafting specifications to ensure that they are not restrictive. In the specification of standards for equipment, materials, and workmanship, recognized Philippine and international standards should be used as much as possible. Where other particular standards are used, whether national standards or other standards, the specifications should state that equipment, materials, and workmanship that meet other authoritative standards, and which ensure at least a substantially equal quality than the standards mentioned, will also be acceptable. The following clause may be inserted in the Special Conditions of Contract or the Technical Specifications.

Sample Clause: Equivalency of Standards and Codes

Wherever reference is made in the Technical Specifications to specific standards and codes to be met by the goods and materials to be furnished or tested, the provisions of the latest edition or revision of the relevant standards and codes shall apply, unless otherwise expressly stated in the Contract. Where such standards and codes are national or relate to a particular country or region,

other authoritative standards that ensure substantial equivalence to the standards and codes specified will be acceptable.

Reference to brand name and catalogue number should be avoided as far as possible; where unavoidable they should always be followed by the words "or at least equivalent." References to brand names cannot be used when the funding source is the GOP.

Where appropriate, drawings, including site plans as required, may be furnished by the Procuring Entity with the Bidding Documents. Similarly, the Supplier may be requested to provide drawings or samples either with its Bid or for prior review by the Procuring Entity during contract execution.

Bidders are also required, as part of the technical specifications, to complete their statement of compliance demonstrating how the items comply with the specification.

Technical Specifications

	Specification	Statement of Compliance
		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each
		Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and crossreferenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]
1.	AUTOCLAVE, Laboratory Autoclave Class N autoclave sterilizer, vertical type volume: 100L Bolted digital display automatic control Sterilization temperature: 116 to 134C Design pressure: 0.25 Mpa Automatic protection function	
	With manufacturer's warranty	

	CABINET, Dimensions: 465 X 620 X 1300	
	A durable 2 drawer steel filing cabinet able to	
	hold either A4 suspension or foolscap	
	hanging files	
2.	40kg loading capacity	
	Fully lockable	
	Anti-tilt mechanism	
	100% drawer extension on smooth	
	runners	
	With manufacturer's warranty	
	CABINET, Filing Cabinet Black- Brown/Light Brown	
	Wood type	
	Depth: 37 cm (14 5/8 ")	
	Height: 198 cm (78 ")	
3.	Width: 270 cm (106 1/4 ")	
	Bookcase	
	Glass	
	Glass-door cabinet with 3 drawers	
	With manufacturer's warranty	
	CABINET, Laminar Flow cabinet	
	ULPA Filter	
	ISO Class 3 work zone	
	DC ECM blower for up to 70 percent energy savings	
	Low noise at 55.8 dBA	
4.	Glass side walls	
	Fixed Sash	
	Internal height: 2.50 ft	
	Available sizes: 6ft	
	With manufacturer's warranty	
	DRILL, Radial drill press	
	220V, 4 KW, spindle rpm 1150,	
5.	spindle travel 420 mm, spindle feeding step16, spindle taper MT5, distance	
J.	from spindle axis to column 350-1650	
	With manufacturer's warranty	
	ENGINE, Hybrid Engine,	
	Engine Code: A25A Complete Engine	
6.	Fuel: Gasoline Doors: 5	
	Mileage: 83979	
	willcage. 037/7	

	Power: 218CV / 160KW
	With manufacturer's warranty
	FLOOR POLISHER, 16 IN. Heavy
	Duty with brush and
7.	Bracket, 230 Volts
	W/d
	With manufacturer's warranty GENERATOR, Silent type diesel
	generator generator
	Rated voltage V:220-240
	Rated frequency Hz :60
	Phase: Single
	Max output kW :9.5
	Rated output kW :8.5 Power Factor:1
8.	Rated speed rpm
	:3600
	Fuel tank L :26
	Net weight Kg :280kg
	Cooling system: Air cooled
	Starting system: Electric with
	maintenance free battery
	With manufacturer's warranty
	INCUBATOR, Laboratory Incubator
	Ventiflow Ventilation System: Forced
	air convection design
	Pre-heat Chamber Technology: 4-zone
	heated air jacket
	Smart Sense Microprocessor PID
9.	Control Technology DIN 12880 Class 3.1 Certified for
	Temperature Safety
	Electrogalvanized steel body
	construction
	Audible and visual alarms
	Available volume: 110L
	With manufacturer's warranty
	LABORATORY EQUIPMENT,
10.	Automatic Feed
10.	Pelletizer Machine, Output Capacity:
	150-180 kg/h

	Dimension (LxWxH): 38 x 12 x 26 inches
	Voltage: 220-240 v
	Motor power: 5 HP
	Die hole specification: 6 mm
	Material: Durable metal
	Emergency stop: Yes
	Emergency stop. Tes
	With manufacturer's warranty
	LABORATORY EQUIPMENT,
	Chlorophyll meter,
	Two (2) wavelength optical density difference method; Measurement area: 2 x 3mm;
	Measurement accuracy: within ±1.0SPAD;
	Memory: 30 data; Warning buzzer, with arbitrary correction function;
	Waterproof structure: IPX4;
11.	Power supply: AA alkaline dry cell x 2 pieces (included);
	Weight: 200g;
	Model number: SPAD-502 Plus;
	Display range: -9.9 to +199.9SPAD;
	Size (mm): 78 x 49 x 164;
	Accessories: Stopper, Reading
	checker, Strap, Soft case
	With manufacturer's warranty
	LABORATORY EQUIPMENT,
	Diesel engine with
	common rail intercooler Educational
	Trainer, 4 stroke engine; 4 in-line
	cylinders; 4 valves per cylinder
	Displacement: 2500/2800 cu. Cm
	Power: 150-170 hp At 4000 RPM
12.	Twin overhead camshaft (DOHC) with timing belt
	Vibration-damping balancing shafts
	Common rail-type direct injection with electro-injectors
	Turbo-supercharger with air-air
	intercooler
	Alternator-oil filter-oil pump
	With manufacturer's warranty

	LABORATORY EQUIPMENT,	
13.	Digital Salinity	
	Refractometer, Hydrometer salinity,	
	measurement and analysis instruments Size:	
	160x59x49mm	
	Weight:230g	
	Function: 0-28% ATC salinity refractometer	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT,	
	Double Door Laboratory	
	Refrigerator, Double Door Laboratory Refrigerator,	
	Shelf/drawer: Shelves/10	
	Cooling method: Forced Air Cooling	
	System	
14.	Defrost: Auto	
	Refrigerant: R290	
	Power consumption(kWh/24h): 5.8	
	Noise(db): 52	
	Ambient temperature celcius: 10~32	
	Temperature range celcius: 2~8	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT,	
	ELECTRIC MIXER,	
	Stand mixer Heavy duty mixer	
	Kneading Cream Filling Machine	
	Eggbeater Mixer Dough Commercial	
15.	dough mixer Kneading Dough	
13.	Power: 1100W	
	Voltage: 220V	
	Capacity: 15L-30L	
	Three major accessories: egg-beating cage. Clapper board. Kneading hook	
	With manufacturer's warranty LABORATORY EQUIPMENT,	
	ESPRESSO MACHINE, 1560 watts	
16.	Espresso Machine	
	Dimensions (HxWxL):	
	13.1" x 12.8" x 12.2"	
	Construction Materials: Brushed	
	Stainless Steel.	
	Bean Hopper Capacity: 1/2 lb. Water	

	Tank Capacity: 2000ml
	Voltage: 220-240 volts
	Settings: Single or Double Shots.
	Heating system: Thermocoil integrated
	stainless steel water path accurately controls
	water temperature. With pre infusion function
	that gradually increases water pressure to
	gently expand grinds for an even extraction.
	Adjustable Grind Amount & Manual
	over-ride.
	Included Accessories:
	Razor Dose Trimming Tool.
	54mm Stainless Steel Portafilter.
	1 cup & 2cup Single & Dual Wall Filter Baskets.
	Coffee Scoop.
	Integrated Tamper.
	Stainless Steel Milk Jug.
	Cleaning disc and tablets.
	Cleaning brush, tool and Allen Key.
	Water Filter Holder and Water Filter.
	With manufacturer's warranty
	LABORATORY EQUIPMENT, Feed
	Pelletizer
	Machine, With Electric Motor
	Power: 5HP Single Phase
17.	Working Load: 80-100 kg/hr
	Default Disc Mill: 3mm
	Boundary Dimension: 750 x 280 x 700mm
	700mii
	With manufacturer's warranty
	LABORATORY EQUIPMENT, Fish
	Smokehouse Oven
	Drying Smoker meat,
	Dimension: 1185x950x1960mm
18.	Capacity: 50kg/time
	Voltage: 380V 50HZ
	Power: 6kw
	With manufacturer's warranty
	With manufacturer 8 warranty

	1	
	LABORATORY EQUIPMENT, Heavy duty vacuum	
	sealing integrated machine for air	
	packaging compression and high	
	suction,	
10	Voltage power: 220V/480w	
19.	Vacuum pump: 2.0L copper core single	
	pump	
	Sealing strip size: length 32cmx 8cm	
	widex2	
	Weight: 42kg	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT,	
	Illuminated Tissue	
	Flotation Bath, Dimensions: Width 295mm x Depth	
	370mm x Height 135mm	
	Bowl: Diameter 220mm x Height	
	90mm	
	Weight: 4.5Kgs	
20.	Temperature range: 30 °C to 70 °C	
20.	Digital display: +/- 1 ^o C	
	Safety: Class 1 cut out	
	Heater power: 400 watts	
	Power Supply: Dual Voltage 220-240V	
	or 110-120V	
	50/60Hz	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT, Lab Mill/Husker,	
	Capacity: 250 grams paddy sample	
	Capacity/hr: 50 kg/hr	
	Power: 400 W (0.5 hp) single phase	
	Head Power: 1,900 RPM	
21.	Follow power: 1,000 RPM	
	Size: 720mm x 480mm x	
	1400 mm	
	Weight: 49kg	
	Power source: 220 V, 60 hz	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT,	
22.	Laboratory Electric	

	Furnace	
	Product name: Electric Furnace	
	Voltage: 110V / 220V	
	Power: 3300W	
	Maximum temperature about 1000 °C	
	Furnace net size: 16 x 16 x 17cm	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT, laboratory water tank	
	Stainless Pressure tank Water Tank 50	
	gals. with	
	JRKJET100 4HP Water Pump	
	Water Tank 50 gallons	
	Industrial	
	Stainless	
23.	Heavy Duty	
	Secured Thread Tube Fittings	
	50 Gallons or 80 Liters in Capacity	
	16 inches in diameter	
	24 inches in height	
	Frequency: 60hz	
	W'A	
	With manufacturer's warranty LABORATORY EQUIPMENT,	
	Moisture analyzer	
	(multi-crop)	
	Input voltage: 230 V AC 50 Hz	
	Weighing capacity [Max]: 200 g	
	Weighing units: % Trockenmasse g %	
	Feuchte	
24.	Maximum humidity: 80 %	
	Maximum operating temperature: 40	
	⁰ C Minimum ambient temperature: 5	
	⁰ C Minimum humidity: 5 %	
	Readability (moisture): 0.050 %	
	Tare range: 200 g	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT, Moisture analyzer,	
25.	Moisture analyzer, capacity 120g;	
	Display-LCD(backlight); AC powered	
	2.5pm, 202 (cackingin), 110 powerou	
	With manufacturer's warranty	

	LABORATORY EQUIPMENT, Multi-Test Photometer,	
	140 parameters, 18 wavelengths, 5.5	
26.	touch-display, WiFi, USB, camera,	
	Bluetooth. With complete accessories	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT,	
	Multiparameter Water	
	Quality Meter, Portable Type, pH Range	
	-2.000-20.000pH	
	Resolution 0001,0.01,0.1pH, selectable	
	Accuracy 0.002pH	
	Calibration Points 1 to 5 points	
	pH Buffer Options USA, NIST, DIN,	
	2 custom buffers	
	ORP Range ±1999.9mV	
	Resolution 0.1, 1mV, selectable	
	Accuracy ±0.2mV	
	Calibration Points 1 point	
	Ion Range 0.001~19999 (depending on	
	the range of ISE)	
	Resolution 0.001, 0.01, 0.1, 1	
27.	Accuracy ±0.5% F.S. (monovalent),	
	±1% F.S. (monovalent),	
	(divalent)	
	Measurement Units ppm, mg/L, mol/L, mmol/L	
	Calibration Paints 2 to 5 points (0.001,	
	0.01, 0.1, 1, 10,	
	100, 1000, 10000)	
	Conductivity Range 0.01~20.00,	
	200.0, 2000μS/cm, 20.00, 200.0mS/cm	
	Resolution 0001,0.01,0.1,1	
	Accuracy ±0.5% F.S.	
	Calibration Paints 1 to 5 points	
	Calibration Solutions 10µS/cm,	
	84µS/cm, 1413µS/cm,	
	12.88mS/cm, 111.8mS/cm	
	Temperature Coefficient Linear(0.0-	
	10.0%/°C) pure water	
	1	

	Reference Temperature 20/25°C
	Cell Constant K=0.1, 1, 10 or custom
	Cen Constant K=0.1, 1, 10 of Custom
	With manufacturer's warranty
	LABORATORY EQUIPMENT, Oil
	Insulation Test Kit, Features:
	Voltage Display Resolution:
	Safety Standards: Meeting IEC 61010
	Accuracy: +/- 1 Percent of FSD
	Variac: Motorized
	Shutdown sensitivity: 5mA
	Gap Gauge: 1mm /2mm / 2.5mm and 4mm
	Indications Cover Open, Wait time, HT On, KV rise, &
28.	BDV
	Weight: 40 Kg. Approx
	Dimensions: L=700 x B=320 x H=325
	mm +/- 10mm
	Humidity Range: 80 Percent Rh at 40 °C
	Temperature Range: Operating 0 - 40 $^{\circ}$ C
	Voltage Range: 0 to 60 KV AC
	Trip Current: Less than10mA
	Indication: 3 1/2 Digit Panel Meter
	Wide an english to the second
	With manufacturer's warranty LABORATORY EQUIPMENT,
	LABORATORY EQUIPMENT, Series Biological
	Trinocular Compound Microscope
	40X-1000X
	Magnification with 9.7" Touchscreen
	Imaging System,
	OS Android 4.1.1
	CPU 1.8GHz
20	Memory 2GB (DDR3)
29.	Internal Storage 2GB
	External Storage MicroSD (TF) 32GB max, USB
	Screen Size (diagonal) 9.7"
	Display Resolution 2048 x 1536
	Display Mount 360° rotation, 90° tilt
	Sensor Type CMOS
	Active Pixels 5M (2592 x 1944)
	Shutter electronic rolling shutter

	Photo Capture Resolution 2592 x 1944	
	2048 x 1536	
	1600 x 1200	
	Video Capture Resolution and	
	Maximum	
	Framerate 15fps @ 2048x1536	
	Connectivity Micro HDMI	
	USB 2.0	
	Wi-Fi Optical System Finite-conjugate	
	Mechanical Tube Length 160mm	
	Head Trinocular, 30° incline, 360° rotatable	
	Interpupillary Adjustment 55-75mm	
	Siedentopfcompensation-free gemel	
	Ocular Diameter 23mm	
	Eyepieces 10X	
	Photo Port height-adjustable 23mm	
	tube, CX series, simul-focal	
	Objective Lenses DIN standard	
	Objective Parfocal Distance 45mm	
	Objective Mounting Thread RMS 20.32mm	
	Objective Turret quadruple	
	Focusing System Coaxial coarse and	
	fine focus, upper limit-stop, tension	
	control	
	Focus Range 28mm	
	Division of Fine Focus 0.002mm	
	Stage Design Double-layer with caliper	
	Stage Dimensions 140mm x 132mm	
	X-Y Translation Range 76mm x 50mm	
	Transmitted Illumination 20W halogen	
	Condenser NA1.25 Abbe condenser	
	with iris diaphragm, 32mm filter holder	
	Sub-stage Condenser-holder rack and pinion	
	Power 85-265VAC 50/60Hz wideband	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT,	
20	Stainless Steel Bench	
30.	Scale, Commercial Digital Weighing Scale/Postal	

	Scale/Shipping Scale, 800×0.05lb	
	Capacity (16"x 20")	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT,	
	Triple Deck Gas Oven, triple deck	
	design	
	1.5" thick Cordierite decks	
	(3) 8" high decks with (3) cooking	
	chambers Throttling thermostet range from 200°	
	Throttling thermostat range from 300° to 650°	
	Independently controlled top and	
	bottom heat dampers	
31.	Heavy-duty, slide-out flame diverters	
	Spring-balanced, fully insulated doors	
	Gas controls with valve, regulator, 50	
	kg LPG tank and pilot safety	
	Side or rear 3/4" NPT gas connection	
	6" steel legs finished with durable	
	Bakertone	
	Stainless steel exterior	
	CE, NSF, CSA Star, CSA Flame	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT, Type:	
	Analytical Balance	
	Model: PR124-Alumin (120 grams, 0.1	
	milligrams),	
	PR204-Alumin (200 grams, 0.1 milligrams),	
	PR224-Alumin (220 grams, 0.1	
	milligrams)	
22	Capacity: 120 grams, 200 grams, 220	
32.	grams	
	Resolution: 0.0001 grams	
	Minimum Weight: 0.0004 grams	
	Repeatability: plus or minus 0.0002 grams	
	Linearity: plus or minus 0.0003 grams	
	Stabilization Time: less than or equal to	
	3 seconds	
	Operating Temperature: 5 to 25	
	degrees Celsius	

	Draft Shield Size: 240 millimeters x 190 millimeters x	
	265 millimeters	
	Calibration Weight:100 grams, 200 grams, 200 grams	
	Options: Printer	
	Calibration: Internal Calibration	
	With manufacturer's warranty	
	LABORATORY EQUIPMENT, Type:	
	Laboratory Pipette, 4 Pack starter kit, volume range 0.5 uL to 1,000 uL,	
33.		
	Single Channel	
	W/4l	
	With manufacturer's warranty LABORATORY EQUIPMENT,	
	LABORATORY EQUIPMENT, Water DO meter,	
	Measures Dissolved oxygen, with	
	datalogger feature; with spare probes;	
	Rugged, IP67-rated housing for plant	
	and field applications; USB and RS-	
	232 output for up to 500 data sets; 500 hours battery life, or optional universal	
34.	power adapter; Built-in stand with wall	
	mount allows for easy benchtop	
	measurement or storage; Ready	
	(stability) indicator; Smart averaging;	
	Hold function; Calibration alarm; Battery-life indicator	
	Battery-fire indicator	
	With manufacturer's warranty	
	LAWN MOWER, Riding Lawn	
	Mower	
	Engine: Gas or Diesel	
	Horsepower: 16-25HP	
	Fuel Capacity: 2-4 Gallons	
	Max Forward Speed: 3-5 mph	
35.	Max Reverse Speed: 2-3 mph	
33.	Cutting Width: 30 - 64 inches	
	Cutting Height: 1/2 - 4 inches	
	Number of Cutting Blades: 1-4	
	Discharge Type: Fabric, Mulching, Side Discharge and	
	Rear Discharge	
	Real Discharge	
1	With manufacturer's warranty	

	MACHINERY AND EQUIPMENT, 3-Head Teaching	
	Microscope Student Teacher Version Objectives: Plan	
	Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI	
	Camera, Video and Photography	
	High Resolution 3.1 MegaPixel Digital Camera System.	
	Complete Digital Microscopy Solution	
	Included. Capture high resolution	
	digital microscope images, 2048×1536	
	pixels.	
	View and record full motion live video	
	microscope images. Frame size options	
	for video mode:	
36.	2048X1536 (up to 11 FPS, depending	
	on PC), 1024 X 768, 640 X 480, 512 X	
	384.	
	Computer connected digital	
	microscope camera connects via	
	USB2.0. Includes USB cable and MS	
	Windows software.	
	Color DSP built into camera provides	
	sharp quality color images. Image	
	sensor size is half inch.	
	Includes measuring capability with the software.	
	Eyepieces and Magnification	
	With manufacturer's warranty	
	MACHINERY AND EQUIPMENT,	
	Combined Forage Shredder & Chopper	
	Machine, Maximum Capacity:	
	450-600 kg/hour	
	Dimension(LxWxH): 610x 635x780mm	
37.	Power: 5.5-7.5Kw	
	No. of Hammers: 16	
	Hammer Clearance: 40-50	
	Spindle speed: 4000 rpm	
	Inlet size: 240x180mm	
	Material: Durable metal	

	With manufacturer's warranty	
	MACHINERY AND EQUIPMENT,	_
	CONVENTIONAL TOP CAGES/	
	LABORATORY ANIMAL CAGE, for	
	MICE/HAMSTER, HANG RACK	
	Stainless Steel with swivel castor wheels	
	with brake	
	105.1cmx42cmx155cm	
	MICE/HAMSTER	
	29cmx17cmx15cm	
	DBPC-0003 (PP)	
	COMPLETE SET: Cage body +	
	stainless steel lid cover with built-in	
	feed hopper and hinged divider + 250ml	
38.		
	water bottle, whole set	
	25 cages and rack included	
	MATERIAL:POLYPROPYLENE Mode from translation food grade	
	Made from translucent food grade	
	plastic which may be a more practical	
	option with good impact strength and	
	heat resistance. More resistant to	
	scratches and can be autoclaved up to	
	121 °C	
	whole set	
	25 cages and rack included	
	With manufacturer's warranty	
	MACHINERY AND EQUIPMENT,	
	Cordless Air Blower	
	(Bare Tool), Very powerful with an air	
	speed of 270 km/hr	
	Very versatile with four accessories	
	Compact and handy design	
39.	Technical data	
J7.	Battery voltage 18.0 V	
	No-load speed 17.000 rpm	
	Max. air speed 75.0 m/s	
	Max. airflow 120.0 m ³ /h	
	Runtime Speed I : 9 min/Ah	
	Speed II: 5 min/Ah	
	Weight excl. battery 1.1 kg	

MACHINERY AND EQUIPMENT, CRDI Engine Fault Diagnosis Training Equipment, Feature CRDI (Common Rail Direct Engine) Simulator Equipment which has fuel, cooling, intake, exhaust panel so that allows theoretical training and experiments. Pressure gauge is attached on each range of hydraulic line on A/T for circuit training of each shifting process. Exhaust muffler is		
CRDI Engine Fault Diagnosis Training Equipment, Feature CRDI (Common Rail Direct Engine) Simulator Equipment which has fuel, cooling, intake, exhaust panel so that allows theoretical training and experiments. Pressure gauge is attached on each range of hydraulic line on A/T for circuit training of		
Feature CRDI (Common Rail Direct Engine) Simulator Equipment which has fuel, cooling, intake, exhaust panel so that allows theoretical training and experiments. Pressure gauge is attached on each range of hydraulic line on A/T for circuit training of		
CRDI (Common Rail Direct Engine) Simulator Equipment which has fuel, cooling, intake, exhaust panel so that allows theoretical training and experiments. Pressure gauge is attached on each range of hydraulic line on A/T for circuit training of		
Simulator Equipment which has fuel, cooling, intake, exhaust panel so that allows theoretical training and experiments. Pressure gauge is attached on each range of hydraulic line on A/T for circuit training of		
cooling, intake, exhaust panel so that allows theoretical training and experiments. Pressure gauge is attached on each range of hydraulic line on A/T for circuit training of		
allows theoretical training and experiments. Pressure gauge is attached on each range of hydraulic line on A/T for circuit training of		
experiments. Pressure gauge is attached on each range of hydraulic line on A/T for circuit training of		
Pressure gauge is attached on each range of hydraulic line on A/T for circuit training of		
hydraulic line on A/T for circuit training of		
cach shifting process. Exhaust mutiler is		
specially designed with heat-resisting paint to		
manufacturing.		
•		
•		
2,900cc		
12) equipped with Automatic		
•		
Devices, DC 12V		
Car Battery and alternator		
14) Cooling System such as Radiator,		
Overflow Tank,Relay, cooling fan		
15) Exhaust System such as Catalytic		
•		
accelerator lever		
19) molding type safety guard is		
C I C 12 11 1E C 1 C 1 C I a 1 ii	Specification Composition 1) CRDI Diesel Engine Assembly, 2,900cc 2) equipped with Automatic Transmission Assembly 3) Injector, Fuel Filter, Fuel Tank, Fuel Pump, Fuel Devices, DC 12V Car Battery and alternator 4) Cooling System such as Radiator, Overflow Tank, Relay, cooling fan 5) Exhaust System such as Catalytic Converter, Emission, Silencer 17) Ignition Switch (Key S/W) Antivibration dampersand a urethane wheels 18) Control box, fuel tank (removable), accelerator lever	be maintained at high temperatures up to 600? minimum). SO9001 certified or its equivalent in manufacturing. Specification Composition 1) CRDI Diesel Engine Assembly, 2,900cc 2) equipped with Automatic Fransmission Assembly 3) Injector, Fuel Filter, Fuel Tank, Fuel Pump, Fuel Devices, DC 12V Car Battery and alternator 4) Cooling System such as Radiator, Dverflow Tank,Relay, cooling fan 15) Exhaust System such as Catalytic Converter, Emission, Silencer 17) Ignition Switch (Key S/W) Anti- ribration dampersand a urethane wheels 18) Control box, fuel tank (removable), accelerator lever 19) molding type safety guard is nstalled

	21) Fault insertion, control panel open	
	and close feature and 3 stage PCB board	
	mounted	
	at least Euro 4, engine	
	With manufacturer's warranty	
	MACHINERY AND EQUIPMENT,	
	Demolition Hammer	
	/Jack Hammer, Voltage: 220-240/50Hz	
	Rated Input power: 1750-2,000W	
	Impact Energy: 41- 62 Joules	
	Impact Rate : 1,000-1300 bpm at Rated Speed	
41.	Weight : 16.9 - 29.5 kg	
	Tool Holder : 28mm 30mm Hex Shank	
	Included Chisel Bit: 2 pcs 28mm - 30mm Hex Shank	
	Service Warranty: 1 to 3 years	
	, ,	
	With manufacturer's warranty	
	MACHINERY AND EQUIPMENT,	
	Fiber Glass	
	Telescoping Hot Stick (Hasting Tip-Lock), Lockable	
	Length 17, 21, 25.5 ft	
42.	Retractable Length 60 ft	
12.	Base Diameter 2 3/16 inches	
	Weight 3.75 kg	
	Carrying Case C-30	
	With manufacturer's warranty	
	MACHINERY AND EQUIPMENT, GBH 3-28 DRE ?	
43.	Rotary Hammer Drill, Power Input: 800 W	
	Max. Bit Dia. : 28 mm	
	Max. Core Bit Dia.: 80 mm	
	No-load Speed: 0 to 900 rpm	
	Impact Rate: 0 to 4000 bpm	
	Impact Force: 0 to 3.5 J	
	Weight: 3.5 kg	
	W'AC .t	
	With manufacturer's warranty	

	MACHINERY AND EQUIPMENT,	
	High Pressure	
	Washer, Voltage:220-240V 60Hz	
	Copper pump. Copper wire induction	
	motor	
44.	Input power:3000W. Max Pressure:130Bar 1850PSI Flow	
	Pressure:130Bar 1850PSI Flow rate:14L/min. Soap bottle, metal spray	
	gun, 10 m high pressure hose steel	
	wired	
	With manufacturer's warranty	
	MACHINERY AND EQUIPMENT, K-SML05/10/15	
	Motor Driven Sirens, K-SML15	
	features: All weather enclosed motor is	
	ideally suited for outdoor use. This	
	siren would be used for audible	
	warning at refineries, oil rigs, in the	
	event of fires and open-cast mining	
	operations. This precision machined	
	unit produces a powerful dual low	
	frequency sound that is ideal for long	
	distance signalling.	
	Maximum Output: 145 db (A) @ 1m	
45.	Tones: Continuous or Wail Tone	
	(when supply is switched on/off)	
	Frequency: 560Hz	
	2.5Km effective range	
	Voltages: 400V 3 Phase	
	Motor Power: 7.5kW	
	Duty: Continuous Enclosure Material: Cast Aluminium	
	Colour: Grey, other colours available	
	Operating Temperature: -20 to +40°C	
	Storage Temperature: -40 to +70°C	
	Relative Humidity: 90% at 20°C	
	Weight: 118KgK-SML15	
	With manufacturer's warranty	
46.	MACHINERY AND EQUIPMENT,	
40.	On Board Diagnostic (OBD) 2	

SCANNER EQUIPMENT, Android system, 8

inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery

7700mAh (at least) supports 150+ car brands worldwide from 1996-2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding, Battery Registration, Injector registration, Fault code delete, Auto Transmission fault detection, A/C fault detection, etc. support more newer car models and brands from 2023 to 2024.

effectively works all cars for all system diagnostics. It reads/clears codes, provides ECU info, displays 5-in-1 Live Data, performs active tests, and special functions for all available modules. With a few clicks, you can easily understand the vehicle's condition.

1-year brand warranty, 12-month free updates, lifetime technical support, and free return and replacement policy. With product certification

With manufacturer's warranty

MACHINERY AND EQUIPMENT,

Plastic Shredder

Machine, Motor: 3 Phase, 380V, 50Hz

Power: 4KW-4, Double motor

Reducer : JL3#-15 (double) Input

speed 15 rpm

47.

Input torque: 5800Nm

Input shaft Ø: 50 Blade size: 180x15 Blade material: 9CrSi Blade Qty.: 26 PCS

Inlet size : 600x500x300 mm

Outlet width: 480 mm

	Outlet height : 200 mm	
	Machine size (LxWxH) :	
	1540x650x1450 mm	
	Machine weight: 800kg	
	With manufacturer's warranty	
	MACHINERY AND EQUIPMENT, PLC Training	
	System Programmable Controls	
	(Multi-Brand) Training	
	System,	
	Dimension: Height :26 inches Width: 24 inches Depth:	
	26 inches	
48.	Training Hardware Kit Height: 26 inches	
	Training Hardware Kit Width: 24 inches	
	Training Hardware Kit Depth: 24 in inches	
	Language: English	
	Software: PLC Programming Software	
	System Format: Freestanding with	
	Cable, Logic components	
	With manufacturer's warranty MACHINERY AND EQUIPMENT,	
	Potable Toilet,	
	1.Wall Panel: 50mm EPS sandwich	
	panel	
	2.Aluminum trim and flashing	
	3.Equipment:one washing	
	basin(triangle shape) and one	
	sitting toilet, one exhaust fan, one	
	light(220V60HZ),one tap ,One Shower	
49.	Head,4psc angle steel gasket	
	4.Weight: 110kg;	
	5.The door is 1.9m	
	6.The wall is white color .	
	7.The thickness of the angle steel is	
	2mm,the thickness of galvanized steel	
	plate is 2.75mm)	
	8. Color: white	
	With manufacturer's warranty	
	", In management 5 warranty	

	MACHINERY AND EQUIDITION
	MACHINERY AND EQUIPMENT, SEWING MACHINE,
	20-30 Stitches
	One-step buttonhole
	Built-in needle threader
	Snap-on presser feet
	3-5-piece feed dog
	Extra high-presser foot lift
	Stitch selection dials
50.	Mechanical Sewing Machine
	Residential Use
	Automatic Buttonholer; Needle Threading System
	220 watts
	Shipping Dimension
	18-25 x 15-20 x 10-15 inches
	Shipping Weight 20.55 lbs
	Color: Any
	With manufacturer's warranty
	MACHINERY AND EQUIPMENT,
	SURGICAL
	CAUTERY MACHINE, Portable Electrocautery
	Machine
	Modes in CUT - Pure, Blend
	Modes in COAG-Contact Coag
	Bipolar coag- standard coag
	Microprocessor controlled
	Handswitch and Footswitch Operation
51.	Frequency - 400W
	Minimum RF Distortion; User settable
	program modes
	HF Leakage current > 150mA
	Weight: 7.5 Kg (Approx.)
	Size: 40x20x15CM
	Weight: Approx. 4.2KG
	With complete accessories
	With manufacturer's warranty
	MACHINERY AND EQUIPMENT, Vocational Training
52.	Equipment House Fire alarm Trainer
	Kit, Single phase
	AC220V 50hz

	Minimum	
	Minimum dimension 1500x660x1800mm 100kg	
	1500A000A1000HHH 100Kg	
	With manufacturer's warranty	
	MICROSCOPE, Binocular	
	,	
	Microscope with electronic eyepiece	
	and monitor	
	360 degree adjustable binocular head,	
	ocular distance is from 55 to 75 mm	
	adjustable.	
	Coarse and fine focus knob,	
	Power and Battery Dual Supply	
	System. with up to 2000x power;	
	Changeable wide field 10x 25x	
	eyepieces and 2x extender allow you to	
	view specimens at 40x; 80x; 160x;	
	100x; 200x; 250x 400x; 800x 1000x	
	2000x etc. magnification.	
	Built-in 6 colored filters Improve the	
	quality of your magnified images.	
	with a 2.0 mp electronic eyepiece, easy to	
53.	connect to a computer and save images /	
55.	videos or viewing specimen live, with	
	measurement / draw line function, with high	
	speed transmission software, not worry about	
	lag.	
	Specification:	
	Model: GF24B	
	Optical System: Finite Biological	
	Microscope bservation head: binocular head,	
	45 degree tilt, 360 degree rotation	
	Eyepiece: WF10X WF25X	
	Objective: 4X 10X 40X	
	Extender: 2.0X	
	Magnification: 40X-2000X	
	Working Stage :90mmX90mm	
	Square/Moving	
	Scale/Disc Filters	
	Adjustment : Coarse Focuser & Fine	
	Focuser (dual knobs)	

	Illuminator Top/Bottom: LED Lights,	
	Uses 3pcs AA batteries (Not included)	
	or DC power supply.	
	Net Weight: 1700g / 3.75lbs	
	Item Size: 185x140x290mm	
	Monitor for viewing	
	With manufacturer's warranty	
	MICROSCOPE, Specifications	
	Binocular Head	
	- Inclined at 30°, capable of 360°	
	rotation	
	- Adjustable interpupillary distance: 52-75mm	
	- Rotatable eyepiece	
	- Wide field eyepiece with multiple	
	magnification options (e.g., 10x, 20x)	
	- Semi-plan achromatic and plan	
	achromatic objectives, available in various	
	magnifications (e.g., 4x, 10x, 20x, 40x, 60x,	
	100x)	
	- Infinite achromatic and plan	
	achromatic objectives- Quadruple or	
54.	quintuple nosepiece for backward rotation	
54.	- Double-layer mechanical stage:	
	140x140mm with movement controls and	
	fine adjustments	
	- Coarse and fine adjustment with	
	precision up to 0.002mm	
	- Condenser with iris diaphragm,	
	adjustable illumination- LED or halogen	
	illumination options with adjustable	
	brightness	
	- Attachments available for	
	photography, video, polarization, phase	
	contrast, and dark field	
	- Fluorescent illumination capabilities	
	- Dimensions: Approx. 35cm x 31cm	
	Weight: Approx. 9.5kg	
	With manufacturer's warranty	
	OVEN, Capacity: 138L	
55.	Temp. Range: RT 5 C to 300 C	
	Temp. Fluctuation: plus or minus 1 C	

	Power Supply: 2500W, AC220V,	
	50Hz	
	Chamber Size: 50x50x55cm	
	Package Size: 90x76x98cm	
	G. Weight:115kg	
	With manufacturer's warranty	
	PRESSURE WASHER, Power Cleaning Machine	
	20 Inches stainless steel floor cleaner	
	Stainless steel handle	
56.	2pcs nozzle	
50.	13hp Gasoline Motor	
	250bar 3600psi pressure	
	Complete set of water gun with 20 meters high pressure hose	
	With manufacturer's warranty	
	REFRIGERATOR, laboratory	
	refrigerator	
	"Cu. Ft.: 30	
	Door(s): Single Glass, Locking	
	Temperature Range: 2°C to 8°C (36°F to 46°F)	
	Exterior Dimensions: 33.85?W x 37.80?D x 81.12?H	
	Interior Dimensions: 27.50?W x	
57.	30.80?D x 61.84?H Alarm: Audible	
37.	and visual high and low temperature	
	alarms	
	Shelves: 4 adjustable shelves, sliding	
	Keyed Door Lock	
	Electrical Requirements: 115V, 60Hz;	
	6 amps	
	UL/cUL 61010-1 listed	
	Shipping Weight: 471 lbs.	
	With manufacturer's warranty	
	ROBOTICS V5, Robotics Portable	
	Competition Field	
	Perimeter & Tiles Kit	
	Specifications:	
_	(16) T Connectors (4) Center Panels,	
58.	(8) Corner Connectors (2) Straps,	
	(4) Side Extrusions (2) Field Cases,	
	(4) Center Extrusions (2) Field Tile	
	Cases,	
	(4) Left Extrusions,	

	(8) Vertical Center Extrusions,	
	4) Vertical Corner Extrusions,	
	(12) GPS Code Extrusions,	
	(8) Side Panels,	
	With manufacturer's warranty	
59.	WEIGHING SCALE, Digital Weighing Balance minimum display value" 0.01g; minimum weighing capacity: minimum-maximum: .0002-10mg;; with calibration weights; power supply: AC adapter or dry cell	
	With manufacturer's warranty	
	WELDING MACHINE, TIG Welding	
	Machine (Best Use for Aluminum):	
	Ampere: 250A	
	Voltage: 220V	
60.	Input Power: 6.0Kw	
	No Load Voltage: 56V	
	Weight: 9Kg	
	With manufacturer's warranty	

BILL OF QUANTITIES

Name of Project : Project 2025-1E: Supply and Delivery of Various

Laboratory Equipment and Machinery for the University

Location : Bayombong and Bambang Campus

Mode of Implementation : Public Bidding

Source of Fund : F101

Number of Calendar Days

to Complete : 30 Calendar Days

Approved Budget for the

Contract : 10,184,886.92

Item No.	Particulars	Qty	Unit of Measurement	Unit Cost	Total Cost
1.	AUTOCLAVE, Laboratory Autoclave	1	Unit	50,000.00	50,000.00
	Class N autoclave sterilizer,				
	vertical type volume: 100L				
	Bolted digital display automatic control				
	Sterilization temperature: 116 to 134C				
	Design pressure: 0.25 Mpa				
	Automatic protection function				
	With manufacturer's warranty				
2.	CABINET, Dimensions: 465 X 620 X 1300	1	Piece	50,000.00	50,000.00
	A durable 2 drawer steel filing				
	cabinet able to hold either A4				
	suspension or foolscap hanging files				
	40kg loading capacity				
	Fully lockable				
	Anti-tilt mechanism				
	100% drawer extension on smooth runners With manufacturer's warranty				
3.	CABINET, Filing Cabinet Black- Brown/Light Brown	1	Piece	65,000.00	65,000.00
	Wood type				
	Depth: 37 cm (14 5/8 ")				
	Height: 198 cm (78 ")				
	Width: 270 cm (106 1/4 ")				

	Bookcase	1			
	Glass				
	Glass-door cabinet with 3 drawers				
,	With manufacturer's warranty				
	CABINET, Laminar Flow cabinet ULPA Filter	2	Unit	80,000.00	160,000.00
	ISO Class 3 work zone				
	DC ECM blower for up to 70 percent energy savings				
	Low noise at 55.8 dBA				
	Glass side walls				
	Fixed Sash				
	Internal height: 2.50 ft				
	Available sizes: 6ft				
	With manufacturer's warranty				
	DRILL, Radial drill press	1	Unit	154,000.00	154,000.00
	220V, 4 KW, spindle rpm 1150,			10 1,000.00	101,000.00
	spindle travel 420 mm, spindle				
	feeding step16, spindle taper				
	MT5, distance from spindle axis to column 350-1650				
	axis to column 550-1650				
,	With manufacturer's warranty				
6.	ENGINE, Hybrid Engine,	1	Unit	229,274.32	229,274.32
	Engine Code: A25A Complete				
	Engine				
	Fuel: Gasoline				
	Doors: 5				
	Mileage: 83979				
	Power: 218CV / 160KW				
	With manufacturer's warranty				
	FLOOR POLISHER, 16 IN.	4	Unit	53,678.90	214,715.60
	Heavy Duty with brush and				
	Bracket, 230 Volts				
	With manufacturer's warranty				
	GENERATOR, Silent type diesel generator	3	Unit	79,637.50	238,912.50

	Rated voltage V :220-240				
	Rated frequency Hz :60				
	Phase: Single				
	Max output kW :9.5				
	Rated output kW :8.5				
	Power Factor:1				
	Rated speed				
	rpm :3600				
	Fuel tank L :26				
	Net weight Kg :280kg				
	Cooling system: Air cooled Starting system: Electric with maintenance free battery				
	With manufacturer's warranty				
9.	INCUBATOR, Laboratory Incubator	2	Unit	70,000.00	140,000.00
	Ventiflow Ventilation System:				
	Forced air convection design				
	Pre-heat Chamber				
	Technology: 4-zone heated air				
	jacket				
	Smart Sense Microprocessor				
	PID Control Technology				
	DIN 12880 Class 3.1 Certified				
	for Temperature Safety				
	Electrogalvanized steel body construction				
	Audible and visual alarms				
	Available volume: 110L				
	With manufacturer's warranty				
10.	LABORATORY EQUIPMENT,	1	Unit	90,000.00	90,000.00
	Automatic Feed				
	Pelletizer Machine, Output Capacity: 150-180 kg/h				
	Dimension (LxWxH): 38 x 12 x 26 inches				
	Voltage: 220-240 v				
	Motor power: 5 HP				
	Die hole specification: 6 mm				
	Die noie specification. U IIIII				

	Material: Durable metal				
	Emergency stop: Yes				
	With manufacturer's warranty				
11.	LABORATORY EQUIPMENT, Chlorophyll meter,	1	Unit	95,000.00	95,000.00
	Two (2) wavelength optical density difference method; Measurement area: 2 x 3mm;				
	Measurement accuracy: within ±1.0SPAD;				
	Memory: 30 data; Warning buzzer, with arbitrary correction function;				
	Waterproof structure: IPX4; Power supply: AA alkaline dry cell x 2 pieces (included);				
	Weight: 200g;				
	Model number: SPAD-502 Plus;				
	Display range: -9.9 to +199.9SPAD;				
	Size (mm): 78 x 49 x 164;				
	Accessories: Stopper, Reading checker, Strap, Soft case				
	With manufacturer's warranty				
12.	LABORATORY EQUIPMENT, Diesel engine with	1	Unit	97,000.00	97,000.00
	common rail intercooler				
	Educational Trainer, 4 stroke				
	engine; 4 in-line cylinders; 4				
	valves per cylinder				
	Displacement: 2500/2800 cu. Cm				
	Power: 150-170 hp At 4000 RPM				
	Twin overhead camshaft (DOHC) with timing belt				
	Vibration-damping balancing shafts				

	Common rail-type direct injection with electro-injectors				
	Turbo-supercharger with air-				
	air intercooler				
	Alternator-oil filter-oil pump				
	With manufacturer's warranty				
13.	LABORATORY EQUIPMENT, Digital Salinity	2	Unit	50,000.00	100,000.00
	Refractometer, Hydrometer				
	salinity, measurement and analysis				
	instruments Size: 160x59x49mm				
	Weight:230g				
	Function : 0-28% ATC salinity refractometer				
	With manufacturer's warranty				
14.	LABORATORY EQUIPMENT, Double Door Laboratory	1	Unit	150,000.00	150,000.00
	Refrigerator, Double Door Laboratory Refrigerator,				
	Shelf/drawer: Shelves/10				
	Cooling method: Forced Air Cooling System				
	Defrost: Auto				
	Refrigerant: R290				
	Power				
	consumption(kWh/24h): 5.8 Noise(db): 52				
	Ambient temperature celcius: 10~32				
	Temperature range celcius: 2~8				
15.	With manufacturer's warranty	4	IIn:t	FO 000 00	200 000 00
15.	LABORATORY EQUIPMENT, ELECTRIC MIXER,	4	Unit	50,000.00	200,000.00
	Stand mixer Heavy duty mixer				
	Kneading Cream Filling				
	Machine Eggbeater Mixer				
	Dough Commercial dough				
	mixer Kneading Dough				

	Power: 1100W				
	Voltage: 220V				
	Capacity: 15L-30L				
	Three major accessories: egg-				
	beating cage. Clapper board.				
	Kneading hook				
	VAY:-th				
16.	With manufacturer's warranty LABORATORY EQUIPMENT,	1	Unit	71,000.00	71,000.00
200	ESPRESSO MACHINE, 1560	1		7 1,000.00	7 1,000.00
	watts Espresso Machine				
	Dimensions (HxWxL):				
	13.1" x 12.8" x 12.2"				
	Construction Materials: Brushed				
	Stainless Steel.				
	Bean Hopper Capacity:1/2 lb.				
	Water				
	Tank Capacity: 2000ml				
	Voltage: 220-240 volts				
	Settings: Single or Double Shots.				
	Heating system: Thermocoil				
	integrated stainless steel water path				
	accurately controls water				
	temperature. With pre infusion				
	function that gradually increases				
	water pressure to gently expand				
	grinds for an even extraction.				
	Adjustable Grind Amount &				
	Manual over-ride.				
	Included Accessories:				
	Razor Dose Trimming Tool. 54mm Stainless Steel				
	Portafilter.				
	1 cup & 2cup Single & Dual				
	Wall Filter Baskets.				
	Coffee Scoop.				
	Integrated Tamper.				
	Stainless Steel Milk Jug.				

Cleaning disc and tablets. Cleaning brush, tool and Allen Key. Water Filter Holder and Water Filter. With manufacturer's warranty 17. LABORATORY EQUIPMENT, 1 Unit 150,000.00 1 Feed Pelletizer	150,000.00
Key. Water Filter Holder and Water Filter. With manufacturer's warranty 17. LABORATORY EQUIPMENT, 1 Unit 150,000.00 1	150,000.00
Filter. With manufacturer's warranty 17. LABORATORY EQUIPMENT, 1 Unit 150,000.00 1	150,000.00
With manufacturer's warranty 17. LABORATORY EQUIPMENT, 1 Unit 150,000.00 1	150,000.00
17. LABORATORY EQUIPMENT, 1 Unit 150,000.00 1	150,000.00
17. LABORATORY EQUIPMENT, 1 Unit 150,000.00 1	150,000.00
Machine, With Electric Motor	
Power: 5HP Single Phase	
Working Load: 80-100 kg/hr	
Default Disc Mill: 3mm	
Boundary Dimension: 750 x	
280 x 700mm	
VAV: 41- va a va a Carta va a	
With manufacturer's warranty 18. LABORATORY EQUIPMENT, 1 Unit 342,000.00 3	342,000.00
Fish Smokehouse Oven	342,000.00
Drying Smoker meat,	
Dimension:	
1185x950x1960mm	
Capacity: 50kg/time	
Voltage: 380V 50HZ	
Power: 6kw	
With manufacturer's warranty	
	60,000.00
Heavy duty vacuum	
sealing integrated machine for	
air packaging compression and	
high suction,	
Voltage power: 220V/480w	
Vacuum pump: 2.0L copper core single pump	
Sealing strip size: length 32cmx 8cm widex2	
Weight: 42kg	
Mith manufactures da successor	
With manufacturer's warranty 20. LABORATORY EQUIPMENT, 1 Unit 100,000.00 1	100,000.00
Illuminated Tissue	100,000.00

	Flotation Bath, Dimensions: Width 295mm x Depth				
	370mm x Height 135mm				
	Bowl: Diameter 220mm x Height 90mm				
	Weight: 4.5Kgs				
	Temperature range: 30 °C to 70 °C				
	Digital display: +/- 1 ⁰ C				
	Safety: Class 1 cut out				
	Heater power: 400 watts				
	Power Supply: Dual Voltage 220-240V or 110-120V				
	50/60Hz				
	With manufacturer's warranty				
21.	LABORATORY EQUIPMENT, Lab Mill/Husker,	1	Unit	100,000.00	100,000.00
	Capacity: 250 grams paddy sample				
	Capacity/hr: 50 kg/hr				
	Power: 400 W (0.5 hp) single phase				
	Head Power: 1,900 RPM				
	Follow power: 1,000 RPM				
	Size: 720mm x				
	480mm x 1400 mm				
	Weight: 49kg				
	Power source: 220 V, 60 hz				
	With manufacturer's warranty				
22.	LABORATORY EQUIPMENT, Laboratory Electric Furnace	1	Unit	50,000.00	50,000.00
	Product name: Electric Furnace				
	Voltage: 110V / 220V				
	Power: 3300W				
	Maximum temperature about 1000 °C Furnace net size: 16 x 16 x 17cm				
	With manufacturer's warranty				
		-			

23.	LABORATORY EQUIPMENT, laboratory water tank Stainless Pressure tank Water Tank 50 gals. with JRKJET100 4HP Water Pump Water Tank 50 gallons Industrial Stainless Heavy Duty Secured Thread Tube Fittings 50 Gallons or 80 Liters in Capacity 16 inches in diameter 24 inches in height Frequency: 60hz With manufacturer's warranty	1	Unit	50,000.00	50,000.00
24.	LABORATORY EQUIPMENT, Moisture analyzer (multi-crop) Input voltage: 230 V AC 50 Hz Weighing capacity [Max]: 200 g Weighing units: % Trockenmasse g % Feuchte Maximum humidity: 80 % Maximum operating temperature: 40 °C Minimum ambient temperature: 5 °C Minimum humidity: 5 % Readability (moisture): 0.050 % Tare range: 200 g	1	Unit	106,700.00	106,700.00
25.	LABORATORY EQUIPMENT, Moisture analyzer, Moisture analyzer, capacity 120g; Display-LCD(backlight); AC powered	1	Unit	200,000.00	200,000.00

	With manufacturer's warranty				
26.	LABORATORY EQUIPMENT, Multi-Test Photometer,	1	Unit	300,000.00	300,000.00
	140 parameters, 18				
	wavelengths, 5.5 touch-				
	display, WiFi, USB, camera,				
	Bluetooth. With complete				
	accessories				
	With manufacturer's warranty				
27.	LABORATORY EQUIPMENT,	1	Unit	60,000.00	60,000.00
	Multiparameter Water				
	Quality Meter, Portable Type,				
	pH Range				
	-2.000-20.000pH				
	Resolution 0001,0.01,0.1pH, selectable				
	Accuracy 0.002pH				
	Calibration Points 1 to 5 points				
	pH Buffer Options USA, NIST,				
	DIN, 2 custom buffers				
	ORP Range ±1999.9mV				
	Resolution 0.1, 1mV, selectable				
	Accuracy ±0.2mV				
	Calibration Points 1 point				
	Ion Range 0.001~19999				
	(depending on the range of ISE)				
	Resolution 0.001, 0.01, 0.1, 1				
	Accuracy ±0.5% F.S. (monovalent), ±1% F.S.				
	(divalent)				
	Measurement Units ppm, mg/L, mol/L, mmol/L				
	Calibration Paints 2 to 5 points (0.001, 0.01, 0.1, 1, 10,				
	100, 1000, 10000)				
	Conductivity Range				
	0.01~20.00, 200.0, 2000μS/cm,				

	20.00.200.0 0./	1			
	20.00, 200.0mS/cm				
	Resolution				
	0001,0.01,0.1,1				
	Accuracy ±0.5% F.S.				
	Calibration Paints 1 to 5 points				
	Calibration Solutions 10μS/cm, 84μS/cm, 1413μS/cm,				
	12.88mS/cm, 111.8mS/cm				
	Temperature Coefficient				
	Linear(0.0-10.0%/°C) pure				
	water				
	Reference Temperature 20/25°C				
	Cell Constant K=0.1, 1, 10 or custom				
	With manufacturer's warranty				
28.	LABORATORY EQUIPMENT,	1	Unit	78,792.00	78,792.00
	Oil Insulation Test Kit,				
	Features:				
	Voltage Display Resolution:				
	Safety Standards: Meeting IEC 61010				
	Accuracy: +/- 1 Percent of FSD				
	Variac: Motorized				
	Shutdown sensitivity: 5mA				
	Gap Gauge: 1mm /2mm / 2.5mm and 4mm				
	Indications Cover Open, Wait time, HT On, KV rise, & BDV				
	Weight: 40 Kg. Approx				
	Dimensions: L=700 x B=320 x H=325 mm +/- 10mm				
	Humidity Range: 80 Percent Rh at 40 °C				
	Temperature Range: Operating 0 - 40 °C				
	Voltage Range: 0 to 60 KV AC				
	Trip Current: Less than10mA				

	Indication: 3 1/2 Digit Panel Meter				
	Meter				
	With manufacturer's warranty				
29.	LABORATORY EQUIPMENT, Series Biological	1	Unit	100,000.00	100,000.00
	Trinocular Compound Microscope 40X-1000X				
	Magnification with 9.7" Touchscreen Imaging System,				
	OS Android 4.1.1				
	CPU 1.8GHz				
	Memory 2GB (DDR3)				
	Internal Storage 2GB				
	External Storage MicroSD (TF) 32GB max, USB				
	Screen Size (diagonal) 9.7"				
	Display Resolution 2048 x 1536				
	Display Mount 360° rotation, 90° tilt				
	Sensor Type CMOS				
	Active Pixels 5M (2592 x 1944)				
	Shutter electronic rolling shutter				
	Photo Capture Resolution 2592 x 1944				
	2048 x 1536				
	1600 x 1200				
	Video Capture Resolution and Maximum				
	Framerate 15fps @ 2048x1536				
	Connectivity Micro HDMI USB 2.0				
	Wi-Fi Optical System Finite- conjugate				
	Mechanical Tube Length 160mm				
	Head Trinocular, 30° incline, 360° rotatable				
	Interpupillary Adjustment 55-75mm				

	Siedentopfcompensation-free				
	gemel				
	Ocular Diameter 23mm				
	Eyepieces 10X				
	Photo Port height-adjustable				
	23mm tube, CX series, simul-				
	focal				
	Objective Lenses DIN standard				
	Objective Parfocal Distance 45mm				
	Objective Mounting Thread RMS 20.32mm				
	Objective Turret quadruple				
	Focusing System Coaxial				
	coarse and fine focus, upper				
	limit-stop, tension control				
	Focus Range 28mm				
	Division of Fine Focus 0.002mm				
	Stage Design Double-layer with caliper				
	Stage Dimensions 140mm x 132mm				
	X-Y Translation Range 76mm x 50mm				
	Transmitted Illumination 20W				
	halogen Condenser NA1.25				
	Abbe condenser with iris				
	diaphragm, 32mm filter holder				
	Sub-stage Condenser-holder rack and pinion				
	Power 85-265VAC 50/60Hz				
	wide-band				
	With manufacturer's warranty				
30.	LABORATORY EQUIPMENT, Stainless Steel Bench	1	Unit	50,000.00	50,000.00
	Scale, Commercial Digital Weighing Scale/Postal				
	Scale/Shipping Scale, 800×0.05lb Capacity (16"x 20")				
	•	120	•	•	•

	With manufacturer's warranty				
31.	LABORATORY EQUIPMENT,	1	Unit	180,000.00	180,000.00
	Triple Deck Gas Oven, triple				
	deck design				
	1.5" thick Cordierite decks				
	(3) 8" high decks with (3) cooking chambers				
	Throttling thermostat range from 300° to 650°				
	Independently controlled top and bottom heat dampers				
	Heavy-duty, slide-out flame diverters				
	Spring-balanced, fully insulated doors				
	Gas controls with valve,				
	regulator, 50 kg LPG tank and				
	pilot safety				
	Side or rear 3/4" NPT gas connection				
	6" steel legs finished with durable Bakertone				
	Stainless steel exterior				
	CE, NSF, CSA Star, CSA Flame				
	With manufacturer's warranty				
32.	LABORATORY EQUIPMENT, Type: Analytical Balance	1	Unit	50,000.00	50,000.00
	Model: PR124-Alumin (120 grams, 0.1 milligrams),				
	PR204-Alumin (200 grams, 0.1 milligrams),				
	PR224-Alumin (220 grams, 0.1 milligrams)				
	Capacity: 120 grams, 200 grams, 220 grams				
	Resolution: 0.0001 grams				
	Minimum Weight: 0.0004 grams				

	Τ		1		
	Repeatability: plus or minus 0.0002 grams				
	Linearity: plus or minus 0.0003 grams				
	Stabilization Time: less than or equal to 3 seconds				
	Operating Temperature: 5 to				
	25 degrees Celsius Draft Shield Size: 240				
	millimeters x 190 millimeters				
	265 millimeters				
	Calibration Weight:100 grams, 200 grams, 200 grams				
	Options: Printer				
	Calibration: Internal Calibration				
	With manufacturer's warranty				
33.	LABORATORY EQUIPMENT, Type: Laboratory Pipette, 4 Pack starter kit, volume range 0.5 uL to 1,000 uL,	1	Unit	50,000.00	50,000.00
	Single Channel				
	With manufacturer's warranty				
34.	LABORATORY EQUIPMENT, Water DO meter,	1	Unit	80,000.00	80,000.00
	Measures Dissolved oxygen,				
	with datalogger feature; with				
	spare probes; Rugged, IP67- rated housing for plant and				
	field applications; USB and RS-				
	232 output for up to 500 data				
	sets; 500 hours battery life, or optional universal power				
	optional universal power adapter; Built-in stand with				
	wall mount allows for easy				
	benchtop measurement or				
	storage; Ready (stability) indicator; Smart averaging;				
	Hold function; Calibration				
	alarm; Battery-life indicator				
	With manufacturer's warranty				

35.	LAWN MOWER, Riding Lawn Mower Engine: Gas or Diesel Horsepower: 16-25HP Fuel Capacity: 2-4 Gallons Max Forward Speed: 3-5 mph Max Reverse Speed: 2-3 mph Cutting Width: 30 - 64 inches Cutting Height: 1/2 - 4 inches Number of Cutting Blades: 1-4 Discharge Type: Fabric, Mulching, Side Discharge and Rear Discharge	1	Unit	285,000.00	285,000.00
36.	With manufacturer's warranty MACHINERY AND	1	Unit	150,000,00	150,000,00
30.	MACHINERY AND EQUIPMENT, 3-Head Teaching	1	Unit	150,000.00	150,000.00
	Microscope Student Teacher Version Objectives: Plan				
	Infinity Led arrow Pointer Trinocular w/ 14 MP HDMI				
	Camera, Video and Photography				
	High Resolution 3.1 MegaPixel Digital Camera System.				
	Complete Digital Microscopy				
	Solution Included. Capture				
	high resolution digital				
	microscope images, 2048×1536 pixels.				
	View and record full motion				
	live video microscope images.				
	Frame size options for video				
	mode:				
	2048X1536 (up to 11 FPS,				
	depending on PC), 1024 X 768,				
	640 X 480, 512 X 384.				
	Computer connected digital microscope camera connects				

	via USB2.0. Includes USB cable				
	and MS Windows software.				
	Color DSP built into camera				
	provides sharp quality color				
	images. Image sensor size is				
	half inch.				
	Includes measuring capability with the software.				
	Eyepieces and Magnification				
	With manufacturer's warranty				
37.	MACHINERY AND	1	Unit	80,000.00	80,000.00
	EQUIPMENT, Combined				
	Forage Shredder & Chopper				
	Machine, Maximum Capacity:				
	450-600 kg/hour				
	Dimension(LxWxH): 610x 635x780mm				
	Power: 5.5-7.5Kw				
	No. of Hammers: 16				
	Hammer Clearance: 40-50				
	Spindle speed: 4000 rpm				
	Inlet size: 240x180mm				
	Material: Durable metal				
	With manufacturer's warranty				
38.	MACHINERY AND EQUIPMENT,	1	Set	200,000.00	200,000.00
	CONVENTIONAL TOP CAGES/				
	LABORATORY ANIMAL CAGE, for				
	MICE/HAMSTER, HANG RACK				
	Stainless Steel with swivel				
	castor wheels with brake				
	105.1cmx42cmx155cm				
	MICE/HAMSTER				
	29cmx17cmx15cm				
	DBPC-0003 (PP)				
	COMPLETE SET: Cage body +				
	stainless steel lid cover with				

	built-in feed hopper and hinged				
	divider + 250ml water bottle,				
	whole set				
	25 cages and rack included				
	MATERIAL:POLYPROPYLENE				
	Made from translucent food				
	grade plastic which may be a				
	more practical option with				
	good impact strength and heat				
	resistance. More resistant to				
	scratches and can be				
	autoclaved up to 121 °C				
	whole set				
	25 cages and rack included				
	With manufacturer's warranty				
39.	MACHINERY AND	7	Unit	7,422.50	51,957.50
	EQUIPMENT, Cordless Air				
	Blower				
	(Bare Tool), Very powerful				
	with an air speed of 270 km/hr				
	Very versatile with four accessories				
	Compact and handy design				
	Technical data				
	Battery voltage 18.0 V				
	No-load speed 17.000 rpm				
	Max. air speed 75.0 m/s				
	Max. airflow 120.0 m ³ /h				
	Runtime Speed I: 9 min/Ah				
	Speed II: 5 min/Ah				
	Weight excl. battery 1.1 kg With manufacturer's warranty				
40.	MACHINERY AND	2	unit	210,000.00	420,000.00
	EQUIPMENT, CRDI Engine				
	Fault				
	Diagnosis Training Equipment,				
	Feature				

CRDI (Common Rail Direct		
Engine) Simulator Equipment		
which has fuel, cooling, intake,		
exhaust panel so that allows		
theoretical training and		
experiments.		
Pressure gauge is attached on each		
range of hydraulic line on A/T for		
circuit training of each shifting		
process. Exhaust muffler is specially		
designed with heat-resisting paint to		
be maintained at high temperatures		
up to 600? (minimum).		
ISO9001 certified or its		
equivalent in manufacturing.		
Specification		
Composition		
16) CRDI Diesel Engine		
Assembly, 2,900cc		
17) equipped with Automatic Transmission Assembly		
18) Injector, Fuel Filter, Fuel Tank, Fuel Pump, Fuel		
Devices, DC 12V		
Car Battery and alternator		
19) Cooling System such as		
Radiator, Overflow Tank,Relay,		
cooling fan		
20) Exhaust System such as Catalytic Converter,		
Emission, Silencer		
22) Ignition Switch (Key S/W)		
Anti-vibration dampersand a		
urethane wheels		
23) Control box, fuel tank (removable), accelerator lever		
24) molding type safety guard is installed		

	25) Battery Voltage Gauge 12DCV				
	26) Fault insertion, control panel				
	open and close feature and 3 stage				
	PCB board mounted				
	at least Euro 4, engine				
	With manufacturer's warranty				
41.	MACHINERY AND EQUIPMENT, Demolition Hammer	2	Unit	56,500.00	113,000.00
	/Jack Hammer, Voltage: 220- 240/50Hz				
	Rated Input power: 1750- 2,000W				
	Impact Energy: 41- 62 Joules				
	Impact Rate : 1,000-1300 bpm at Rated Speed				
	Weight : 16.9 - 29.5 kg				
	Tool Holder : 28mm 30mm Hex Shank				
	Included Chisel Bit : 2 pcs 28mm -30mm Hex Shank				
	Service Warranty: 1 to 3 years				
	With manufacturer's warranty				
42.	MACHINERY AND EQUIPMENT, Fiber Glass	1	Unit	85,507.00	85,507.00
	Telescoping Hot Stick (Hasting Tip-Lock) , Lockable				
	Length 17, 21, 25.5 ft				
	Retractable Length 60 ft				
	Base Diameter 2 3/16 inches				
	Weight 3.75 kg				
	Carrying Case C-30				
	With manufacturer's warranty				
43.	MACHINERY AND EQUIPMENT, GBH 3-28 DRE ?	3	Unit	18,000.00	54,000.00
	Rotary Hammer Drill, Power Input: 800 W				
	Max. Bit Dia. : 28 mm				

	Max. Core Bit Dia. : 80 mm				
	No-load Speed : 0 to 900 rpm				
	Impact Rate : 0 to 4000 bpm				
	Impact Force : 0 to 3.5 J				
	Weight: 3.5 kg				
	YAZTA C				
44.	With manufacturer's warranty MACHINERY AND	2	Unit	120,000.00	240,000.00
	EQUIPMENT, High Pressure	2		120,000.00	210,000.00
	Washer, Voltage:220-240V				
	60Hz				
	Copper pump. Copper wire induction motor				
	Input power:3000W. Max				
	Pressure:130Bar 1850PSI Flow rate:14L/min. Soap				
	bottle, metal spray gun, 10 m				
	high pressure hose steel wired				
	With manufacturer's warranty				
45.	MACHINERY AND EQUIPMENT, K-SML05/10/15	3	Unit	150,000.00	450,000.00
	Motor Driven Sirens, K-SML15				
	features: All weather enclosed				
	motor is ideally suited for				
	outdoor use. This siren would				
	be used for audible warning at				
	refineries, oil rigs, in the event				
	of fires and open-cast mining				
	operations. This precision				
	machined unit produces a				
	powerful dual low frequency				
	sound that is ideal for long				
	distance signalling.				
	Maximum Output: 145 db (A)				
	@ 1m				
	Tones: Continuous or Wail				
	Tone (when supply is switched				
	on/off)				
	Frequency: 560Hz				

Voltages: 400V 3 Phase Motor Power: 7.5kW Duty: Continuous Enclosure Material: Cast Aluminium Colour: Grey, other colours available Operating Temperature: -20 to +40°C Storage Temperature: -40 to +70°C Relative Humidity: 90% at 20°C Weight: 118KgK-SML15 With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding, Battery Registration, Injector		2.5Km effective range				
Motor Power: 7.5kW Duty: Continuous Enclosure Material: Cast Aluminium Colour: Grey, other colours available Operating Temperature: -20 to +40°C Storage Temperature: -40 to +70°C Relative Humidity: 90% at 20°C Weight: 118KgK-SML15 With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
Duty: Continuous Enclosure Material: Cast Aluminium Colour: Grey, other colours available Operating Temperature: -20 to +40°C Storage Temperature: -40 to +70°C Relative Humidity: 90% at 20°C Weight: 118KgK-SML15 With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
Enclosure Material: Cast Aluminium Colour: Grey, other colours available Operating Temperature: -20 to +40°C Storage Temperature: -40 to +70°C Relative Humidity: 90% at 20°C Weight: 118KgK-SML15 With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
Aluminium Colour: Grey, other colours available Operating Temperature: -20 to +40°C Storage Temperature: -40 to +70°C Relative Humidity: 90% at 20°C Weight: 118KgK-SML15 With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
available Operating Temperature: -20 to +40°C Storage Temperature: -40 to +70°C Relative Humidity: 90% at 20°C Weight: 118KgK-SML15 With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
+40°C Storage Temperature: -40 to +70°C Relative Humidity: 90% at 20°C Weight: 118KgK-SML15 With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,		_				
+70°C Relative Humidity: 90% at 20°C Weight: 118KgK-SML15 With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
20°C Weight: 118KgK-SML15 With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
With manufacturer's warranty 46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996-2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,		Weight: 118KgK-SML15				
46. MACHINERY AND 1 Unit 65,000.00 65,000.00 EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996-2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,		With manufacturar's warranty				
EQUIPMENT, On Board Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,	46.	-	1	Unit	65.000.00	65.000.00
Diagnostic (OBD) 2 SCANNER EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
EQUIPMENT, Android system, 8 inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
inch touchscreen (at least) with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
with link cables or wireless adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
adaptor and complete set of accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
accessories Battery 7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
7700mAh (at least) supports 150+ car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
car brands worldwide from 1996- 2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
2024 car models. OBD2 code reader equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
equipped with 28+ hot services including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
including Oil Reset, SAS Calibration, ABS Bleeding, Injector Coding,						
ABS Bleeding, Injector Coding,						
Battery Registration, Injector		ABS Bleeding, Injector Coding,				
		Battery Registration, Injector				
registration, Fault code delete, Auto		registration, Fault code delete, Auto				
Transmission fault detection, A/C		Transmission fault detection, A/C				
fault detection, etc. support more		fault detection, etc. support more				
newer car models and brands from		newer car models and brands from				
2023 to 2024.		2023 to 2024.				

47.	effectively works all cars for all system diagnostics. It reads/clears codes, provides ECU info, displays 5-in-1 Live Data, performs active tests, and special functions for all available modules. With a few clicks, you can easily understand the vehicle's condition. 1-year brand warranty, 12-month free updates, lifetime technical support, and free return and replacement policy. With product certification With manufacturer's warranty MACHINERY AND EQUIPMENT, Plastic Shredder Machine, Motor : 3 Phase, 380V, 50Hz Power : 4KW-4, Double motor Reducer : JL3#-15 (double) Input speed 15 rpm Input torque : 5800Nm Input shaft Ø: 50 Blade size : 180x15 Blade material: 9CrSi Blade Qty. : 26 PCS Inlet size : 600x500x300 mm Outlet width : 480 mm Outlet height : 200 mm Machine size (LxWxH) :	1	Unit	988,680.00	988,680.00
	Inlet size: 600x500x300 mm Outlet width: 480 mm Outlet height: 200 mm				
48.	With manufacturer's warranty MACHINERY AND EQUIPMENT, PLC Training	1	Unit	192,388.00	192,388.00

Controls Training System, Dimension: Height :26 Width: 24 inches Depth 26 inches Training Hardware Kit 26 inches Training Hardware Kit 24 inches Training Hardware Kit 24 inches Language: English Software: PLC Progra Software System Freestanding with Cabl components With manufacturer's w 49. MACHINERY EQUIPMENT, Potable T 1.Wall Panel: 50mr sandwich panel 2.Aluminum trim and file	Height: Width: Depth: mming Format: e, Logic arranty AND 3 oilet, n EPS ashing vashing nd one est fan, one tap ,One ngle steel r . e angle ness of ate is	Unit	320,000.00	960,000.00
--	--	------	------------	------------

50.	MACHINERY AND EQUIPMENT, SEWING MACHINE,	6	Unit	50,000.00	300,000.00
	20-30 Stitches				
	One-step buttonhole				
	Built-in needle threader				
	Snap-on presser feet				
	3-5-piece feed dog				
	Extra high-presser foot lift				
	Stitch selection dials				
	Mechanical Sewing Machine				
	Residential Use				
	Automatic Buttonholer; Needle Threading System				
	220 watts				
	Shipping Dimension				
	18-25 x 15-20 x 10-15 inches				
	Shipping Weight 20.55 lbs				
	Color: Any				
	With manufacturer's warranty				
51.	MACHINERY AND EQUIPMENT, SURGICAL	1	Unit	100,000.00	100,000.00
	CAUTERY MACHINE, Portable				
	Electrocautery				
	Machine				
	Modes in CUT - Pure, Blend				
	Modes in COAG-Contact Coag				
	Bipolar coag- standard coag				
	Microprocessor controlled				
	Handswitch and Footswitch Operation				
	Frequency - 400W				
	Minimum RF Distortion; User settable program modes				
	HF Leakage current > 150mA				
	Weight: 7.5 Kg (Approx.)				
	Size: 40x20x15CM				
	Weight: Approx. 4.2KG				
	With complete accessories				
	With manufacturer's warranty				

52.	MACHINERY AND EQUIPMENT, Vocational Training Equipment House Fire alarm Trainer Kit, Single phase AC220V 50hz Minimum dimension 1500x660x1800mm 100kg With manufacturer's warranty	1	Unit	180,000.00	180,000.00
53.	MICROSCOPE, Binocular Microscope with electronic eyepiece and monitor 360 degree adjustable binocular head, ocular distance is from 55 to 75 mm adjustable. Coarse and fine focus knob, Power and Battery Dual Supply System. with up to 2000x power; Changeable wide field 10x 25x eyepieces and 2x extender allow you to view specimens at 40x; 80x; 160x; 100x; 200x; 250x 400x; 800x 1000x 2000x etc. magnification. Built-in 6 colored filters Improve the quality of your magnified images. with a 2.0 mp electronic eyepiece, easy to connect to a computer and save images / videos or viewing specimen live, with measurement / draw line function, with high speed transmission software, not worry about lag.	4	Unit	50,000.00	200,000.00

	Specification:				
	Model: GF24B				
	Optical System: Finite Biological				
	Microscope bservation head:				
	binocular head, 45 degree tilt, 360				
	degree rotation				
	Eyepiece: WF10X WF25X				
	Objective: 4X 10X 40X				
	Extender: 2.0X				
	Magnification: 40X-2000X				
	Working Stage :90mmX90mm Square/Moving				
	Scale/Disc Filters				
	Adjustment : Coarse Focuser &				
	Fine Focuser (dual knobs)				
	Illuminator Top/Bottom: LED				
	Lights, Uses 3pcs AA batteries				
	(Not included) or DC power				
	supply.				
	Net Weight: 1700g / 3.75lbs				
	Item Size: 185x140x290mm				
	Monitor for viewing				
	With manufacturer's warranty				
54.	MICROSCOPE, Specifications Binocular Head	2	Unit	52,000.00	104,000.00
	- Inclined at 30°, capable of 360° rotation				
	- Adjustable interpupillary distance: 52-75mm				
	- Rotatable eyepiece				
	- Wide field eyepiece with				
	multiple magnification options (e.g.,				
	10x, 20x)				
	- Semi-plan achromatic and				
	plan achromatic objectives,				
	available in various magnifications				
	_				

	- Infinite achromatic and plan				
	achromatic objectives- Quadruple				
	or quintuple nosepiece for				
	backward rotation				
	- Double-layer mechanical				
	stage: 140x140mm with movement				
	controls and fine adjustments				
	- Coarse and fine adjustment with precision up to 0.002mm				
	- Condenser with iris				
	diaphragm, adjustable illumination-				
	LED or halogen illumination options				
	with adjustable brightness				
	- Attachments available for				
	photography, video, polarization,				
	phase contrast, and dark field				
	- Fluorescent illumination capabilities				
	- Dimensions: Approx. 35cm x				
	31cm				
	Weight: Approx. 9.5kg				
55.	With manufacturer's warranty	1	Unit	67,000.00	67,000.00
33.	OVEN, Capacity:138L Temp. Range: RT 5 C to 300 C	1	Offic	67,000.00	67,000.00
	Temp. Fluctuation: plus or				
	minus 1 C				
	Power Supply: 2500W, AC220V, 50Hz				
	Chamber Size: 50x50x55cm				
	Package Size: 90x76x98cm				
	G. Weight:115kg				
56.	With manufacturer's warranty	1	TT - *4	172 500 00	172 500 00
50.	PRESSURE WASHER, Power Cleaning Machine	1	Unit	172,500.00	172,500.00
	20 Inches stainless steel floor cleaner				
	Stainless steel handle				
	2pcs nozzle				
	13hp Gasoline Motor				
	250bar 3600psi pressure				

	Complete set of water gun with				
	20 meters high pressure hose				
	With manufacturer's warranty				
57.	REFRIGERATOR, laboratory refrigerator	1	Unit	120,000.00	120,000.00
	"Cu. Ft.: 30				
	Door(s): Single Glass, Locking				
	Temperature Range: 2°C to 8°C (36°F to 46°F)				
	Exterior Dimensions: 33.85?W x 37.80?D x 81.12?H				
	Interior Dimensions: 27.50?W				
	x 30.80?D x 61.84?H Alarm:				
	Audible and visual high and				
	low temperature alarms				
	Shelves: 4 adjustable shelves, sliding				
	Keyed Door Lock				
	Electrical Requirements: 115V, 60Hz; 6 amps				
	UL/cUL 61010-1 listed				
	Shipping Weight: 471 lbs.				
	With manufacturer's warranty				
58.	ROBOTICS V5, Robotics Portable Competition Field	1	Set	265,860.00	265,860.00
	Perimeter & Tiles Kit				
	Specifications:				
	(16) T Connectors (4) Center Panels,				
	(8) Corner Connectors (2) Straps,				
	(4) Side Extrusions (2) Field Cases,				
	(4) Center Extrusions (2) Field Tile Cases,				
	(4) Left Extrusions,				
	(8) Vertical Center Extrusions,				
	4) Vertical Corner Extrusions,				
	(12) GPS Code Extrusions,				
	(8) Side Panels,				
	With manufacturer's warranty				

59.	WEIGHING SCALE, Digital Weighing Balance minimum display value" 0.01g; minimum weighing capacity: minimum- maximum: .0002-10mg;; with calibration weights; power supply: AC adapter or dry cell With manufacturer's warranty	1	Unit	72,600.00	72,600.00
60.	WELDING MACHINE, TIG Welding Machine (Best Use for Aluminum): Ampere: 250A Voltage: 220V	1	Unit	55,000.00	55,000.00
	Input Power: 6.0Kw No Load Voltage: 56V Weight: 9Kg				
	With manufacturer's warranty				

Name of Supp	olier:		
Address	:		_
Contact Num	ber :		

Technical Specifications

	TECHNICAL SPECIFICATIONS				
Item / Service	Maximum Quantity	Technical Specifications / Scope of Work	Statement of Compliance		
			[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and crossreferenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution.]		

Section VIII. Checklist of Technical and Financial Documents

Notes on the Checklist of Technical and Financial Documents

The prescribed documents in the checklist are mandatory to be submitted in the Bid, but shall be subject to the following:

- a. GPPB Resolution No. 09-2020 on the efficient procurement measures during a State of Calamity or other similar issuances that shall allow the use of alternate documents in lieu of the mandated requirements; or
- b. Any subsequent GPPB issuances adjusting the documentary requirements after the effectivity of the adoption of the PBDs.

The BAC shall be checking the submitted documents of each Bidder against this checklist to ascertain if they are all present, using a non-discretionary "pass/fail" criterion pursuant to Section 30 of the 2016 revised IRR of RA No. 9184.

Checklist of Technical and Financial Documents

I. TECHNICAL COMPONENT ENVELOPE

Class "A" Documents

-	1.5	Cuss 11 Documents
Leg	<u>gal Do</u>	<u>cuments</u>
	(a)	Valid PhilGEPS Registration Certificate (Platinum Membership) (all pages); or
	(b)	Registration certificate from Securities and Exchange Commission (SEC), Department of Trade and Industry (DTI) for sole proprietorship, or Cooperative Development Authority (CDA) for cooperatives or its equivalent document, <u>and</u>
	(c)	Mayor's or Business permit issued by the city or municipality where the principal place of business of the prospective bidder is located, or the equivalent document for Exclusive Economic Zones or Areas; and
	(d)	Tax clearance per E.O. No. 398, s. 2005, as finally reviewed and approved by the Bureau of Internal Revenue (BIR).
Tec	chnica	l Documents
	(e)	Statement of the prospective bidder of all its ongoing government and private
	(0)	contracts, including contracts awarded but not yet started, if any, whether similar or not similar in nature and complexity to the contract to be bid; and
	(f)	Statement of the bidder's Single Largest Completed Contract (SLCC) similar to the contract to be bid, except under conditions provided for in Sections 23.4.1.3 and 23.4.2.4 of the 2016 revised IRR of RA No. 9184, within the relevant period as provided in the Bidding Documents; and
	(g)	Original copy of Bid Security. If in the form of a Surety Bond, submit also a certification issued by the Insurance Commission; <u>or</u> Original copy of Notarized Bid Securing Declaration; <u>and</u>
	(h)	Conformity with the Technical Specifications, which may include production/delivery schedule, manpower requirements, and/or aftersales/parts, if applicable; and
	(i)	Original duly signed Omnibus Sworn Statement (OSS); and if applicable, Original Notarized Secretary's Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authority to its officer to sign the OSS and do acts to represent the Bidder.
T:		I Do comments

Financial Documents

☐ (j) The Supplier's audited financial statements, showing, among others, the Supplier's total and current assets and liabilities, stamped "received" by the BIR or its duly accredited and authorized institutions, for the preceding calendar year which should not be earlier than two (2) years from the date of bid submission; **and**

		(k) The prospective bidder's computation of Net Financial Contracting Capacity (NFCC);
		or A committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation.
		Class "B" Documents
	(l) If ap	plicable, a duly signed joint venture agreement (JVA) in case the joint venture is already in existence;
		or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.
II. FIN	ANCL	AL COMPONENT ENVELOPE
	(m)	Original of duly signed and accomplished Financial Bid Form; and
	(n)	Original of duly signed and accomplished Price Schedule(s).
<u>Oti</u>	her doc	rumentary requirements under RA No. 9184 (as applicable)
		or foreign bidders claiming by reason of their country's extension of reciprocal rights to Filipinos] Certification from the relevant government office of their country stating that Filipinos are allowed to participate in government procurement activities for the same item or product. Tertification from the DTI if the Bidder claims preference as a Domestic Bidder or Domestic Entity.

ANNEX I – BIDDING FORMS

Bid Form for the Procurement of Goods

[shall be submitted with the Bid]

	BID FORM
	Date:
	Project Identification No:
To: [name and	d address of Procuring Entity]
Bulletin Numbers offer to [supply/d of [total Bid amo computational err and made part of t the applicable tax	examined the Philippine Bidding Documents (PBDs) including the Supplemental or Bid is [insert numbers], the receipt of which is hereby duly acknowledged, we, the undersigned, [leliver/perform] [description of the Goods] in conformity with the said PBDs for the sum that it words and figures] or the total calculated bid price, as evaluated and corrected for cors, and other bid modifications in accordance with the Price Schedules attached herewith this Bid. The total bid price includes the cost of all taxes, such as, but not limited to: [specify taxes, e.g. (i) value added tax (VAT), (ii) income tax, (iii) local taxes, and (iv) other fiscal dy, which are itemized herein or in the Price
If our B	id is accepted, we undertake:
	o deliver the goods in accordance with the delivery schedule specified in the Schedule of Requirements of the Philippine Bidding Documents (PBDs);
b. to	o provide a performance security in the form, amounts, and within the times prescribed in the PBDs;
	o abide by the Bid Validity Period specified in the PBDs and it shall remain binding upon us at any ime before the expiration of that period.
Commis	his paragraph if Foreign-Assisted Project with the Development Partner: sions or gratuities, if any, paid or to be paid by us to agents relating to this Bid, and to on if we are awarded the contract, are listed below:
	ress Amount and Purpose of agent nission or gratuity

Until a formal Contract is prepared and executed, this Bid, together with your written acceptance thereof and your Notice of Award, shall be binding upon us.

We understand that you are not bound to accept the Lowest Calculated Bid or any Bid you may receive.

We certify/confirm that we comply with the eligibility requirements pursuant to the PBDs.

The undersigned is authorized to submit the bid on behalf of [name of the bidder] as evidenced by the attached [state the written authority].

We acknowledge that failure to sign each and every page of this Bid Form, including the attached Schedule of Prices, shall be a ground for the rejection of our bid.

Name:	
Legal capacity:	
Signature:	
Duly authorized to sign the Bid for and behalf of:	
Date:	

Bid Securing Declaration Form

[shall be submitted with the Bid if bidder opts to provide this form of bid security]

REPUBLIC OF THE PHILIPPINES)	
CITY OF) S.S.

BID SECURING DECLARATION Project Identification No.: [Insert number]

To: [Insert name and address of the Procuring Entity]

I/We, the undersigned, declare that:

- 1. I/We understand that, according to your conditions, bids must be supported by a Bid Security, which may be in the form of a Bid Securing Declaration.
- 2. I/We accept that: (a) I/we will be automatically disqualified from bidding for any procurement contract with any procuring entity for a period of two (2) years upon receipt of your Blacklisting Order; and, (b) I/we will pay the applicable fine provided under Section 6 of the Guidelines on the Use of Bid Securing Declaration, within fifteen (15) days from receipt of the written demand by the procuring entity for the commission of acts resulting to the enforcement of the bid securing declaration under Sections 23.1(b), 34.2, 40.1 and 69.1, except 69.1(f),of the IRR of RA No. 9184; without prejudice to other legal action the government may undertake.
- 3. I/We understand that this Bid Securing Declaration shall cease to be valid on the following circumstances:
 - a. Upon expiration of the bid validity period, or any extension thereof pursuant to your request;
 - b. I am/we are declared ineligible or post-disqualified upon receipt of your notice to sucheffect, and (i) I/we failed to timely file a request for reconsideration or (ii) I/we filed a waiver to avail of said right; and
 - c. I am/we are declared the bidder with the Lowest Calculated Responsive Bid, and I/we have furnished the performance security and signed the Contract.

IN WITNESS WHEREOF, I/We have hereunto set my/our hand/s this ______day of [month] [year] at [place of execution].

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE]

[Insert signatory's legal capacity]

Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

Omnibus Sworn Statement (Revised)

[shall be submitted with the Bid]

REPUBLIC OF THE PHILIPPINES) CITY/MUNICIPALITY OF) S.S.

AFFIDAVIT

- I, [Name of Affiant], of legal age, [Civil Status], [Nationality], and residing at [Address of Affiant], after having been duly sworn in accordance with law, do hereby depose and state that:
- 1. [Select one, delete the other:]

[If a sole proprietorship:] I am the sole proprietor or authorized representative of [Name of Bidder] with office address at [address of Bidder];

[If a partnership, corporation, cooperative, or joint venture:] I am the duly authorized and designated representative of [Name of Bidder] with office address at [address of Bidder];

2. [Select one, delete the other:]

[If a sole proprietorship:] As the owner and sole proprietor, or authorized representative of [Name of Bidder], I have full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached duly notarized Special Power of Attorney;

[If a partnership, corporation, cooperative, or joint venture:] I am granted full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached [state title of attached document showing proof of authorization (e.g., duly notarized Secretary's Certificate, Board/Partnership Resolution, or Special Power of Attorney, whichever is applicable;)];

3. [Name of Bidder] is not "blacklisted" or barred from bidding by the Government of the Philippines or any of its agencies, offices, corporations, or Local Government Units, foreign government/foreign or international financing institution whose blacklisting rules have been recognized by the Government Procurement Policy Board, by itself or by relation, membership, association, affiliation, or controlling interest with another blacklisted person or entity as defined and provided for in the Uniform Guidelines on Blacklisting;

- 4. Each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information provided therein are true and correct;
- 5. [Name of Bidder] is authorized representative(s) to verify all the documents submitted;
- 6. [Select one, delete the rest:]

[If a sole proprietorship:] The owner or sole proprietor is not related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a partnership or cooperative:] None of the officers and members of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a corporation or joint venture:] None of the officers, directors, and controlling stockholders of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

- 7. [Name of Bidder] complies with existing labor laws and standards; and
- 8. *[Name of Bidder]* is aware of and has undertaken the responsibilities as a Bidder in compliance with the Philippine Bidding Documents, which includes:
 - a. Carefully examining all of the Bidding Documents;
 - b. Acknowledging all conditions, local or otherwise, affecting the implementation of the Contract:
 - c. Making an estimate of the facilities available and needed for the contract to be bid, if any; and
 - d. Inquiring or securing Supplemental/Bid Bulletin(s) issued for the [Name of the Project].
- 9. [Name of Bidder] did not give or pay directly or indirectly, any commission, amount, fee, or any form of consideration, pecuniary or otherwise, to any person or official, personnel or representative of the government in relation to any procurement project or activity.
- 10. In case advance payment was made or given, failure to perform or deliver any of the obligations and undertakings in the contract shall be sufficient grounds to constitute criminal liability for Swindling (Estafa) or the commission of fraud with unfaithfulness or abuse of confidence through misappropriating or converting any payment received by a person or entity under an obligation involving the duty to deliver certain goods or services, to the prejudice of the public and the government of the Philippines pursuant to Article 315 of Act No. 3815 s. 1930, as amended, or the Revised Penal Code.

IN WITNESS WHEREOF, I have hereunto set my hand this day of , 20 at _, Philippines.

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE]

[Insert signatory's legal capacity]

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

Price Schedule for Goods Offered from Within the Philippines

[shall be submitted with the Bid if bidder is offering goods from within the Philippines]

Name of Bidder				Project		Page of			
			1		T				
1	2	3	4	5	6	7	8	9	10
Item	Description	Country of origin	Quantity	Unit price EXW per item	Transportation and all other costs incidental to delivery, per item	Sales and other taxes payable if Contract is awarded, per item	Cost of Incidental Services, if applicable, per item	Total Price, per unit (col 5+6+7+ 8)	Total Price delivered Final Destination (col 9) x (col 4)
ame:									
ame.									
egal (Capacity: _								

STATEMENT OF SINGLE LARGEST COMPLETED CONTRACT SIMILAR TO THE CONTRACT TO BE BID

This is to certify that (company) has the following completed contracts for the period CY 2019-2021. (Note: covering 2 years up to the opening of bids)

Date of the Contract	Contracting Party	Name of Contract	Kind of Goods Sold	Amount of Contract	Date of Delivery/ End-user's Acceptance	Date of Official Receipt	Bi A) B) C)	dder is Manufactu Supplier Distributor
Date	Name a	and Signature of						
	Authori	zed Representative						

*Instructions:

- a) Cut-off date as of:
 - (i) Up to the day before the deadline of submission of bids.
- b) In the column under "Dates", indicate the dates of Delivery/ End-user's Acceptance and Official Receipt.
- c) "Name of Contract". Indicate here the Nature/ Scope of the Contract for the Procuring Entity to determine the relevance of the entry with the procurement at hand. Example: "Supply and Delivery of Generator Set"

	Statem	ent of: (i) Ongoing Co	ntracts and; (ii) Awar	ded But Not Yo	et Started Cont	racts
This is to cert	ify that	(company)	has the following ongoing ar	nd awarded but not	t yet started contra	cts:
Date of the Contract	Contracting Party	Name of Contract	Kind of Goods Sold	Amount of Contract	Value of Outstanding Contracts	Bidder is A) Manufacturer B) Supplier C) Distributor
Data	Name a	and Signature of		-1		
Date	Authori	zed Representative				

*Instructions:

- a) State <u>all</u> ongoing contracts including those awarded but not yet started (government and private contracts which may be similar or not similar to the project called for bidding) as of:
 - i. The day before the deadline of submission of bids.
- b) If there is no ongoing contract including awarded but not yet started as of the aforementioned period, state none or equivalent term.
- c) The total amount of the ongoing and awarded but not yet started contracts should be consistent with those used in the Net Financial Contracting Capacity (NFCC) in case an NFCC is submitted as an eligibility document.
- d) "Name of Contract". Indicate here the Nature/ Scope of the Contract for easier tracking of the entries/ representations. Example: "Supply and Delivery of Generator Se

Contract Agreement Form for the Procurement of Goods (Revised)

[Not required to be submitted with the Bid, but it shall be submitted within ten (10) days after receiving the Notice of Award]

CONTRACT AGREEMENT

THIS AGREEMENT made the	day of	20	between [name of	
PROCURING ENTITY] of the Philippines	(hereinafter c	alled "the Entity")	of the one part and	[name
of Supplier] of [city and country of Supplier	r] (hereinafter	called "the Suppl	ier") of the other par	t;

WHEREAS, the Entity invited Bids for certain goods and ancillary services, particularly [brief description of goods and services] and has accepted a Bid by the Supplier for the supply of those goods and services in the sum of [contract price in words and figures in specified currency] (hereinafter called "the Contract Price").

NOW THIS AGREEMENT WITNESSETH AS FOLLOWS:

- 1. In this Agreement words and expressions shall have the same meanings as are respectively assigned to them in the Conditions of Contract referred to.
- 2. The following documents as required by the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184 shall be deemed to form and be read and construed as integral part of this Agreement, *viz.*:
 - i. Philippine Bidding Documents (PBDs);
 - i. Schedule of Requirements;
 - ii. Technical Specifications;
 - iii. General and Special Conditions of Contract; and
 - iv. Supplemental or Bid Bulletins, if any
 - ii. Winning bidder's bid, including the Eligibility requirements, Technical and Financial Proposals, and all other documents or statements submitted;

Bid form, including all the documents/statements contained in the Bidder's bidding envelopes, as annexes, and all other documents submitted (*e.g.*, Bidder's response to request for clarifications on the bid), including corrections to the bid, if any, resulting from the Procuring Entity's bid evaluation;

- iii. Performance Security;
- iv. Notice of Award of Contract; and the Bidder's conforme thereto; and
- v. Other contract documents that may be required by existing laws and/or the Procuring Entity concerned in the PBDs. Winning bidder agrees that additional contract documents or information prescribed by the GPPB that are subsequently required for submission after the contract execution, such as the Notice to Proceed, Variation Orders, and Warranty Security, shall likewise form part of the Contract.

- 3. In consideration for the sum of [total contract price in words and figures] or such other sums as may be ascertained, [Named of the bidder] agrees to [state the object of the contract] in accordance with his/her/its Bid.
- 4. The [Name of the procuring entity] agrees to pay the above-mentioned sum in accordance with the terms of the Bidding.

IN WITNESS whereof the parties hereto have caused this Agreement to be executed in accordance with the laws of the Republic of the Philippines on the day and year first above written.

[Insert Name and Signature] [Insert Name and Signature]

[Insert Signatory's Legal Capacity] [Insert Signatory's Legal Capacity]

for: for:

[Insert Procuring Entity] [Insert Name of Supplier]

Acknowledgment

[Format shall be based on the latest Rules on Notarial Practice]

